Town of Granby is inviting you to a scheduled Zoom meeting.

Join Zoom Meeting

https://us02web.zoom.us/j/87283025080?pwd=F6Ks2Ejfkn8tDfVSyRnXa59soLbsOZ.1

Meeting ID: 872 8302 5080

Passcode: 666822

CAPITAL PROGRAM PRIORITY ADVISORY COMMITTEE REGULAR MEETING MONDAY, OCTOBER 6, 2025 – 5 p.m. TOWN HALL MEETING ROOM 5:00 P.M.

AGENDA

- 1. Pledge Of Allegiance
- 2. Minutes
 - 2.I. Approval Of CPPAC Regular Meeting Minutes December 2, 2024

Documents:

CPPAC MINUTES 12022024.PDF

- 3. Public Comment
- 4. Appointments
 - 4.I. None
- 5. Communications
 - 5.I. Town Manager's 10-Year Capital Plan Report Compilation Background
 - 5.II. Town Bonding Process Overview Capital Thresholds And Bonding Timeframes

Documents:

10 YEAR CAPITAL PLAN DOCS FOR CPPAC COMP.PDF

- 6. New Business
 - 6.I. Board Of Education Presentation Capital Priorities

Documents:

GRANBY FIELDS MASTER BUDGET (1) COND.PDF
GRANBY TURF FIELD 2025 (1).PDF
GRANBY MEMORIAL HS - TRACK FIELD NEW OPTIONS - BUDGET.PDF
07.2025 TRACK GEOTECHNICAL REPORT.PDF

7. Adjournment

TOWN OF GRANBY CAPITAL PROGRAM PRIORITY ADVISORY COMMITTEE SPECIAL MEETING MINUTES DECEMBER 2, 2024

PRESENT: Margaret Chapple, Board of Selectmen; Kevin Hobson, Board of Finance; William Kennedy, Board of Finance; Heather Lombardo, Board of Education; Mark Neumann, Board of Selectmen and David Peling, Board of Education

EX OFFICIO MEMBERS PRESENT: John Adams, Treasurer; Cheri Burke, Superintendent of Schools; Mark Fiorentino, First Selectman; Michael Guarco, Chairman, Board of Finance; Monica Logan, Chairman, Board of Education and Mike Walsh, Town Manager

I. CALL TO ORDER

The meeting was called to order by temporary chairman Mark Fiorentino at 5:00 p.m.

II. APPROVAL OF MEETING MINUTES FROM FEBRUARY 27, 2019, MEETING ON A MOTION by M. Neumann, seconded by M. Chapple, the committee voted (6-0-0) to approve the meeting minutes of February 27, 2019.

ON A MOTION by M. Neumann, seconded by D. Peling, the committee voted (6-0-0) to reorder the agenda to move Business item #8 to after Business item #4.

III. BUSINESS

a. Swear in Committee Members

The Capital Program Priority Advisory Committee members were sworn in by Town Clerk Scott Nolan.

b. Elect A Chair, Vice-Chair and Secretary

ON A MOTION by M. Neumann, seconded by D. Peling, the committee voted (6-0-0) to nominate Kevin Hobson as the Chairman of the Capital Program Priority Advisory Committee.

ON A MOTION by M. Neumann, seconded by M. Chapple, the committee voted (6-0-0) to nominate William Kennedy as the Vice-Chairman of the Capital Program Priority Advisory Committee.

ON A MOTION by K. Hobson, seconded by M. Chapple, the committee voted (6-0-0) to nominate Mark Neumann as the Secretary of the Capital Program Priority Advisory Committee.

c. Adopt Roberts Rules of Order

ON A MOTION by K. Hobson, seconded by M. Neumann, the committee voted (6-0-0) to adopt Robert's Rules of Order for meetings of the Capital Program Priorities Advisory Committee.

d. Set/Adopt Meeting Dates and Times

The committee agreed to meet regularly on the first and fourth Mondays of each month from 5:0 p.m. to 7:00 p.m.

e. Solar Placement on Town Buildings/Property – Identification/Selection Approval

A presentation on the potential use of solar power in Granby was presented to the committee to determine if the committee supported exploring the project further through the Connecticut Green Bank to reduce energy costs through renewable energy. After discussion, the committee agreed the project should move forward to the next phase with a limited scope on the type and location of panels.

f. Develop Definition of a Capital Improvement

ON A MOTION by M. Neumann, seconded by W. Kennedy, the committee voted (6-0-0) to adopt the following criteria for items to be eligible for inclusion in the capital improvement program:

- 1. Capital improvement items are included if the improvement cost is greater than \$10,000 and the life of the improvement is more than five (5) years.
- 2. Capital equipment items are included if the equipment cost includes items costing more than \$5,000 in 2025. All such items are required to be inventoried and depreciated.

The remainder of the agenda items under Business were deferred to the next meeting in the interest of time.

IV. PUBLIC SESSION

None

V. SCHEDULE NEXT MEETING

The next meeting of the Capital Program Priority Advisory Committee has not been scheduled.

VI. ADJOURNMENT

ON A MOTION by M. Neumann, seconded by W. Kennedy, the committee voted (6-0-0) to adjourn the meeting at 6:42 p.m.

Respectfully submitted,

aggette

Betsy Mazzotta Recording Secretary



MEMORANDUM

DATE: September 30, 2025

<u>TO:</u>

The Capital Program Priority Advisory Committee Members (CPPAC)

FROM:

Mike Walsh, Town Manager

REGARDING:

Transmittal of the 10-Year Town and BOE Capital Plan to CPPAC

As you may recall, since mid-2024, the Town and Board of Education have been working to compile one capital plan list. More recently, a draft 10-Year Town and Board Capital Plan with a transmittal memo dated May 13, 2025 (see attached) identifying Town and Board Capital priorities was provided to the Board of Selectmen (BOS) for their review.

After their initial review of the draft plan, the BOS requested a number of edits to the plan which were completed over the summer.

At the recent September Board of Education (BOE) meeting, the BOE section of the capital plan was approved. Additionally, at the most recent Board of Selectmen Meeting, the entire plan was approved and referred to CPPAC.

Accordingly, based on the action taken by the Board of Selectmen, attached please find the updated 10-Year Capital Plan for the Town of Granby, including the BOE's capital needs. I have also attached a "shortened" list of capital items over \$250,000.

This \$250,000 threshold separates small capital items that are traditionally handled as part of the annual General Fund budget appropriation from large capital items that are periodically considered for bonding.

This shortened list will allow CPPAC to focus their efforts on the priority items over \$250,000 as the next bond initiative to present to voters for approval is sized and timed.

Several other reference documents that may be helpful as these documents are reviewed are included as follows:

- 1. A summary of the renovation items identified by the Cossitt Building Needs Report
- 2. An August 14th memo from Parks and Recreation Board Chair Anthony McGovern identifying their capital priorities for investment in the parks
- 3. A July 16th transmittal of the Master Park Study, including all identified capital items

I will be on hand to answer any questions you may have on these materials. Thank you.



MEMORANDUM

DATE: May 13, 2025

TO:

The Granby Board of Selectmen

FROM:

Mike Walsh, Town Manager

REGARDING:

Town of Granby Town and BOE 10-Year Capital Plan Approval

Please accept the Town of Granby's 10-Year Capital Plan for the Town and Board of Education. The Town Capital Plan totals \$36,279,000 while the Board of Education Capital Plan totals \$33,518,325, for a grand total of \$69,797,325.

These documents are being provided to you for the purpose of communicating the plan and related priorities so that the Board of Selectmen can approve the list consistent with Town of Granby Charter, Chapter 10-2, Section (d).

The capital priorities of each organization are detailed below:

The Town of Granby Capital Priorities:

Sewer Pump/Infrastructure Replacement	\$250,000
Bridge Replacement/Inspection Program	\$2.6 million
(Exclusive of State Reimbursement)	
3. Rolling Stock (PD and PW continued regular replacement)	\$650,000
4. GAA 2 nd Ambulance Replacement	\$122,500
5. RIP – Annual Road Improvement Program	\$1.1 million
6. Public Library Expansion Discussion	\$4.0 million

The Town of Granby Board of Education Capital Priorities:

District Safety and Security Program	\$ 1.2 million
GMHS Turf Track and Field replacement	\$ 4.0 million
3. GMMS Renovate to New	\$ TBD
4. Board of Education Building Roof Replacement	\$100,000
5. District Facility Storage	\$200,000

Based on the process the Town has traditionally followed, once the Board of Selectmen approve of the attached list, they will be forwarded to the CPPAC for further review and discussion.

I will be on hand at your meeting to answer any questions you may have on the documents or the process. Thank you.



TOWN OF GRANBY CAPITAL IMPROVEMENT PLAN POLICY DISCUSSION

Forward

The Town of Granby Charter, Section 10-2 - Finance and Taxation, outlines the duties of the Town Manager on the Budget, and in particular on the Town's capital improvement projects as follows:

"d. As a part of the annual budget or as a separate report attached thereto, the Town Manager shall present a program concerning proposed Town Capital improvement projects (municipal and school) for the ensuing fiscal year and for the four fiscal years thereafter. The Town Manager shall recommend to the Board of Selectmen those projects to be undertaken during the ensuing fiscal years and method of financing the same. The proposed municipal and school capital projects shall be analyzed jointly by the Board of Selectmen, Board of Finance, Board of Education or representatives thereof and other appropriate officials to evaluate for timing and budget impact of the proposed projects."

Ten-Year Capital Improvement Plan (CIP)

Consistent with the Granby Town Charter Section 10-2 (d) above, the Town Manager, after consultation with the Superintendent of Schools, and as part of the annual budget process, compile a Ten-Year Capital Improvement Plan (CIP).

The CIP list shall be separated between Town and Board of Education items. All listed items will be prioritized with the highest priority items being placed in year one, and lower priority items placed in succeeding years.

Additionally, each individual list shall be further separated between Large Capital Improvement items and Small Capital Improvement items. Those items with a cost of \$250,000 and above shall be classified as Large Capital Improvement items and those items with a cost below \$250,000 shall be classified as Small Capital Improvement items.

Capital Program Priority Advisory Committee (CPPAC) - Membership

On April 14, 1984, the Board of Selectmen of the Town of Granby created the Capital Program Priority Advisory Committee (CPPAC) for the purpose of:

- 1. Developing a definition of a Capital Improvement
- 2. Developing criteria for prioritizing Capital Improvement Projects
- 3. Recommending a Capital Improvement Program schedule to the Board of Selectmen.

The CPPAC committee structure includes two members from the Board of Selectmen, Board of Finance, and Board of Education, with one member from each political party, plus the Town Treasurer. These seven members of CPPAC are voting members

Additionally, Ex-Officio members include the chairs of each of those committees, the Town Manager, and the School Superintendent. Ex-Officio members are non-voting members of CPPAC.

Moving forward on an annual basis, the continued work of CPPAC will serve the Town in an advisory role during the budget process.

Funding Capital Improvement Items - Which Financial Vehicle is Used?

Bonding (used to address "Large Capital Improvement items")

Granby bonds for large capital items approximately once every seven years to maintain financial flexibility and stability.

The Town of Granby comparatively has low bonded indebtedness with about \$13 million of outstanding debt as of June 30, 2024. The debt is layered from three bond issues with each having annual debt service of about \$600 thousand per year, or \$1.8 million in total. The Town of Granby usually issues debt over a 20-year life.

The Town desires to keep debt service stable at around \$1.8 million annually. One of the bond issues is fully paid after FY26 allowing \$600 thousand of debt service be programmed to fund debt service for new capital priorities.

2026 will be the "7th year" and a bonding opportunity will present itself to the Town and BOE. A bond of some amount will likely be considered, subject to voter approval.

CPPAC will work to identify capital priorities with some variation of priorities being the High School running track (\$4 million) the Middle School code renovation (\$5 million) and the Library expansion (\$4 million).

The Town will also consider sewer pump replacements and a pickleball facility at Salmon Brook Park outside of the above bond as the cost of those items will be paid from the Sewer and Parks and Recreation Funds, respectively.

CPPAC and/or the community could change these priorities and amounts as the process unfolds.

Generally speaking, the Town of Granby issues bonds to address "Large Capital Improvement items" that can't be easily or efficiently addressed with other financing means. Using the threshold provided above, moving forward, Large Capital Improvement items will be those with a cost at or above \$250,000.

General Fund Appropriation (used to address "Small Capital Improvement items")
The Town of Granby historically has embedded cash into each annual budget to provide a source of funds to allow for the funding of necessary capital improvement items that

have historically been called "a Small Cap item".

In FY25, the Town and Board of Education (BOE) have "cash" in the amount of \$377,000 and \$625,000, respectively available to use on "Small Capital Improvement items". Using the threshold provided above, moving forward, Small Capital Improvement items will be those with a cost below \$250,000.

Beginning in FY26, the Town and BOE will work to begin the process of identifying Small Capital Improvement items that more appropriately belong in the operating budget. The process to budget them in the appropriate department by transferring them out of the Small Capital Improvement funding line will more accurately present the annual operating budget.

Beginning in FY26, capital improvement items where cash is to be considered a funding source include the following types of items:

- 1. Road resurfacing including, but not limited to, road milling and overlays
- 2. Building improvements or equipment where the value is less than \$250,000

Leasing

The Town of Granby historically has used tax exempt capital leasing as a method to fund certain capital improvement items. These items have also historically been called "a Small Cap item" with the leases being placed generally having a 4-year repayment schedule for capital items like public works trucks, various equipment, police vehicles, school computers, school buses, and a variety of other capital items.

Beginning in FY26, leases issued by the Town will be limited to vehicles and equipment using in the operation of the Town.

Also beginning in FY26, a 10-year Capital Improvement plan will be approved by the Board of Selectmen along with a tax-exempt lease resolution to allow for a capital equipment lease to be placed with a lease company or bank.

Further, the Town budget book will detail a schedule of leases issued by year with the accompanying payment schedule detailing the annual town obligation to each bank/lease company.

Capital Fund

The Town of Granby provides for the use of a Capital Fund. Unlike the General Fund which begins on July 1 and ends on June 30 (a fiscal year/12-month period), the Capital Fund is project based and begins when a project is funded and ends when a project is completed.

Capital Lease payments on prior capital purchases should be budgeted and paid from the annual operating General Fund budget and not passed through the Capital Fund.

The Capital Fund has no end date for budgetary purposes allowing funds to be contributed from different fiscal years and different funding sources in order to be accurately accounted for until the project is completed.

Using a Capital Fund is an important budgetary and management tool to maintain control over a complex capital project that may span several years, administrations, and employees.

Periodic reporting, like quarterly, should be made the Board of Selectmen and Board of Finance for transparency purposes.

The Accompanying 10-Year Capital Plan Worksheet

The attached Town of Granby Capital Improvement Plan for the Fiscal Years 2027 through 2036 is a working document and will regularly change to represent the ongoing assessment of both the condition of all capital items as well as the changing replacement priority based on need and the Town's ability to judiciously fund the plan.

Summary of Proposed Library Expansion Project October 6, 2025

Situation on the Ground

The Granby Public Library does not have enough space to adequately provide library services to the community. Both the Director of Library Services (Library Director) and the Granby Library Board (Library Board) agree that the space situation at the library needs to be addressed with an expansion.

Background Work

The Library Director and the Library Board have worked cooperatively compiling expansion plans, using ARPA funding to pay for an architect to explore various sized expansion options and preliminary cost estimates.

Those options can be quantified as follows:

- 1. \$7 million marked improvement, but short of State recommended standards.
- 2. \$10 million even greater improvement, and meets State recommended standards.

The Town's Financial Situation

Granby is a very small town with above average taxes that historically has made good financial decisions to place us on a solid financial footing. However, Granby bonds for large capital items approximately once every seven years to maintain financial flexibility and stability.

2026 will be the "7th year" and a bonding opportunity will present itself to the Town and BOE. A bond of a maximum of \$13 million will likely be considered, subject to voter approval. CPPAC will work to identify capital priorities with some variation of priorities being the High School running track (\$4 million) the Middle School code renovation (\$5 million) and the Library expansion (\$4 million).

The Town will also consider sewer pump replacements and a pickleball facility at Salmon Brook Park outside of the above bond as the cost of those items will be paid from the Sewer and Parks and Recreation Funds, respectively.

CPPAC and/or the community could change these priorities and amounts as the process unfolds.

The Current Library Expansion Recommendation

After much work, thought, discussion, and consideration, the Board of Selectmen (BOS), the Library Director, and the Library Board recommend a \$7 million total library expansion for the voters to consider.

Because the Library expansion renovation is budgeted at \$7 million with \$4 million likely coming from Town bonding, a \$3 million funding gap exists.

Summary of Proposed Library Expansion Project October 6, 2025

Enter the Capital Campaign and the search for "innovative" grants. Futuristically, the expectation is the Granby Library Association will raise at least \$2 million by launching the Library Expansion Capital Campaign in the month of November, 2025.

Additionally, the Library Director will begin the search for "innovative" grants of at least \$1 million so the library expansion project can commence. Normal BOS approval prior to applying for grants is necessary.

If Fundraising and Grant Searches are More Successful

Should the capital campaign and/or the grant searches prove more successful than planned, the scope and associated cost of the library expansion may increase.

If there are Project Cost Overruns

Capital Funds must be dedicated to any cost overruns as taxpayer contribution to this project will be fixed.

Other Considerations and Cautions

- 1. The Granby Library Association will be the repository of Capital Campaign contributions.
- 2. The Town and town staff can only use Town budget funds to provide neutral project information. The Town cannot promote the library expansion with town funds.
- 3. The Friends of the Granby Public Libraries and the Granby Library Association can promote the Library expansion, but must use their own funds to do that.
- 4. The Friends of the Granby Public Libraries and the Granby Library Association must remain at arm's length from all Town of Granby Library staff on the expansion project

Ref#	Project Description	Funding Source	Estimate Confidence	Other Funding	CPPAC Recomm.	FY27
	Public Works Capital Items					
	Roads, Curbing, Sidewalks, Bridges, and Other Infrastructure					
026-001	Bridge 18 - Doherty Road - Salmon Brook - 1956	Prior Bond Initiative coupled with 50% State Grant	Good	Yes		2,300,000
026-002	Annual Road Improvement Program - subject to updated road ratings	Embedded in the Annual General Fund Appropriation	Good	No	1	1,100,000
026-003	Bridge 04517 - Silver Street - E. Salmon Brook - 1969	Reviewing the work with consultants, may go lower	Good	Yes		300,000
	Sub Total					3,700,000
	Public Works Capital Items					
	Rolling Stock				1	
026-100	Dump Truck with Plow and Sander - 6 Wheeler - Truck 4	Tax Exempt Capital Lease - Part of Annual Budget Process	Good	No		335,000
026-101	Dump Truck with Plow and Sander - 6 Wheeler - Truck 6 - FWD	Tax Exempt Capital Lease - Part of Annual Budget Process	Good	No		345,000
	Sub Total				1-	680,000
	Public Works Buildings and Infrastructure				1 - 1	
	Public Works					
026-300	Pumping Station - 166 Salmon Brook Street	Funding (Direct or Debt Service) will come from the Sewer Fund	Good	No		108,000
026-301	Pumping Station - Route 189	Funding (Direct or Debt Service) will come from the Sewer Fund	Good	No		87,000
026-302	Pumping Station Generator - 166 Salmon Brook Street	Funding (Direct or Debt Service) will come from the Sewer Fund	Good	No		54,000
	Sub Total	CPPAC to make an amount and timeline recommendation			>>>>>>	249,000
	Public Works Buildings and Infrastructure				-	
	Library Department					
2026-400	Main Library Expansion	CPPAC to make an amount and timeline recommendation	Good	Yes	>>>>>>	7,000,000
	Sub Total				7-1	7,000,000
	Public Works Buildings and Infrastructure					
	Community Services (Senior, Youth, Parks and Recreation)					
2026-500	Parks Master Plan - SBP - Route 20 Path to Soccer Fields	State STEAP Grant Award with Town Match	Good	Yes		700,000
2026-501	Parks Master Plan - SBP - Pickleball Courts and relocation of Lacrosse Fields	Funding (Direct or Debt Service) will come from the P and R Fund	Good	Yes	>>>>>>	500,000
	Sub Total	CPPAC to make an amount and timeline recommendation				1,200,000
	Total Town					12,829,000
	Board of Education					
1 -	Granby Memorial High School					
2026-650	Turf/Track Field - includes excavation and recompaction Sub Total	CPPAC to make an amount and timeline recommendation	Good	Yes	>>>>>>	4,000,000
	Board of Education					
	Granby Memorial Middle School					
2026-700	Renovate to new	CPPAC to make an amount and timeline recommendation	Good	Yes	>>>>>>	20,000,000
2026-701	Renovate "in kind" (supports status quo) - no sprinklers Sub Total	CPPAC to make an amount and timeline recommendation	Good	Yes		3,100,000 23,100,000
	Board of Education				===1	
	Central Services Building				1	
2026-850	Security Initiative - Whole District (\$850k in place via Small Cap)	\$850,000 already in place via Town's Capital Fund	Good	No		1,200,000
	Sub Total	Toolean anday in place the 10th to capital 1 une	5000	140		1,200,000
	Total Board of Education					28,300,000
	Total Town and Board of Education					41,129,000

Ref#	Project Description	Funding Source	Estimate Confidence	Other Funding	Recom.	FY27	FY28	FY29	FY30 & FY31	EV32 8 EV33	EV24 EV26	TOTAL
	Public Works Capital Items							1120	1100 01 101	1132 6 1133	F134-F130	TOTAL
	Roads, Curbing, Sidewalks, Bridges, and Other Infrastructure						-					
2026-001	Bridge 18 - Doherty Road - Salmon Brook - 1956		Good	Yes	-	2.300.000		-				2.300.000
2026-002	Annual Road Improvement Program - subject to updated road ratings		Good	No	-	1,100,000	1,100,000	1,200,000	2.500.000	2,700,000	4.200,000	12,800,000
2026-003	Bridge 04517 - Silver Street - E. Salmon Brook - 1969		Good	Yes	- 3	300.000	1,100,000	1,200,000	2,000,000	-2,700,000	4,200,000	300,000
2026-004	Unidentified Culverts/Drainage		Good	No	1.60	50.000	50.000	50,000	100.000	100.000	150,000	500,000
2026-005	Curbing, Sidewalks, Other Road Related Infrastructure	1 1 11	Good	No		25,000	25,000	25,000	50.000	50,000	75,000	250,000
2026-006	Bridge Inspections		Good	Yes		15,000	15,000	15.000	30,000	30,000	45,000	150,000
2026-007	Bridge 06196 - Thornebrook Dr Higley Brook - 1990		Good	Yes		70,000	20,000	80,000	30,000	30,000	45,000	100,000
2026-008	Bridge 04518 - East Street - E. Salmon Brook - 1937		Good	Yes			20,000	80,000	1			100,000
2026-009	Town Center Study - sidewalks north side of East Granby Road		Good	Yes		-	20,000	120,000			-	120,000
2026-010	Bridge 04519 - Wells Road - E. Salmon Brook - 1956		Good	Yes	1.1			120,000	4,000,000	- 20		4,000,000
2026-011	Bridge 04523 - Simsbury Road - Bissell Brook - 1956		Good	Yes	1.21		(D)	- 3:	4,000,000			4,000,000
2026-012	Bridge 04526 - Board Hill Road - W. Salmon Brook - 1956		Good	Yes			-		4,000,000			4,000,000
2026-013	POCD - sidewalks to connect from Route 20 Parking Lot to Town Hall		Good	Yes	-				4,000,000		250,000	250,000
2026-014	Bridge 04525 - Simsbury Road - W. Salmon Brook - 1956		Good	Yes			- 3		4		230,000	
2026-015	Bridge CDOT SPN 55-144 Moosehorn 2019		Good	Yes	-		12.1				3.0	
2026-016	Bridge CDOT 055002 Griffin Road 2019		Good	Yes	-				-			
2026-017	Bridge CDOT 05010 Hungary Road 2019		Good	Yes					-	11 12		
2026-018	Bridge CDOT SPN 55-146 Donahue 2019		Good	Yes				-				-
2026-019	Bridge 04520 - East Street - Bradley Brook - 1937		Good	Yes					- 20			-
2026-020	Bridge 04521 - Mechanicsville - E. Salmon Brook - 1969		Good	Yes		2.1		-	- 1			•
2026-021	Bridge 04524 - Barn Door Hills - W. Salmon Brook - 1956		Good	Yes	1000				-		- 1	
2026-022	Bridge 04530 - Doherty Road - Carson Pond Brook - 1956		Good	Yes	1	201		-	19.	21		-
2026-023	Bridge 04531 - Meadowbrook - Bradley Brook - 1956		Good	Yes			-				- 1	
2026-024	Bridge 06197 - Northwoods Road - E. Salmon Brook - 1982		Good	Yes			7.1					-
	Sub Total		2300			3,790,000	1,230,000	1,570,000	14,680,000	2.880.000	4,720,000	28,870,000
						2,1.20,000	.,255,000	1,0,0,000	1-1,000,000	2,000,000	7,120,000	20,070,000

Ref#	Project Description	Funding Source	Estimate Confidence	Other Funding	Recom.	FY27	FY28	FY29	FY30 & FY31	EV32 & EV32	EV34 EV36	TOTAL
	Public Works Capital Items		-	- Containing	Tubbonia	1.12/	1120	1120	1100 41 131	F132 GF133	F134-F130	TOTAL
	Rolling Stock											
2026-100	Dump Truck with Plow and Sander - 6 Wheeler - Truck 4		Good	No		335,000		-		-		335.000
2026-101	Dump Truck with Plow and Sander - 6 Wheeler - Truck 6 - FWD		Good	No		345,000	-			-		345,000
2026-102			Good	No	-	160,000						160,000
2026-103	Van - Senior Transport		Good	Yes	1	100,000		141	100.000			200,000
2026-104	Dump Truck with Plow and Sander - 6 Wheeler - Truck 1		Good	No		700,000	335,000		100,000	-		335,000
2026-105	Loader - #23		Good	No		1.2	95,000	- 51		1 - 10		95,000
2026-106	Pickup Truck - Mid-size - Truck 12		Good	No			90,000			1 31		90,000
2026-107	Dump Truck with Plow and Sander - 6 Wheeler - Truck 5		Good	No	1 2		30,000	305,000	1	-		305,000
2026-108	Loader - #20		Good	No		-			750,000			750.000
2026-109	Backhoe - #22		Good	No					190,000			190,000
2026-110	Pickup Truck - Mid-size - Truck 14		Good	No				0-7	90,000			90,000
2026-111	Roller - 1 Ton - #64		Good	No	·				20,000			20,000
2026-112	Dump Truck with Plow and Sander - 6 Wheeler - Truck 17		Good	No		6.1			20,000	400,000		400,000
2026-113	Dump Truck with Plow and Sander - 6 Wheeler - Truck 18		Good	No		-			1	400,000		400,000
2026-114			Good	No		-				90,000		90,000
2026-115	Pickup Truck - Mid-size - Truck 130		Good	No					1	85,000		85,000
2026-116			Good	No						65,000		65,000
2026-117	Pickup Truck - Mid-size - Truck 15		Good	No		-				65.000		65,000
2026-118	Trailer - #38		Good	No				9.1		10,000		10,000
2026-119			Good	No						8.000		8,000
2026-120	Trailer - #37		Good	No			- :	-		8,000		8,000
2026-121	Dump Truck with Plow and Sander - 6 Wheeler - Truck 2		Good	No				-		0,000	400,000	400,000
	Dump Truck with Plow and Sander - 6 Wheeler - Truck 3		Good	No							400,000	400,000
2026-123	Sweeper - #62		Good	No				- 2			400,000	400,000
2026-124	- construction and the construction of the con		Good	No							335,000	335,000
2026-125			Good	No				-			195,000	195,000
2026-126			Good	No				/		21	145,000	145,000
2026-127	Skid steer - #8		Good	No		-	-			-	100,000	100,000
2026-128	Pickup Truck - Mid-size - Truck 16		Good	No				-			90,000	90,000
2026-129			Good	No		-	-	-			90,000	90,000
2026-130	Director vehicle		Good	No				-			65.000	65,000
2026-131	Trailer - #35		Good	No					1.5	-	65,000	65,000
2026-132			Good	No	20.	- 12	1				30,000	30,000
2026-133	Trailer - #31		Good	No		-		-		-	20,000	20,000
2026-134	Trailer - #32		Good	No		-				-	15,000	15,000
2026-135			Good	No		- :					8,000	8,000
2020-100	Sub Total		Guu	INO		940,000	520,000	305,000	1,150,000		2,358,000	
	San Iviai					340,000	520,000	305,000	1,150,000	1,131,000	2,358,000	6,404,000

Ref#	Project Description	Funding Source	Estimate Confidence	Other Funding	Recom.	FY27	FY28	FY29	FY30 & FY31	FY32 & FY33	FY34 - FY36	TOTAL
	Public Works Capital Items	9 1										
-	Operating Equipment	0 7 8 8 4		7 - 1	11	11						
2026-200	Portable Pipe Cleaner		Good	No	4.0	20,000						20,000
2026-201	Traffic Counter		Good	No		8,000			11	- (-)		8,000
2026-202	Paving Box - #39		Good	No			300,000	(4)		- 100		300,000
2026-203	Roadside Mower - #24		Good	No			125,000		21	1 - 3		125,000
2026-204	Mower - #50		Good	No		-	80,000	-		1,21	-	80,000
2026-205	Roadside Mower Head		Good	No		(2)	-2	60,000	1 20			60,000
2026-206	Mower - #51		Good	No				25,000				25,000
2026-207	Tractor - #21		Good	No	•	12.11			65,000		11	65,000
2026-208	Portable welder/generator - #48	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	Good	No		-			5,000	19-1		5,000
2026-209	Screening Plant - #28		Good	No	121		140			40,000	- 1	40,000
2026-210	Mower - #52		Good	No	3-1	- 45		- 8-5		30,000	- 1	30,000
2026-211	Curbing Machine - #69		Good	No.				-		8,000	-	8,000
2026-212	Roadside Mower Head	0.11	Good	No			-	0.4			195,000	195,000
2026-213	Lift - #68		Good	No	-		-	11 A	1 2	- 7.0	125,000	125,000
2026-214	Wood Chipper - #27		Good	No		-			11 - 2		60,000	60,000
2026-215	Tractor - #55		Good	No			-		100		30,000	30,000
2026-216	Mower - #53		Good	No	120	-		-			30,000	30,000
2026-217	Mower - #54		Good	No	-			(-)	11 00	1 5 5 1	30,000	30,000
2026-218	RTV - #57		Good	No				- 15	11 211	-5	30,000	30,000
2026-219	Road Saw - #61		Good	No	4	3.40			11 2		15,000	15,000
	Sub Total					28,000	505,000	85,000	70,000	78,000	515,000	1,281,000

Ref#	Project Description	Funding Source	Estimate Confidence	Other Funding	Recom.	FY27	FY28	FY29	FY30 & FY31	FY32 & FY33	FY34 - FY36	TOTAL
	Town Hall Capital Items											
	Miscellaneous Furniture, Fixtures, and Equipment											
2026-250	Capital Contribution to GAA (1/3 of two new ambulances)		Good	No		122,500						122,500
2026-251	Servers		Good	No	11 70-01	30,000	30,000	-	11 (020)	60,000	60,000	180,000
2026-252	Furn., Fixtures, & Equipment		Good	No		10,000	10,000	10,000	25,000	25,000	25,000	105,000
2026-253	Oil Boilers and Tanks Equipment Removal		Good	No			150,000	54.	54.1			150,000
2026-254	Wifi Access Points		Good	No				49,500	1 - 14	-	49,500	99,000
2026-255	Security Camera Equipment and Storage		Good	No	100		1.5	10,000		10,000	10,000	30,000
2026-256	Townwide PCs and Monitors		Good	No	1	-		0.49	127,500		127,500	255,000
2026-257	Townwide Laptops	4	Good	No	1			14	100,000	- 300	100,000	200,000
2026-258	Network Switches		Good	No		-	-		75,000	75,000	150,000	300,000
2026-259	Redundant Firewalls		Good	No	100			-	40,000	1	40,000	80,000
2026-260	Avaya Phone System J179 2023		Good	No				-			50,000	50,000
	Sub Total		1			162,500	190,000	69,500	367,500	170,000	612,000	1,571,500

Ref#	Project Description	Funding Source	Estimate Confidence	Other Funding	Recom.	FY27	FY28	FY29	FY30 & FY31	FY32 & FY33	FY34 - FY36	TOTAL
	Public Works Buildings and Infrastructure											
	Public Works						-					
2026-300	Pumping Station - 166 Salmon Brook Street		Good	No	-	108,000	-	-				108,000
2026-301	Pumping Station - Route 189		Good	No		87,000		-				87,000
2026-302	Pumping Station Generator - 166 Salmon Brook Street		Good	No		54,000		- 3-2				54,000
2026-303	DPW Interior Drainage Repairs		Good	No		16,000					1000	16,000
2026-304	DPW Install Stairway from Mezzanine to Ground		Good	No		15,000					11	15,000
2026-305	DPW Garage Roof Replacement		Good	No	1	11,000	100,000		2.			111,000
2026-306	DPW Overhead/Passage Doors/Doors		Good	No		8,000	8,000	8,000	14,000	12,000	68,000	118,000
2026-307	DPW Fuel Pump Station Concrete Repairs		Good	No	1	-	10,000				1.0	10,000
2026-308	DPW Salt Storage Repairs		Good	No	100	-	-	18,000				18,000
2026-309	DPW Furnace/AC Replomt.		Good	No		-		15,000	-	15,000	- 1	30,000
2026-310	DPW Furniture/Fixtures/Apparatus		Good	No	1	2.1		5,000	5,000		11 3.4	10,000
2026-311	DPW Cold Storage Renovation/Build		Good	No		-			50,000	(C) 411		50,000
2026-312	DPW Window Replacement		Good	No	- 3	-			18,000	(a		18,000
2026-313	DPW Ceiling Tiles/Duct Cleaning/Painting		Good	No		-			8,000			8,000
2026-314	DPW Salt Shed		Good	No	7.1						315,000	315,000
2026-315	Transfer Station - 7 Sheds		Good	No		-					108,000	108,000
2026-316	Transfer Station Building Replacement		Good	No	-	-		-			100,000	100,000
2026-317	DPW Generator		Good	No						-	54,000	54,000
2026-318	DPW Exterior Building Repairs & Roof		Good	No		- 2		- 9/1	11 4 11-1		50,000	50,000
2026-319	DPW Garage Repointing and Masonry Repairs		Good	No				94	11		50,000	50,000
2026-320	DPW Garage HVAC Replacement		Good	No			- 1				25,000	25,000
2026-321	DPW Garage Window/Door Replacement		Good	No		-	-		1 5-21		25,000	25,000
2026-322	DPW Garage Plumbing Repairs		Good	No	-	-	-	-	11		5,000	5,000
	Sub Total					299,000	118,000	46,000	95,000	27,000	800,000	1,385,000

Ref#	Project Description	Funding Source	Estimate Confidence	Other Funding	Recom.	FY27	FY28	FY29	FY30 & FY31	FY32 & FY33	FY34 - FY36	TOTAL
	Public Works Buildings and Infrastructure											
-	Police Department				-							
2026-350	Police Station HVAC Replacement	14	Good	No		10,000	10,000	10,000		-	2,700,000	2,730,000
2026-351	Police Station Repointing and Masonry Repairs		Good	No	1	5,000			-		250,000	255,000
2026-352	Police Station Roof Replacement		Good	No	7.00		- 2	- 6	11 5		250,000	250,000
2026-353	Police Station Window/Doors Replacement		Good	No					-		150,000	150,000
2026-354	Police Station Plumbing Repairs		Good	No			-	-	-		50,000	50,000
2026-355	Animal Shelter HVAC Replacement		Good	No	10.00			-			15,000	15,000
2026-356	Animal Shelter Repointing and Masonry Repairs		Good	No							15,000	15,000
2026-357	Animal Shelter Roof Replacement		Good	No	0.00	-	-				15,000	15,000
2026-358	Animal Shelter Window/Door Replacement		Good	No					- Ca-		10,000	10,000
2026-359	Animal Shelter Plumbing Repairs		Good	No			-				5,000	5,000
	Sub Total					15,000	10,000	10,000			3,460,000	3,495,000

Ref#	Project Description	Funding Source	Estimate Confidence	Other Funding	Recom.	FY27	FY28	FY29	FY30 & FY31	FY32 & FY33	FY34 - FY36	TOTAL
	Public Works Buildings and Infrastructure											
	Library Department		11									
2026-400	Main Library Expansion		Good	Yes		7,000,000			1 04			7.000.000
2026-401	GPL Generator		Good	No		65,000			1 20-			65,000
2026-402	GPL Hang French Door to Reading Rm		Good	No	11.6	20,000		5.0			7	20,000
2026-403	GPL Automatic Entry Doors Replacement		Good	No	- 2	15,000			100		1.0	15,000
2026-404	GPL Book Drops Replacement		Good	No	Le. I	12,000						12,000
2026-405	GPL New Library Signage		Good	No	10.		10,000					10,000
2026-406	GPL Rear Staff Entrance & Parking: ADA Compliance		Good	No				25,000	1		-	25,000
2026-407	GPL EV Charging Stations		Good	Yes					37,000			37,000
2026-408	Cossitt Library Downstairs Entrance		Good	No	1.0		100	K-0	20,000			20,000
2026-409	Cossitt Library Septic System		Good	No			244		10,000			10,000
2026-410	Main Library HVAC Replacement		Good	No	11.0			1.0	p- 1		4,100,000	4,100,000
2026-411	Cossitt Historically Based Capital Replacement Items (please see the detailed list)		Good	Yes		-	-				493,500	493,500
2026-412	Main Library Roof Replacement		Good	No	1.2			-		- 100	250,000	250,000
2026-413	Main Library Repointing and Masonry Repairs		Good	No	-			- 4		- 5	125,000	125,000
2026-414	Main Library Window/Door Replacement		Good	No					J > -	-	75,000	75,000
2026-415	Cossitt Library Window/Door Replacement		Good	No			-	1 1 1 2			45,000	45,000
2026-416	Cossitt Library HVAC Replacement		Good	No	79.0	-	-		11 041		25,000	25,000
2026-417	Cossitt Library Repointing and Masonry Repairs		Good	No			9.5	-	7		25,000	25,000
2026-418	Cossitt Library Roof Replacement		Good	No							25,000	25,000
2026-419	Main Library Plumbing Repairs		Good	No			1.5	-			20,000	20,000
2026-420	Cossitt Library Plumbing Repairs		Good	No							20,000	20,000
*	Sub Total					7,112,000	10,000	25,000	67,000	1	5,203,500	12,417,500

Ref#	Project Description	Funding Source	Estimate Confidence	Other Funding	Recom.	FY27	FY28	FY29	FY30 & FY31	FY32 & FY33	FY34 - FY36	TOTAL
	Public Works Buildings and Infrastructure											
	Town Hall											
2026-450	TH Town Clerk Land Record Book Shelving		Good	No		30,000						30,000
2026-451	TH Town Clerk Vault Door Replacement		Good	No		20,000	-	- 1 D•1	1	21		20,000
2026-452	Town Hall Window/Door Replacement		Good	No		15,000	15,000	15,000	15,000	1-0	250,000	310,000
2026-453	TH Town Clerk Central Filing System		Good	No	-	5-6	50,000			- J-5.	-	50,000
2026-454	TH Town Clerk Non-combustible Flooring		Good	No	- 6	1.4.1	25,000		-	5.1		25,000
2026-455	Town Hall HVAC Replacement/Town Clerk Vault HVAC		Good	No			15,000	30,000	110 - 20		4,100,000	4,145,000
2026-456	Town Hall Roof Replacement		Good	No	-	¥1.			15 0 20	-	250,000	250,000
2026-457	83 Salmon Brook Street Building (Freshies)	100	Good	No	- 5				11 - 50		75,000	75,000
2026-458	Town Hall Generator		Good	No	- 1				1 20	1 - 2	54,000	54,000
2026-459	Town Hall Plumbing Repairs		Good	No			- 0			1 - 1	50,000	50,000
2026-460	Town Hall Repointing and Masonry Repairs		Good	No	4.1						50,000	50,000
2026-461	Gazebo - Town Center		Good	No			-				25,000	25,000
2026-462	Drummer Building - 11 North Granby Road		Good	No	91	- 0.11				9,11	10,000	10,000
-	Sub Total					65,000	105,000	45,000	15,000		4,864,000	5,094,000

Ref#	Project Description	Funding Source	Estimate Confidence	Other Funding	Recom.	FY27	FY28	FY29	FY30 & FY31	FY32 & FY33	FY34 - FY36	TOTAL
	Public Works Buildings and Infrastructure						4,724	1124	1.140 27 101	1102 41 100	1100-1100	TOTAL
	Community Services (Senior, Youth, Parks and Recreation)		7									
2026-500	Parks Master Plan - SBP - Route 20 Path to Soccer Fields		Good	Yes		700,000		-	-			700,000
2026-501	Parks Master Plan - SBP - Pickleball Courts and relocation of Lacrosse Fields		Good	Yes		500,000	1.0					500,000
2026-502	SBP - STEAP Grant Match		Good	No		150,000			-			150,000
2026-503	SBP Bathroom (Renovation or additional)		Good	No	100	100,000				140	-	100,000
2026-504	SBP Storage Garage		Good	No		50,000	- 2-	- 51	1.			50,000
2026-505	HF - Siding		Good	Yes		50,000		- 3.1	1.6:		-	50,000
2026-506	SC Furniture		Good	No	100	40,000				- 2	40,000	80,000
2026-507	SBP Stairlift for Storage		Good	No		10,000					70,000	10,000
2026-508	SBP Ductless Air Splits		Good	No	7	10,000			1.41			10,000
2026-509	SBP Lifeguard Chair replacement		Good	No	1 - 14	8,500						8,500
2026-510	HF - Stone Dust Path		Good	No		5,000			140			5,000
2026-511	SBP Swim Building Rebuild		Good	No				100.000				100,000
2026-512	SC Carpet Replacement		Good	No	1-3-		0.10	25,000			- 1	25,000
2026-513	Senior/Youth Center HVAC Replacement		Good	No			- 2 /	20,000			2,300,000	2,300,000
2026-514	Parks Master Plan - SBP - Restroom		Good	Yes	1003.0	- 2-					1,000,000	1,000,000
2026-515	Parks Master Plan - SBP - Skatepark		Good	Yes	7		1000	-	7.11		1,000,000	1,000,000
2026-516	Parks Master Plan - Ahrens - Pump Track		Good	Yes	100				-		1,000,000	1,000,000
2026-517	Parks Master Plan - SBP - Relocation of Ballfields 3 and 5		Good	Yes	5.4	4.1					600,000	600,000
2026-518	Parks Master Plan - SBP - Playground ages 5-12		Good	Yes	15.0	5.1	- 2.5.	-	-		600,000	600,000
2026-519	Parks Master Plan - SBP - Upgraded Ballfields		Good	Yes	- 7-		120				600,000	600,000
2026-520	Parks Master Plan - Ahrens - Playground		Good	Yes		- 6-			-		600,000	600,000
2026-521	Parks Master Plan - SBP - Natureplay Playscape		Good	Yes		- 2					500,000	500,000
2026-522	Parks Master Plan - Ahrens - Pickleball Counts		Good	Yes							500,000	500,000
2026-523	Parks Master Plan - SBP - Exercise Stations		Good	Yes			1 72	2 9 1			400,000	400,000
2026-524	Parks Master Plan - Ahrens - Football Field Lighting		Good	Yes	19						400,000	400,000
2026-525	Parks Master Plan - SBP - Splashpad		Good	Yes	1-	-	-	140		-	350,000	350,000
2026-526	Parks Master Plan - SBP - New Parking Lot		Good	Yes		2.0	-1-				350,000	350,000
2026-527	Parks Master Plan - SBP - Route 20 Parking Lot Renovations		Good	Yes							350,000	350,000
2026-528	Parks Master Plan - Ahrens - Expanded Parking		Good	Yes		- 1		-			350,000	350,000
2026-529	Parks Master Plan - SBP - Electrical, Water, Sanitary Expansion		Good	Yes		-	1421		-		300,000	300,000
2026-530	Parks Master Plan - Ahrens - Paved Walking Path		Good	Yes							300,000	300,000
2026-531	Holcomb Farm Roof Replacement		Good	No		-					250,000	250,000
2026-532	Holcomb Farm Window/Door Replacement		Good	No			1.				250,000	250,000
2026-533	Parks Master Plan - Reconfigure Public Works Parking for Greater Utilization		Good	Yes		-			-		250,000	250,000
2026-534	Parks Master Plan - SBP - 3 Way Stop Intersection		Good	Yes				-	-	-	200,000	200,000
2026-535	Parks Master Plan - SBP - Accessible Walkways, including Band Shell		Good	Yes		-	10/10		- 0		200,000	200,000
2026-536	Senior/Youth Center Roof Replacement		Good	No.	- 4		36	1 2	- 0		175,000	175,000
2026-537	SBP Main Office Building Repointing and Masonry Repairs		Good	No			1	-	-		150,000	150,000
2026-538	SBP Main Office Building Roof Replacement		Good	No			- 0	30	1		150,000	150,000
2026-539	SBP Small Playground Replacement		Good	No				201		-	150,000	150,000
2026-540	Parks Master Plan - Ahrens - Hiking Trails		Good	Yes			-				100,000	100,000
2026-541	Senior/Youth Center Repointing and Masonry Repairs		Good	No.	12.				- 0		100,000	
2026-542	SBP Band Shell Roof Replacement		Good	No	-						75,000	100,000
2026-543	Senior/Youth Center Window/Door Replacement		Good	No				-	-		75,000	75,000
2026-544	Senior/Youth Center - Generator		Good	No			-		-		54.000	75,000 54,000
2026-545	Parks Master Plan - SBP - Seating along Walking Path		Good	Yes			1.4					
2026-546	Parks Master Plan - SBP - Seating along Walking Path Parks Master Plan - SBP - Landscaped Entrances, Memorials		Good	Yes		7.1	-				50,000	50,000
2026-547	Pond Dredging		Good	No No	-	-			-		50,000	50,000
2026-548	Holcomb Farm Dwelling HVAC Replacement		Good	No No								50,000
2026-549	Holcomb Farm Dwelling Window/Door Replacement		Good		-		-				50,000	50,000
2026-550	Holcomb Farm HVAC Replacement		Good	No No			- :			-	50,000	50,000
2026-550	Holcomb Farm HVAC Replacement Holcomb Farm Plumbing Repairs			No No	-	3.0	~				50,000	50,000
2026-552			Good	No		•	-		-		50,000	50,000
	Holcomb Farm Repointing and Masonry Repairs		Good	No		•	*:				50,000	50,000
2026-553	SBP Main Office Building HVAC Replacement		Good	No			-		-		50,000	50,000

Ref#	Project Description	Funding Source	Estimate Confidence	Other Funding	Recom.	FY27	FY28	FY29	FY30 & FY31	FY32 & FY33	FY34 - FY36	TOTAL
2026-554	SBP Main Office Building Window/Door Replacement		Good	No	× 1			-	-		30,000	30,000
2026-555	SBP Rec Building Roof Repair		Good	No		-81		0	-		25,000	25,000
2026-556	Generator for SBP Parkhouse		Good	No		17-11		-			25,000	25,000
2026-557	Generator for NB Pavilion	1 1	Good	No		- 191		-	11 - 20	- 4	25,000	25,000
2026-558	Bathhouse Repointing and Masonry Repairs		Good	No	1 041		w 1		11 - 00		25,000	25,000
2026-559	Bathhouse Roof Replacement		Good	No		- 98				-	25,000	25,000
2026-560	Holcomb Farm Dwelling Plumbing Repairs		Good	No					11.		25,000	25,000
2026-561	Holcomb Farm Dwelling Repointing and Masonry Repairs		Good	No		1.61	7.1	100 SeV	2.1		25,000	25,000
2026-562	Holcomb Farm Dwelling Roof Replacement		Good	No		-	- 2				25,000	25,000
2026-563	SBP Main Office Building Plumbing Repairs		Good	No	7.1				1 5 5		25,000	25,000
2026-564	SBP Pond Dock Replacement		Good	No	1	- 1		1	112		25,000	25,000
2026-565	Senior/Youth Center Plumbing Repairs		Good	No	-	9.11		39-1	10 - 41	1	25,000	25,000
2026-566	Digital Sign SBP Entrance	- I > II	Good	No		5.1		0-2	1 000		15,000	15,000
2026-567	Bathhouse Window/Door Replacement		Good	No							15,000	15,000
2026-568	Parks Master Plan - Ahrens - Lacrosse Fields Addition		Good	Yes		- 601		- 2.	91 1 1 2.19		10,000	10,000
2026-569	Bathhouse Plumbing Repairs		Good	No				Lead	11 - 12		5,000	5,000
2026-570	SBP Band Shell Plumbing Repairs		Good	No					31.		5,000	5,000
2026-571	SBP Band Shell Window/Door Replacement		Good	No						- 4-1	5.000	5,000
2026-572	SBP Band Shell Repointing and Masonry Repairs		Good	No	- 7	1-11			I L vol		5,000	5.000
2026-573	Bathhouse HVAC Replacement		Good	No					I a section			-
2026-574	SBP Band Shell HVAC Replacement		Good	No			- 21	•				
	Sub Total					1,623,500		125,000			14,534,000	16,282,500

Ref#	Project Description	Funding Source	Estimate Confidence	Other Funding	Recom.	FY27	FY28	FY29	EV30 & EV31	EV32 & EV33	FY34 - FY36	TOTAL
	Police Department Capital Items						1120	1120	1100 01 101	1102 01100	1134-1130	TOTAL
	Rolling Stock and Equipment											
2026-575	Police Cruiser VID #20		Good	No.		70,000	-	-		-		70,000
2026-576	Police Cruiser VID #10		Good	No		65,000	1.0		-			65,000
2026-577	PD Fire Alarm Panel Replacement		Good	No	-	11,000						11,000
2026-578	PD Window Security Protection		Good	No		7,000					-	7.000
2026-579	Police Mobile Data Terminal (MDT) x6		Good	No		5,000	5,000	5,000	5,000	5,000	5.000	30,000
2026-580	PD Stairway Replacement		Good	No		- 0,000	90,000	5,000	3,000	3,000	3,000	90,000
2026-581	Police Cruiser VID #40		Good	No			70,000				-	70,000
2026-582	Police Cruiser VID #30		Good	No	-		65,000	-				65,000
2026-583	PD Impound Lot Upgrades		Good	No			20,000				-	20,000
2026-584	PD AEDs for Cruisers		Good	No			5,000	5.000	5,000	5,000	15,000	35,000
2026-585	Police/TH Video Security System		Good	No			5,000	0,000	5,000	0,000	5,000	15,000
2026-586	PD Electric Bicycles		Good	No			3,000		0,000	3,000	3,000	6,000
2026-587	Police Cruiser VID #60		Good	No			0,000	70,000		3,000		70,000
2026-588	Police Cruiser VID #50		Good	No.			-	65.000			-	65,000
2026-589	PD Office Furniture/Storage		Good	No				20,000				20,000
2026-590	PD Storage Shed		Good	No				15,000		1 - 2	- 20	15,000
2026-591	PD Speed Trailers		Good	No	54			10,000		10,000	10,000	30,000
2026-592	M4 Rifle Suppressors		Good	No			1.	10,000		10,000	10,000	10,000
2026-593	Police Cruiser VID #90		Good	No			1.4.0	10,000	70,000			70,000
2026-594	Police Cruiser VID #96		Good	No		20	- 4	- 2	70,000		1	70,000
2026-595	Police Cruiser VID #70		Good	No	-		-		65,000			65,000
2026-596	Police Cruiser VID #95		Good	No	-				65,000			65,000
2026-597	PD Variable Message Board		Good	No	1.0		-		15,000			15,000
2026-598	Police Cruiser VID #100		Good	No					10,000	70,000		70,000
2026-599	Police Cruiser VID #97		Good	No	-	-				65,000		65,000
2026-600	Police Cruiser VID #110		Good	No					-	65,000	-	65,000
2026-601	Police Station Generator		Good	No.	-	-					50,000	50,000
2026-602	PD Carpet Replacement		Good	No							27,000	27,000
	Sub Total				-	158,000	263,000	200,000	300,000	223,000	112,000	1,256,000
	Total Town				-	14,193,000	2.951.000	2.480.500	16,744,500	4,509,000	37,178,500	78,056,500

Ref#	Project Description	Funding Source	Estimate Confidence	Other Funding	Recom.	FY27	FY28	FY29	FY30 & FY31	FY32 & FY33	FY34 - FY36	TOTAL
	Board of Education				-				1			
	Non-Builidng, Rolling Stock and Equipment											
2026-625	Ford F-350 4x4 Styeside - 26GR		Good	No				-	75,000	-		75,000
2026-626	Ford E-150 Cargo Van - 51GR		Good	No						50,000	-	50,000
2026-627	Ford Full Size Van - 44GR	9	Good	No						20,000		20,000
2026-628	Robotics Trailer - 49GR		Good	No			-			12,000	-	12,000
2026-629	Ford F-350 4x4 - 60GR		Good	No	-	-					75,000	75,000
2026-630	Ford F-450 4x4 - 57GR		Good	No							75,000	75,000
2026-631	Ford E-150 Cargo Van - 58GR		Good	No	-		-				50,000	50,000
2026-632	Maintenance Trailer - 55GR		Good	No				-			45,000	45,000
2026-633	Trailer 6x12 - 15GR		Good	No			0.00				45,000	45,000
2026-634	Ford Full Size Van - 53GR		Good	No							20,000	20,000
	Sub Total								75,000	82,000	310,000	467,000

Ref#	Project Description	Funding Source	Estimate Confidence	Other Funding	Recom.	FY27	FY28	FY29	FY30 & FY31	FY32 & FY33	FY34 - FY36	TOTAL
1111	Board of Education											
	Granby Memorial High School											
2026-650	Turf/Track Field - includes excavation and recompaction		Good	Yes	76-1	4,000,000			-			4,000,000
2026-651	Repointing Masonry		Fair	No		200,000	-		-	0.0	-	200,000
2026-652	Interior Fire Door Replacement (realign, repair gaps also)		Good	No		150,000						150,000
2026-653	Storage space - auditorium & drama		Good	No	1 +1	15,000	-			·		15,000
2026-654	Corridor Tile Replacement (all 5 buildings, total)		Fair	No			500,000	0.44	-	10.00 m	-	500,000
2026-655	Community Gym bleachers		Good	No					140,000			140,000
2026-656	Upgraded dugouts, pressbox, multipurpuse fields upgrade, lighting, tennis		Good	Yes			-		-	3,000,000	3,000,000	6,000,000
2026-657	HS & MS Parking lot resurfacing		Good	No	1				-	1,700,000	-	1,700,000
2026-658	Water heaters		Good	No	il at in					40,000		40,000
2026-659	Elevator		Fair	No	1.0			-	-		225,000	225,000
2026-660	HVAC Replacement RTU 10 (auditorium)		Good	No	0.00	-		(C*)*	-		100,000	100,000
2026-661	HVAC Replacement RTU 1		Good	No	4	-	- 26	-			75,000	75,000
2026-662	HVAC Replacement RTU 2		Good	No			7-01		-		75,000	75,000
2026-663	HVAC Replacement RTU 3		Good	No		-		19-h	3-1	-	75,000	75,000
2026-664	HVAC Replacement RTU 4		Good	No		-					75,000	75,000
2026-665	HVAC Replacement RTU 5		Good	No	1.40				-		75,000	75,000
2026-666	HVAC Replacement RTU 6		Good	No		-		-	-		75,000	75,000
2026-667	HVAC Replacement RTU 7		Good	No	n bed						75,000	75,000
2026-668	HVAC Replacement RTU 8		Good	No		- 1	-				75,000	75,000
2026-669	HVAC Replacement RTU 9		Good	No							75,000	75,000
2026-670	HVAC Replacement RTU 11		Good	No		-			-		75,000	75,000
2026-671	HVAC Replacement RTU 12		Good	No		-	-	-			75,000	75,000
2026-672	HVAC Replacement RTU 13		Good	No				- •		-	75,000	75,000
2026-673	HVAC Replacement RTU 14		Good	No		-	-	•		100	75,000	75,000
2026-678	HVAC Replacement RTU 15		Good	No	- Day		-				75,000	75,000
			Fair	No	9.1						75,000	75,000
2026-680			Good	No	1 . 1		-	-		-	75,000	75,000
	Sub Total					4,365,000	500,000		140,000	4,740,000	4,525,000	14,270,000

Ref#	Project Description	Funding Source	Estimate Confidence	Other Funding	Recom.	FY27	FY28	FY29	DV20 2 DV24	FW00 0 FW00		-
	Board of Education	Course	Commission	Landing	Necotii.	F12(FT26	F129	F130 & F131	FY32 & FY33	FY34 - FY36	TOTAL
	Granby Memorial Middle School										-	
2026-700	Renovate to new		Good	Yes	-	20,000,000						
2026-701	Renovate "in kind" (supports status quo) - no sprinklers	-	Good	Yes		3.100.000	100		-	-	-	20,000,000
2026-702			Good	No		400.000	-				F- 5-1	3,100,000
2026-703			Good	No		390,000			-		-	400,000
2026-704	MS bleachers	_	Good	No		150,000	-				-	390,000
2026-705	Refurbish portions of the interior and exterior AHUs		Good	No			-	-	2.	-		150,000
2026-706			Good	No	1	140,000		•	0.4		-	140,000
2026-707	Fire alarm control panel upgrade	-	Good	No		110,000 75,000	13.			-		110,000
2026-708	Ecology Center maintenance and upgrades	-	Good	No		50,000						75,000
2026-709		1	Good									50,000
	Phased renovation of locker rooms and restroom interior finishes and fixtures	-	Good	No		30,000				1411	1.2	30,000
2026-711	Refurbish HVAC VAV units, HHW coils, baseboard radiators, unit heaters, DOAS, HHW piping	-		No		-	280,000	280,000	280,000		6.0	840,000
026-712	Repair, repoint exterior masonry and seal		Good	No			145,000	. 2	-	(-0)	-	145,000
	Elevator (in ground cylinder replacement) & modernization of can and controls		Good	No			140,000		-	-	-	140,000
	Replace all bathroom fixtures (cost per bathroom)		Good	No			120,000				6-01	120,000
	HVAC Replacement RTU 1		Good	No	-		90,000				-	90,000
		_	Good	No			75,000	-		-		75,000
	HVAC Replacement RTU 3		Good	No			75,000				~	75,000
			Good	No	- 0.		75,000				- 1	75,000
	HVAC Replacement RTU 5		Good	No		*	75,000	1.0		1 - 1		75,000
			Good	No	-		75,000	-	- 5-			75,000
	HVAC Replacement RTU 7		Good	No			75,000			-	-	75,000
	Concrete paving replacement		Good	No.			75,000	-			-	75,000
			Good	No		-	59,000	-				59,000
	HVAC controls upgrade Refinish gym floor		Good	No	14			100,000	- A-C			100,000
			Good	No			T	24,000	- 1			24,000
026-725	Replace loading dock manual steel overhead doors		Good	No	- 19	~ 1		5,700		-		5,700
	Kitchen Equipment upgrades		Good	No		-		-	400,000	¥		400,000
	Replace single ply TPO roof membrane assembly		Good	No	-	-	-		210,000		-	210,000
	Upgrade fire rated doors (50 @ \$1,000 each)		Good	No	9-04	-	C	-	50,000			50,000
	Water heaters		Good	No		-	121		45,000	3-1	-	45.000
	Kitchen fridge and freezer upgrade		Good	No	7.4		-	-	30,000		7-1	30,000
026-731	Kitchen lighting upgrades		Good	No					15,000			15,000
026-732	Kitchen dishwasher upgrade		Good	No	4.0				5,000		3-2	5,000
026-733	Kitchen hood relocation		Good	No								
026-734	Kitchen paint upgrades		Good	No				-	3,000	1.2	-	3,000
	Rolloff Trailer storage containers w/AC		Good	No No		-	- 1	-	1,500	-		1,500
	Pavilion 20'x40' (cement slab & piers)						-	-			350,000	350,000
	Sprinkler system update - full building study needed		Fair	No				-	- 1		75,000	75,000
020-131	Sub Total		Good	No						-	-	T- T-(-D.
	Sub total					24,445,000	1,359,000	409,700	1,039,500		425,000	27,678,200

Ref#	Project Description	Funding Source	Estimate Confidence	Other Funding	Recom.	FY27	FY28	FY29	FY30 & FY31	FY32 & FY33	FY34 - FY36	TOTAL
	Board of Education								1		1.102 1.100	TOTAL
	Kelly Lane Primary School		-						1-			
2026-750	Roofing Replacement - Gross of grant reimbursement		Good	Yes		100,000	2,800,000					2,900,000
2026-751	Window/Door Replacement (Fire code)		Good	No		-	50,000				2 1	50,000
2026-752	Boiler and pump replacement (after converting to propane in FY26)		Good	No		- 2		-	500,000			500,000
2026-753	Parking lot resurfacing / expansion		Good	No		- 1.	-	-	380,000			380,000
2026-754	HVAC Replacement - RTU 1		Fair	No		10010	-		75,000			75,000
2026-755	HVAC Replacement - RTU 2		Fair	No				-	75,000	-		75,000
2026-756	HVAC Replacement - RTU 3		Fair	No		-		-	75,000	-		75,000
2026-757	HVAC Replacement - RTU 4		Fair	No	-	1.4.1			75,000			75,000
2026-758	HVAC mini-splits (cost per unit, need 3), classrooms		Good	No					30,000			30,000
	HVAC mini-splits (cost per unit, need 2), server rooms		Good	No		343.1			20,000			20,000
2026-760	Kitchen Updates (flooring, equipment, walk-ins)		Good	No	-	- 1			20,000	600,000		600,000
	Gym floor (rubber)		Good	No		-		-		150,000		150,000
	Pavilion 20'x40' (cement slab & piers)		Fair	No			-	-		75,000		75,000
2026-763	Playground updates (design equipment/ composite flooring / mulch)		Good	No		7.31				75,500	250,000	250,000
	Courtyard redesign / outdoor learning space / compost		Fair	No							100,000	100,000
	Catch basin replacement (6)		Good	No		-				-	100,000	100,000
			Good	No				-		-	75,000	75,000
2026-767			Good	No		-	-				40,000	40,000
2026-768	Shed		Fair	No							40,000	40,000
	HVAC Replacement - RTU 4		Good	No	1		-		1		40,000	40,000
	Sub Total		2300			100,000	2,850,000	-	1,230,000	825,000	605,000	5,610,000

Ref#	Project Description	Funding Source	Estimate Confidence	Other Funding	Recom.	FY27	FY28	FY29	FY30 & FY31	FY32 & FY33	FY34 - FY36	TOTAL
	Board of Education								1100 01 101	1102 01100	1104-1100	TOTAL
	Wells Road Intermediate School											
2026-800	Gym floor (rubber)		Good	No		150,000			Y-	120		150,000
2026-801	Roofing Replacement - Gross of grant reimbursement		Good	Yes		100,000	2,800,000					2,900,000
2026-802	Water System Upgrade (similar to Kelly Lane)		Good	No			400.000				-	400,000
2026-803	Parking lot resurfacing / expansion		Good	No		-	350,000					350,000
2026-804	Window/Door Replacement (Fire code)		Good	No			50,000	4		1-0		50,000
2026-805	Cafeteria and Stage Renovation		Fair	No	-				600,000	-	-	600,000
2026-806	Boiler and pump replacement (after converting to propane in FY26)		Good	No				-	500,000	-		500,000
2026-807	Parking lot resurfacing / expansion		Good	No	-	-	-		380,000	-	-	380,000
2026-808	HVAC Replacement - RTU 1		Fair	No				-	75,000	-		75,000
2026-809	HVAC Replacement - RTU 2		Fair	No			-	-	75,000		-	75,000
2026-810	HVAC Replacement - RTU 3		Fair	No					75,000	-		75,000
2026-811	HVAC Replacement - RTU 4		Fair	No					75,000		-	75,000
2026-812	Water Heaters		Good	No	-		-		30,000		-	30,000
2026-813	HVAC mini-split, need 1, server room		Good	No					20,000			20,000
2026-814	Kitchen Updates (flooring, equipment, walk-ins)		Good	No					20,000	600,000		600,000
2026-815	Window Replacement (just affected areas)		Good	No	-	-	1.	-	1.	-	150,000	150,000
2026-816	Catch basin replacement (6)		Good	No		-	2.44			-	100,000	100,000
2026-817	Bathroom renovations (per bathroom)		Good	No			- 4				75,000	75,000
2026-818	HVAC ERU's, need 3 (cost per unit)		Good	No	1.		7.				70,000	10,000
	Repointing and Masonry Repairs		Good	No				-				
	Sub Total					250,000	3,600,000		1,830,000	600,000	325,000	6,605,000

Ref#	Project Description	Funding Source	Estimate Confidence	Other Funding	Recom.	FY27	FY28	FY29	FY30 & FY31	FY32 & FY33	FY34 - FY36	TOTAL
	Board of Education							1.1-1				
	Central Services Building											
2026-850	Security Initiative - Whole District (\$850k in place via Small Cap)		Good	No		1,200,000		-		- ~		1,200,000
2026-851	Storage -Butler Building (multiple bays with plumbing and electrical)		Good	No		-		250,000				250,000
2026-852	Office Reconfiguration		Good	No				-			40,000	40,000
	Sub Total					1,200,000		250,000			40,000	1,490,000
	Total Board of Education		-			30,360,000	8,309,000	659,700	4,314,500	6,247,000	6,230,000	56,120,200
	Total Town and Board of Education					44,553,000	11,260,000	3,140,200	21,059,000	10.756.000	43,408,500	134,176,700

Priority level Level 1 =	Category	Project	Initial Estimate	Notes	2025- 40% increase in cost	
within 1 yr; Level 2 = 2-5			100	The second secon		
rs; Level 3 = 5-10 yrs.						
evel 1	Exterior Facades & Roofing	Replace new metal door @ vestibule entrance to lower level with appropriate wood door with glass lights.	\$ 2,000.00		\$ 2,800.00	
wel 1	Exterior Facades & Roofing	Inspect all gutters & leaders on a routine basis at least twice yearly & after extreme	5. 2,000.00		5	
	•	climate events. Secure all leaders to their bases to storm drain boot and secure all drainage system connections. Repair and adjust any observed deficiencies.	2,500,50			
evel 5	Exterior Facades & Roofing	Install gutter on north portion of East Elevation of East Addition	\$ 2,000.00	Complete	\$	1
evel 1	Exterior Facades & Roofing	Increase overhang on North Elevation of the East Addition	\$ 6,000.00		\$ 8,400.00	
evel 1	Exterior Facades & Roofing	Provide slope away from building on brick-clad buttresses metal covers. Install base flashing extending under wood trim at juncture of metal covers to the wood install sealant at all junctures of flashing with wood trim or other building elements.	\$ 8,000.00		\$ 11,200,00	
evel 2	Exterior Facades & Roofing	Carefully remove all masonry coatings and efflorescence from brick walls, brick chimney and concrete foundation walls.	\$ 20,000,00		\$ 28,000.00	T
evel 2	Exterior Facades & Roofing	Repair or replace all displaced, damaged, or missing bricks, specifically at base of wall.	\$ 5,000,00		\$ 7,000.00	
evel 2	Exterior Facades & Roofing	Repoint all missing or damaged mortar joints to match example of original pointing visible in Storage Area under West Entrance Vestibule.	\$ 4,000,00		\$ 5,600.00	
evel 2	Exterior Facades & Roofing	Install liner in brick chimney, Repair metal chimney cap as necessary.	5 5,000.00		5 7,000.00	
evel 2	Exterior Facades & Roofing	Carefully remove all loose and flaking paint and all sealant from wood siding (clapboard and shingles) and trim so as not to damage historic material.		Completed Clerestory, Lower Level Remaining		Estimate + 40% increase/ half
evel 2	Exterior Facades & Roofing	Replace all damaged, deteriorated and missing wood elements with wood to match original in appearance and with same species of wood, if possible.	\$ 20,000.00	Completed Clerestory, Lower Level Remaining	\$ 14,000.00	Estimate + 40% increase/ half
evel 2	Exterior Facades & Roofing	Prepare wood to receive appropriate primer, prime and apply two coats of appropriate paint in color determined by finish analysis. Paint any unpainted elements of the Lower Level Entrance enclosure to match selected paint on wood on original portions of building.	\$ 25,000.00	Completed Clerestory, Lower Level Remaining	\$ 17,500.00	Estimate + 40% increase/ half
evel 2	Exterior Facades & Roofing	install sealant at all joints and gaps whether wood to wood, wood to metal, wood to masonry, or wood to windows.	\$ 10,000,00	Completed Clerestory, Lower Level Remaining	\$ 7,000.00	Estimate + 40% increase/ half
evel 2	Exterior Facades & Roofing	Repair or replace to match original and properly secure all damaged decorative cast iron grills on the vent openings at the base of the brick wall.	2		5 2,800.00	
evel 2	Exterior Facades & Roofing	Repair any damaged elements, scrape, prime and paint, metal railing at steps to parking area.	\$ 1,000.00		\$ 1,400.00	
evel 3	Exterior Facades & Roofing	Replace screen doors at entrance to upper level with new storm/screen doors to match the screen doors visible in historic photographs including visually appropriate. hardware	\$ 3,000,00		\$ 4,200.00	
evel 3	Exterior Facades & Roofing	On the two pair of wood doors at the West, Upper Level Entrance, replace the existing brass replacement doorknobs with replica knobs to match the original.	\$ 1,000,00		5 1,400.00	
evel 3	Exterior Facades & Roofing	Fabricate and install replacement transom window above Lower Level Entrance door to match original, including the word, "HALL", but sized to fit the altered opening size. New window shall be double-glazed for thermal efficiency	\$ 2,000.00		\$ 2,800.00	
evel 3	Exterior Facades & Roofing	Replace white metal louver vent on East Elevation of East Addition with more appropriate, yet functional element.	\$ 2,000.00		\$ 2,800.00	
evel 1	Interior	Fill gap between concrete floor slab & building wall in Lower Level Entrance Vestibule, repairing any damaged masonry as necessary.	\$ 1,000.00		5 1,400.00	
evel 1	Interior	Treat building to eliminate all insects & nests.		Regulary DPW Maintenance	+ -	
evel 1	Interior	Install screens over light fixtures to prevent accumulation of insects & deris. Periodically inspect & clean fixtures.	\$ 1,000,00		\$ 1,400.00	
evel 2	Interior	Repair damaged gypsum board at Lower Level ceiling beam and any other locations of damage to match adjacent finishes.	\$ 2,000.00		\$ 2,800.00	
evel 3	Interior	Conduct historic finish analysis of exterior and interior surface materials.	\$ 5,000.00		\$ 7,000.00	
evel 3	Interior	Carefully remove all damaged plaster to facilitate repairs. Install new plaster to match original, adjacent plaster surfaces in composition, color, and finish.			5 7,000.00	
evel 3	Interior	Paint plaster on walls and ceilings based upon finishes analysis.	\$ 5,000.00		5 7,000.00	
evel 3	Interior	Paint all damaged, flaking and unfinished wood and masonry elements inside the Lower Level Entrance Vestibule in same manner as directed above.	\$ 2,000.00		\$ 2,800.00	
evel 3	Interior	Carefully clean all interior woodwork and cabinetry in the Upper Level, original library space of any scuffs or other surface stains and refinish as necessary based on finish analysis.			\$ 7,000.00	
evel 3	Interior	Strip and re-stain risers on interior stairs to match existing.	\$ 3,000.00		\$ 4,200.00	
evel 3	Interior	Remove existing virryl tile flooring in the boiler room, clean and repair floor as necessary and install new virryl flooring	5 2,000.00		\$ 2,800.00	110
Level 2	Interior	Restore all damaged clerestory window woodwork based upon historic finishes analysis	\$ 10,000.00		\$ 14,000.00	
level 1	Life Safety	Install new addressable smoke and heat detectors and emergency interior and exterior lighting with self-contained battery back-up.	5 5,000,00		5 7,000,00	
Level 2	Life Safety	Install new state-of-the-art building-wide NPPA 13-approved fire-suppression sprinkler system.	\$ 50,000.00		\$ 70,000,00	

Level 2-3		Upgrade the electrical service to a 3-phase, 4-wire service with increased amperage. (2-3)	\$ 10,000.0	0	\$	14,000.00	
Level 2		Install new distribution, panel boards, switches and receptacles throughout the building	\$ 25,000.0	0	\$	35,000.00	
Level 2		Replace/upgrade existing restroom plumbing fixtures to meet all current ADA requirements	\$ 5,000.0	0	5	7,000.00	
Level 2-3		Installing new modern central multi-zone air-conditioning/heating system with the capability to bring in and condition outside air and exhaust spent air at rates prescribed by code. (2-3)	5 75,000.0	0	\$	105,000.00	
Level 3	Mechanical/Electrical/Plumbing	Install new septic system.	\$ 10,000.0	0	5	14,000.00	
Level 1		Maintain slope away from building and maintain height of the mulch adjacent to building at least 8 inches below any building material.	\$ 3,000.0	0	5	4,200.00	-
Level 1	and annually may a some manager of the contract of	Ratch all damaged locations in the concrete sidewalk and concrete parking lot steps to match the existing, surrounding material, Level any portions of sidewalk which could present a tripping hazard.	\$ 3,000.0	Gompleted with ARPA funds			
Level 1		Redesign area between parking area and Lower Level entrance so that handicapped access is more direct and ADA-compliant, using historically compatible material.	5 10,000.0	0	\$	14,000.00	
Level 1		Install pedestrian crossing including appropriate signage on East Street between parking area across East Street and Library parking lot.	\$ 3,000.0	0	\$	4,200.00	
tevel 1		Install additional exterior lighting at the Lower Level Vestibule Entrance door and as needed along sidewalks, pathways, and parking areas with lighting compatible with the historic environment.	5 5,000.6	0	5	7,000.00	-
Level 1	Universal Access	Install automatic door openers at both the Lower Level entrance door and the door leading from the Lower Level Vestibule into the Children's Room	5 6,000.0	0	S	8,400.00	Historic Accuracy?
Level 1	Universal Access	Lower the height of the masonry threshold at the Lower Level Entrance for ADA compliance.	5 1,000	0	\$	1,400.00	
Level 1	Universal Access	If increased or full ADA compliance is desired, engage services of a professional architect knowledgeable in historic preservation to develop a design to provide full ADA-compliance.	5 10,000,0	0	5	14,000.00	
Total Project					5	493,500.00	

Memorandum

To: Town of Granby Board of Selectmen

Mike Walsh, Town Manager - Town of Granby

Sandy Yost, Director of Community Services - Town of Granby

From: Anthony McGovern, Chairperson - Granby Parks and Recreation Board

Date: August 14, 2025

Subject: Endorsement of Parks Improvements – Input for Capital Planning Process

Purpose

The purpose of this memorandum is to highlight proposed improvements to Granby's Parks, as outlined in the recent Recreation Facilities Analysis ("Parks Master Plan") conducted by GZA GeoEnvironmental, Inc. (GZA). Please consider the proposed investments highlighted as the priorities recommended by the Parks and Recreation Board and to specifically inform the upcoming Capital Planning process acknowledging that time is of the essence for such input. Again, this submission reflects the items we've determined to be of most value to the Granby community at this point in time and we acknowledge that these improvement concepts will require much further refinement of requirements and expectations. This is not intended to bypass a more thorough review of the Parks Master Plan which reflects a wider array of potential investments. We look forward to that future conversation with you.

Summary of GZA's Approach

GZA's work was guided by a comprehensive and community-centered methodology, which included:

- Site Analysis: Detailed review of existing conditions at Salmon Brook Park and Ahrens Park through site visits, GIS mapping, and document analysis.
- Public Engagement: A robust outreach effort including stakeholder interviews, an online survey with 619 respondents, and two public meetings. This process identified key community priorities and concerns.
- Parks Master Plan Development: Creation of conceptual master plans for both parks, designed to address landscape constraints, usage conflicts, and program redundancies.

The plans offer advice for logical phases of implementation and include cost estimates (rough order of magnitude based on GZA's actual experience for similar projects) of each improvement, or project, for which we believe should aid in the Capital Planning considerations for the years ahead.

Key Improvements Endorsed

The Parks and Recreation Board recommends the priorities shown on Exhibit A (attached) as investments at Salmon Brook Park and Ahrens Park. Items shaded in grey reflect those investments that have interdependencies and sequencing in the Capital Plan should be given consideration. All other items are potential stand-alone projects.

These improvements reflect the community's vision and address both current needs and future growth.

We appreciate the BOS's attention to this matter and look forward to continued collaboration as the Parks Master Plan progresses.

Respectfully submitted on behalf of the Parks and Recreation Board,

Anthony McGovern, Chairperson

a.Molen

Exhibit A

Recommendation	Description	Potential Cost Range
	Salmon Brook Park	
Route 20 Path to Soccer Fields, Improvements for Pedestrian and Equestrian Use	Upgrade the existing path to the Route 20 parking lot. Develop an unpaved equestrian trail parallel to this. Expand ADA accessibility from the central parking lot to the soccer fields, connecting to the improved Route 20 path. This is listed as part of Phase 1 because the Town has already received a Small Town Economic Assistance Program (STEAP) grant from the State of Connecticut to implement this	\$600,000- \$700,000 (inclusive of STEAP funding)
Salmon Brook Park Pickleball Courts and Relocation of Lacrosse Fields	Relocate the two smaller lacrosse fields from Salmon Brook Park to Ahren's park (the two small lacrosse fields that are currently closest to the swimming pond and central parking lot). Build a new pickleball court in Salmon Brook Park off the southern end of the central parking lot (four dedicated pickleball courts, with fencing and lighting). Revert existing court to dedicated tennis	\$400,000- \$500,000
Salmon Brook Park Ballfields 3 and 5	Relocate ballfield 3 and re-orient ballfield 5 into configuration shown on Master Plan. Add upgraded and accessible seating, lights, and scoreboards to redeveloped ballfields.	\$500,000- \$600,000
Playground (Ages 5-12)	Develop a new playground for ages 5-12 in a revised park location.	\$400,000- \$600,000
Utilities Expansion	Install utilities for the proposed restroom building and future use. This should include a study of available water supply which may result in the installation of an additional well to support the proposed and future use.	\$200,000- \$300,000
Restroom	Develop a new restroom building between Fields 3 and 5 and relocated pickleball court.	\$150,000- \$200,000
3-Way Stop Intersection	Reconfigure the Salmon Brook Park Road 3-way intersection to a 3-way stop intersection (4-way stop including DPW parking lot drive) and reconfigure the parking lot by the smaller playground for safety and improved usage of space.	\$150,000- \$200,000
Walking Path Improvements	Adult fitness stations, shade trees, seating, memorial benches, and ADA access where required.	\$20,000- \$400,000
Landscaped Entrance, Memorials	Install landscape improvements to Veterans Memorial Wall and Children's Garden, including accessible pathways carefully designed to compliment the spaces,topsoil and planting improvements to the gardens.	\$20,000- \$50,000
Expand Rt 20 Parking Lot	Expand the Route 20 parking lot to accommodate horse trailer parking and some additional car parking, and add a new second curb cut onto Route 20 for pull-through access.	\$250,000- \$350,000
DPW Parking Lot	Expand and reconfigure the parking lot by the DPW garage to better utilize the space while providing nedestrian access to Field 4 spectator areas	\$150,000- \$250,000
	Ahrens Park	
Playground	Develop a playground (ages 2-5 and ages 5-12) adjacent to the existing pavilion/ restroom building	\$400,000- \$600,000



Stockerhold Englishments Economical

MARKAGEMENT

1350 Main Stront Suite 1400 Springfield, MA 75103 F 413,726 2300 F 413,735,1249



July 16, 2025 File No. 15.0167378.00

Mike Walsh, Town Manager Town of Granby 15 North Granby Road Granby, CT 06035

Re: Granby Recreation Facilities Analysis Summary Memorandum Granby Parks and Recreation Department

Dear Mr. Walsh,

In accordance with GZA GeoEnvironmental, Inc. ("GZA")'s December 19, 2024 Proposal for Professional Services, we are pleased to provide the Town of Granby ("Town; Client") this summary memorandum describing GZA's efforts in producing the attached Master Plans for Salmon Brook Park and Ahrens Park, hereinafter referred to collectively as the Project. GZA's efforts included a site analysis of existing conditions at the two Town-owned parks, a public engagement process, and development of the two conceptual Master Plans.

This summary memorandum is subject to the limitations included in **Attachment A**. Copies of the Master Plans, public meeting presentations, and online survey results are included as attachments to this letter, respectively.

PROJECT BACKGROUND

The Town of Granby, Connecticut is fortunate to have two generously sized public parks located near the center of town: Salmon Brook Park and Ahrens Park. Salmon Brook Park is a well-used, 116-acre park which offers a wide range of recreational programming and facilities. Ahren's Park offers additional open space with less formal programming and is 45 acres in size.

Salmon Brook Park has served as a public open space since the early 20th century and became formalized as a public park in the early 21st century with many of its existing recreational facilities developed within the past two decades. Ahrens Park was owned by the Ahrens family until 2003 when the town acquired it as a protected open space.

Recreational facilities at Salmon Brook Park currently include softball and baseball fields, soccer and lacrosse fields, tennis and pickleball courts, playgrounds, a dog park, a horse ring, a swimming pond and bath house, a band shell, picnic pavilions, memorial gardens, the Park House building (with offices and public meeting room), a restroom building, walking paths, and access to hiking trails.





Ahren's Park is less programmed. Its formal recreational facilities are limited to a collection of multi-purpose sports fields, a restroom and pavilion building, a bocce court, and the Town's community gardens.

In 2022, to better understand the community's needs, the Town conducted a public survey to learn about park usage, asking what additional elements and programs town residents would like the two parks to have. Possible park improvements that ranked highly included: ice skating area, splash pad, walking paths, additional seating, skate park, and pickleball courts. Over the following two years, the Town began to implement some of these improvements, including new walking paths throughout Salmon Brook Park and the conversion of Salmon Brook Park's tennis court to multi-purpose tennis and pickleball courts.

As these new elements began to be added to the park, and due to fact that park features have varying lifespans requiring updates or replacement, the Town recognized the need for developing a master plan to guide future development and management of the two parks to ensure future improvements are well-coordinated, reflect the community's goals, and make effective use of available resources. To meet this need, the Town engaged GZA to perform the Recreation Facilities Analysis, or "Study", of the two parks. GZA's Study included an inventory of existing conditions, public engagement, and development of master plans for the two parks. The results of the Study are summarized in the following sections of this memorandum.

EXSISTING CONDITIONS INVENTORY

REVIEW OF EXISTING CONDITIONS: SALMON BROOK PARK

GZA reviewed existing site conditions through site visits, GIS mapping, and review of available site plans and documents. GZA found that most of the Town-managed park facilities at Salmon Brook Park are well-maintained and in good condition. Site features that were in need of repair or showing their age included the large playground located at the southern end of the park. Additionally, the informal gravel path connecting the Route 20 parking lot to the soccer fields has experienced erosion likely due to its steepness and lack of proper drainage measures.

Based on conversations with Town staff, GZA learned that sanitary sewer, electrical, and water utilities serve the southern end of the park. Water in the park is sourced from a well located within the park. Irrigation extends throughout the whole developed portion of the park, as far north as the soccer fields.

As its name implies, Salmon Brook Park is located alongside Salmon Brook, and occupies the low-lying, flat topography typically associated with a riparian floodplain. The FEMA Flood Hazard survey for Salmon Brook does not extend into the Project site; however, from conversations with Granby Town staff and park stakeholders, GZA heard that Field 2 and the adjacent playground area flood during heavy rain events, into portions of Field 1. Based on review of publicly-available LIDAR contour data of the site's topography, GZA has estimated the extent of the flood-prone area that had been described, for master planning purposes. Town staff also described to GZA that the edge of Field 3 (third base to home plate) floods periodically, as does the adjacent dog park; though somewhat less frequently and extensively than the playground/ Field 2 area.



REVIEW OF EXISTING CONDITIONS: AHRENS PARK

Ahrens Park is located north of Granby Center on Hungary Road. The developed portion of the park is situated on a flat plateau, while the wooded portions of the site occupy lower-lying riparian areas adjacent to the east branch of Salmon Brook. The site contains football and lacrosse fields, as well as a baseball field in a neglected condition which is not routinely used by the Town's sports leagues. There is also a pavilion and restroom building on the site, a parking lot, and a bocce court. At the north end of the site is the Town's community gardens, which are separated from the rest of the site by a wooded area and have their own driveway entrance.

PUBLIC ENGAGEMENT


PUBLIC ENGAGEMENT: STAKEHOLDER INTERVIEWS

GZA conducted phone interviews with representatives from sports leagues and community organizations ("stakeholders") who regularly use the park and/or maintain their own dedicated facilities within the park. This list of suggested stakeholders was provided by the Town and included:

- Granby Youth Lacrosse: Clay Morad
- Granby/East Granby Little League: Greg Dion
- Granby Rovers Soccer: Austin Busbey
- Granby Youth Football: Dave Collins and Mike Gero
- Granby Horse Council: Joan Davis
- D.O.G.G.S. (Dog Park): Martha Delaney
- Granby Community Gardens: Deborah Roe
- Children's Memorial: Jane Johnson
- Veterans Memorial Wall: Betty Hart
- Live Nativity: Rev. Clark Pfaff
- Town of Granby Summer Camps: Daphne Shinder

Each interview consisted of a 15-30 minute conversation. GZA asked stakeholders about their use of the park and its facilities. Conversations touched upon how each group uses the park, which facilities they maintain, if there are any unmet needs or challenges they face, and if there is a need for coordination with other groups. The input from these conversations helped GZA to develop a holistic understanding of the two parks and how their various facilities and user groups interact, and was used in identifying areas for further public input in the online survey and public meetings (described in the following sections).

From the interviews, GZA learned that Ahrens Park's fields are almost never in use all at once, and therefore there is an opportunity to utilize some of this space for other uses (including potentially locating new facilities here or relocating features from Salmon Brook Park to Ahrens Park if additional space at Salmon Brook Park was needed). Overall, the stakeholder interviews revealed that there is generally good coordination among sports leagues and other uses of the park, resulting in a minimum of congestion and conflict during peak use times. Representatives





from Little League and Rovers Soccer indicated a desire to add lights to some or all of the sports fields, to extend the length of use during the season and usable hours for practices and games.

GZA also had discussions with Town of Granby staff about the parks. In discussions with Town staff, the Salmon Brook Park pickleball courts were identified as a key point of focus for the master plan. The existing tennis courts, which are adjacent to a residential complex, were recently updated to double as pickleball courts. These new pickleball courts have quickly become very popular and are highly used, and the resulting noise of pickleball games has resulted in frequent complaints to the Town from the adjacent residential neighbors. The Town identified a need to identify suitable locations for potentially relocating the pickleball courts.

PUBLIC ENGAGEMENT: ONLINE SURVEY

GZA developed an online public survey consisting of thirteen questions about people's use of the two parks and desires for future improvements. The survey was distributed and advertised by the Town, on the town of Granby website and Town Facebook page, as well as on the Facebook pages of individual Town departments. The survey had a total of 619 respondents. Full survey results are included in **Attachment G**. Results from the survey showed that:

- People tend not to visit Ahrens Park, mainly because of a lack of things to do there.
- Interest in potential new recreational features at Salmon Brook Park included, in order:
 - Water spray deck / splash pad
 - o Ice skating area
 - Updated playground
 - o Adult fitness equipment
 - Pump track (course for bikes)
 - Skate park
- Interest in potential new recreational features at Salmon Brook Park included, in order:
 - Walking paths
 - o Pickleball court
 - o Playground
 - Pump track (course for bikes)
 - Water spray deck / splash pad
- There was interest in relocating the pickleball courts from Salmon Brook Park to Ahrens Park.
- There was support for adding lights to sports fields at the parks.
- Park visitors want additional restroom access at Salmon Brook Park.



PUBLIC ENGAGEMENT: PUBLIC MEETINGS

The Town of Granby held the first of two public meetings for the Project on April 1, 2025. GZA presented a slideshow presentation on the project background and site analysis and facilitated a group discussion to gather public input on future improvements to the parks. Public input heard at the meeting included:

- Ahrens Park is underutilized and has great potential.
- With its horse ring and connection to extensive woodland trails, Salmon Brook Park is a unique and important destination for equestrians in the region. There is a need for a few horse trailer parking spaces somewhere in the park.
- Improvements to the Route 20 parking lot path at Salmon Brook Park should be compatible with equestrian use.
- The existing larger playground at Salmon Brook Park is located adjacent to the brook, which adds a valuable aspect of nature and water access to the play environment.
- Salmon Brook Park needs an additional public restroom.
- Dedicated pickleball courts would be preferable over existing shared tennis/pickleball.
- The three-way intersection at Salmon Brook Park Road can be dangerous and would benefit from stop signs.

At the public meeting, GZA provided a "dot sticker" board activity, where participants could vote for potential new recreational facilities at both parks by placing stickers on the elements they were most interested in. The results of this activity were generally consistent with the online survey. This board is shown in **Attachment E**.

A second in-person public meeting was held in the Park House at Salmon Brook Park during the Parks Commission meeting on June 3, 2025. At this meeting, GZA shared draft master plans for the parks (Master Plans are described in the following section). Public input on the draft plans was limited and included discussion on whether the park's existing parking lots would be able to support additional visitorship resulting from the proposed new recreational facilities depicted in the plans. In response to the discussions at this meeting, GZA revised the plans to include an expanded parking area. The final Master Plans for proposed conditions at Salmon Brook Park and Ahrens Park are described in the next section.

SALMON BROOK PARK AND AHRENS PARK MASTER PLAN

DEVELOPMENT OF CONCEPTUAL MASTER PLANS

The proposed Conceptual Master Plans for both parks (Attachments B and C) depict a future condition in which the highest priority new program elements identified during this Study are arranged in response to the landscape constraints, usage conflicts, and program redundancies identified between both parks, resolving those elements in the process. Implementation of the proposed condition would occur in multiple phases over several years. The two sites' plans are intrinsically tied to each other, because the added program





elements proposed at Salmon Brook Park are accommodated by relocating two of the smaller youth lacrosse fields to Ahrens Park, whose fields are not currently fully utilized.

In developing the master plans, GZA and the Town of Granby reviewed public meeting input and identified which elements made sense for inclusion in the recommendations for both parks, based on the effective use of Town resources, available space, and coordination with other recreational facilities in the region. Most of the elements that were repeatedly identified during the public engagement process are included in the master plan recommendations, with the notable exception of an ice skating area. Because there is an existing skating facility nearby in Simsbury (the International Ice Skating Center of Connecticut), the Town determined that developing one in Granby may not be worth the significant investment required.

The proposed design for Salmon Brook Park is built around the following major organizing schemes:

- A corridor of new recreational facilities is established between the Park House and the central
 parking lot, along the northeast edge of the swimming pond. This corridor is connected by new
 accessible paved pedestrian paths, and includes:
 - New skatepark
 - New splash pad
 - New playground (replaces existing playground currently in flood-prone southern area)
 - New dedicated pickleball courts adjacent to the central parking lot (these are relocated from the tennis courts, which revert to being dedicated tennis courts)

Space for this corridor is made available by relocating two smaller lacrosse fields to Ahrens Park, and relocating Field 3 (softball) to the north. The western edge of this corridor is converted to a vegetated floodplain shrub-meadow landscape, to help mitigate periodic flooding.

• Reconfigured ballfields: Ballfield 1 is rotated, and ballfields 3 and 5 are re-positioned and rotated, so that Fields 1 and 2 and Fields 3 and 5 have their backstops adjacent to one another for consolidated spectator and player access, and Fields 1 and 5 no longer are oriented with the batter facing south (batter facing south is less preferable because of the risk of being blinded by the sun). Ballfield lighting is added to these redeveloped fields, along with upgraded and accessible spectator seating. This reconfiguration of ballfields makes space for the recreation facilities corridor described above, while providing opportunity for improvements to the ballfields themselves as well as pedestrian circulation throughout the park.

Additional proposed improvements to Salmon Brook Park are described in the following section on project phasing.



PHASING AND IMPLEMENTATION

The sequence and phasing of the proposed work is based on both identified priority and spatial coordination. The proposed work should begin with the initial phases outlined below in Table 1. Phases may be combined based on availability of funding. Numbers in the "Plan Legend Number" column correspond to the numbered items on the Master Plan for each park, **Attachments B and C**.

Approximate ranges of costs are indicated for each proposed Park improvement, based on GZA's experience with recent similar projects in the region. Please note that GZA's assignment did not include any detailed design beyond the conceptual master planning level. As such, the ranges of potential costs should be considered "order of magnitude" and used for budgeting and comparison purposes only. Costs are assumed to be inclusive of "soft costs" such as survey, permitting, design/engineering, contingency, and publicly-bid construction. Costs are in 2025 dollars.

SALMON BROOK PARK: PROPOSED PARK IMPROVEMENTS, PHASES 1-5

TABLE 1: Salmon Brook Park, Proposed Park Improvements, Phases 1 - 5				
Phase Recommendation Description		Description	Plan Legend Number	Potential Cost Range
1A	Route 20 Path to Soccer Fields, Improvements for Pedestrian and Equestrian Use	Upgrade the existing path to the Route 20 parking lot, by adding paved surfacing as well as stairs at the steepest sections. Develop an unpaved equestrian trail parallel to this. Expand ADA accessibility from the central parking lot to the soccer fields, connecting to the improved Route 20 path. This is listed as part of Phase 1 because the Town has already received a Small Town Economic Assistance Program (STEAP) grant from the State of Connecticut to implement this project.	19	\$600,000- \$700,000
18	Salmon Brook Park Pickleball Courts and Relocation of Lacrosse Fields	Relocate the two smaller lacrosse fields from Salmon Brook Park to Ahren's park (the two small lacrosse fields that are currently closest to the swimming pond and central parking lot). Build a new pickleball court in Salmon Brook Park off the southern end of the central parking lot (four dedicated pickleball courts, with fencing and lighting). Revert existing court to dedicated tennis.	2, 14	\$400,000- \$500,000



TABLE 1: Salmon Brook Park, Proposed Park Improvements, Phases 1 - 5

Phase	Recommendation	Description	Plan Legend Number	Potential Cost Range
2	Salmon Brook Park Ballfields 3 and 5	Relocate ballfield 3 and re-orient ballfield 5 into configuration shown on Master Plan. Add upgraded and accessible seating, lights, and scoreboards to redeveloped ballfields.	16, 17	\$500,000- \$600,000
3	Playground (Ages 5-12)	Develop a new playground for ages 5-12 in the location shown on Master Plan.	13	\$400,000- \$600,000
4A	Utilities: Electrical, Water, and Sanitary Expansion	Install utilities for the proposed restroom building and splash pad. This should include a study of available water supply which may result in the installation of an additional well to support the proposed features, or alternatively, may result in design recommendations for restroom and spray features with lower water usage.	12, 15	\$200,000- \$300,000
4B	Develop a new restroom building between Fields 3 and 5 and relocated pickleball court, by central parking lot. Assumes utilities are in place from Phase 4A.		\$500,000- \$1,000,000	
4C	Splash Pad	Develop a new splash pad or misting area in the location shown on the Master Plan. Assumes utilities are in place from Phase 4A.	12	\$250,000- \$350,000



SALMON BROOK PARK: ADDITIONAL PROPOSED IMPROVEMENTS

The following improvements listed in Table 2 are less dependent on sequencing of other project phases and could be implemented as stand alone projects at the Town's discretion.

TABLE 2: Salmon Brook Park, Additional Park Improvements				
Recommendation	Description	Plan Legend Number	Potential Cost Range	
3-Way Stop Intersection	Reconfigure the Salmon Brook Park Road 3-way intersection to a 3-way stop intersection (4-way stop including DPW parking lot drive) and reconfigure the parking lot by the smaller playground for safety and improved usage of space.	4	\$150,000- \$200,000	
Skate Park	Develop a 10,000 SF skate park in the location shown in the Master Plan.	11	\$800,000- \$1,000,000	
Nature Play	Develop a nature-play area and gathering space in the flood-prone southern area (where larger playground is proposed to be relocated from), which can be utilized by summer camp programs as well as for general nature-play, including brook access.	9	\$300,000- \$500,000	
New Accessible Parking Lot	Expand the central parking area into the space adjacent to the horse ring and soccer field, to create a new accessible parking lot (and associated stormwater management).	18	\$250,000- \$350,000	
Multiple Exercise Stations Along Path	Develop 5 adult fitness equipment stations at intervals along the park walking path; each station includes safety surfacing and shade trees.	6	\$200,000- \$400,000	
Seating Along Path	Install 5 additional seating areas along walking trails, including shade and memorial benches.	-	\$20,000- \$50,000	
Accessible Walkways	Expand paved accessible walkways to more of the park features, including pavilions, and install ADA upgrades to the band shell.	8, 10	\$100,000- \$200,000	



TABLE 2: Salmon Brook Park, Additional Park Improvements				
Recommendation	Description	Plan Legend Number	Potential Cost Range	
Landscaped Entrance, Memorials	Install landscape improvements to Veterans Memorial Wall and Children's Garden, including accessible pathways carefully designed to compliment the spaces, topsoil and planting improvements to the gardens.	1	\$20,000- \$50,000	
Upgraded Ballfields 1 and 2	Reconfigure and upgrade ballfields 1 and 2 (including lights) as shown on Master Plan	7	\$400,000- \$600,000	
Expand Rt 20 Parking Lot	Expand the Route 20 parking lot to accommodate horse trailer parking and some additional car parking, and add a new second curb cut onto Route 20 for pull-through access.	20	\$250,000- \$350,000	
DPW Parking Lot	Expand and reconfigure the parking lot by the DPW garage to better utilize the space while providing pedestrian access to Field 4 spectator areas.	3	\$150,000- \$250,000	

AHRENS PARK: PROPOSED PARK IMPROVEMENTS

The proposed design for Ahrens Park includes the elements listed below, in Table 3. These improvements can be somewhat flexible in terms of their phasing and sequencing:

TABLE 3: Ahrens Park, Proposed Park Improvements				
Recommendation	Description	Plan Legend Number	Potential Cost Range	
Paved Walking Paths	Install paved, accessible walking paths around the field perimeters, connected to the parking lot.	6	\$200,000- \$300,000	
Playground	Develop a playground (ages 2-5 and ages 5-12) adjacent to the existing pavilion/ restroom building	2	\$400,000- \$600,000	




TABLE 3: Ahrens Park, Proposed Park Improvements			
Recommendation	Description	Plan Legend Number	Potential Cost Range
Football Field Lighting	Upgrade football field and install field lighting	5	\$300,000- \$400,000
Lacrosse Fields	Lacrosse Fields Adjust layout of lacrosse fields to accommodate two small lacrosse fields relocated from Salmon Brook Park		\$5,000- \$10,000
Pump Track	Pump Track Remove neglected baseball field and develop a pump track for bicycles in its location		\$600,000-
Develop a new parking area (and associated stormwater management) parallel to Park driveway entrance, with pull-through vehicular circulation, to expand parking capacity by about 50%.		1	\$250,000- \$350,000
Hiking Trails	Develop hiking trails in the wooded portion of the site, using the existing abandoned road/path down the hillside	10	\$50,000- \$100,000
Additional Pickleball Courts	Potentially develop additional new pickleball courts in the location shown on Ahrens Park Master Plan. Pickleball courts at this location would be in addition to the relocated courts proposed for Salmon Brook Park, not in place of them, since removing pickleball from Salmon Brook Park may result in informal use of the tennis courts for pickleball.	3	\$400,000- \$500,000

SUMMARY OF ANTICIPATED PERMITS

Potential permits for the proposed park improvements may include, but are not necessarily limited to, the following:

For any of the proposed improvements that occur within a wetland/watercourse, or within 100 feet measured horizontally from the boundary of any wetland, or within 200 feet of any vernal pool or watercourse, a permit would be required from the Town of Granby Inland Wetlands & Watercourses Commission. Work directly in a wetland or watercourse would also require a permit from the U.S. Army Corps of Engineers.





A new curb cut and driveway at the Route 20 parking lot would require an Encroachment Permit from the Connecticut Department of Transportation, and a Town of Granby Driveway Permit.

Any proposed work impacting more than one acre of land will require a Construction General Permit (CGP) under the National Pollutant Discharge Elimination System (NPDES), which includes preparation of a Stormwater Pollution Prevention Plan (SWPPP).

Installation of a new well would require a permit from the Farmington Valley Health District.

A Building Permit from the Town of Granby would be required for the construction of new buildings, outbuildings, or any improvement that requires the installation or movement of mechanical, electrical, heating or plumbing equipment or components.

CLOSING

We appreciate the opportunity to assist the Town of Granby on this project and look forward to discussing this with you further. Please contact us at (413) 726-2100 if you have any questions concerning this summary memorandum.

Consultant / Reviewer

Very truly yours,
GZA GEOENVIRONMENTAL, INC.

Daniel Shaw, PLA Landscape Architect

Landscape Architect

Stephen Lecco,

For Nathaniel L. Russell, P.E.

Principal-in-Charge

Attachments:

Attachment A - Limitations

Attachment B - Salmon Brook Park Master Plan

Attachment C - Ahrens Park Master Plan

Attachment D - Public Meeting Presentation #1

Attachment E - Public Meeting Dot Sticker Voting Boards

Attachment F - Public Meeting Presentation #2

Attachment G - Online Survey Results

ATTACHMENT A: LIMITATIONS



USE OF REPORT

GZA GeoEnvironmental, Inc. (GZA) prepared this report on behalf of, and for the exclusive use of our Client for
the stated purpose(s) and location(s) identified in the Proposal for Services and/or Report. Use of this report, in
whole or in part, at other locations, or for other purposes, may lead to inappropriate conclusions; and we do not
accept any responsibility for the consequences of such use(s). Further, reliance by any party not expressly identified in the contract documents, for any use, without our prior written permission, shall be at that party's sole risk,
and without any liability to GZA.

STANDARD OF CARE

- 2. GZA's findings and conclusions are based on the work conducted as part of the Scope of Services set forth in Proposal for Services and/or Report, and reflect our professional judgment. These findings and conclusions must be considered not as scientific or engineering certainties, but rather as our professional opinions concerning the limited data gathered during the course of our work. If conditions other than those described in this report are found at the subject location(s), or the design has been altered in any way, GZA shall be so notified and afforded the opportunity to revise the report, as appropriate, to reflect the unanticipated changed conditions.
- GZA's services were performed using the degree of skill and care ordinarily exercised by qualified professionals
 performing the same type of services, at the same time, under similar conditions, at the same or a similar
 property. No warranty, expressed or implied, is made.
- 4. In conducting our work, GZA relied upon certain information made available by public agencies, Client and/or others. GZA did not attempt to independently verify the accuracy or completeness of that information. Inconsistencies in this information which we have noted, if any, are discussed in the Report.

SUBSURFACE CONDITIONS

- 5. In preparing this report, GZA relied on certain information provided by the Client, state and local officials, and other parties referenced therein which were made available to GZA at the time of our evaluation. GZA did not attempt to independently verify the accuracy or completeness of all information reviewed or received during the course of this evaluation. If variations or other latent conditions then become evident, it will be necessary to reevaluate the conclusions and recommendations of this report.
- 6. Site-specific evaluation of groundwater levels have not been made. Fluctuations in the level of the groundwater should be anticipated to occur due to temporal or spatial variations in areal recharge rates, soil heterogeneities, the presence of subsurface utilities, and/or natural or artificially induced perturbations. The water table encountered in the course of the work may differ from that indicated in the Report.
- 7. GZA's services did not include an assessment of the presence of oil or hazardous materials at the project location. Consequently, we did not consider the potential impacts (if any) that contaminants in soil or groundwater may have on construction activities, or the use of structures on the property.

COMPLIANCE WITH CODES AND REGULATIONS

8. We used reasonable care in identifying and interpreting applicable codes and regulations. These codes and regulations are subject to various, and possibly contradictory, interpretations. Compliance with codes and regulations by other parties is beyond our control.



COST ESTIMATES

- 9. Unless otherwise stated, our cost estimates are only for comparative and general planning purposes. These estimates may involve approximate quantity evaluations. Note that these quantity estimates are not intended to be sufficiently accurate to develop construction bids, or to predict the actual cost of work addressed in this Report. Further, since we have no control over either when the work will take place or the labor and material costs required to plan and execute the anticipated work, our cost estimates were made by relying on our experience, the experience of others, and other sources of readily available information. Actual costs may vary over time and could be significantly more, or less, than stated in the Report.
- 10. Cost opinions presented in the Report are based on a combination of sources and may include published RS Means Cost Data; past bid documents; cost data from federal, state or local transportation agency web sites; discussions with local experienced contractors; and GZA's experience with costs for similar projects at similar locations. GZA did not attempt to independently verify the accuracy or completeness of all information reviewed or received during the course of this evaluation. Actual costs will likely vary depending on the quality of materials and installation; manufacturer of the materials or equipment; field conditions; geographic location; access restrictions; phasing of the work; subcontractors mark-ups; quality of the contractor(s); project management exercised; and the availability of time to thoroughly solicit competitive pricing. In view of these limitations, the costs presented in the Report should be considered "order of magnitude" and used for budgeting and comparison purposes only. Detailed quantity and cost estimating should be performed by experienced professional cost estimators to evaluate actual costs. The opinions of cost in the Report should not be interpreted as a bid or offer to perform the work. Unless stated otherwise, all costs are based on present value.
- 11. The opinion of costs are based only on the quantity and/or cost items identified in the Report, and should not be assumed to include other costs such as legal, administrative, permitting or others. The estimate also does not include any costs with respect to third-party claims, fines, penalties, or other charges which may be assessed against any responsible party because of either the existence of present conditions or the future existence or discovery of any such conditions.

ADDITIONAL SERVICES

12. GZA recommends that we be retained to provide services during any future: site observations, design, implementation activities, construction and/or property development/redevelopment. This will allow us the opportunity to: i) observe conditions and compliance with our design concepts and opinions; ii) allow for changes in the event that conditions are other than anticipated; iii) provide modifications to our design; and iv) assess the consequences of changes in technologies and/or regulations.

ATTACHMENT B: SALMON BROOK PARK MASTER PLAN



- 1 LANDSCAPED ENTRANCE, VETERAN'S MEMORIAL WALL/GARDEN
- 2 DEDICATED TENNIS COURTS
- 3 PARKING LOT EXPANSION AND RECONFIGURATION
- (4) 3-WAY STOP INTERSECTION
- (5) NEW PARKING CONFIGURATION AT SMALL PLAYGROUND
- (6) MULTIPLE FITCORE/ATHLETIC EXERCISE STATIONS ALONG PATH
- (7) REORIENTATION OF FIELD #1
- (8) WHEELCHAIR ACCESSIBLE PATHS TO PAVILIONS, BASKETBALL
- (9) NATURE PLAY AREA (ORIGINAL LARGE PLAYGROUND LOCATION)
- (10) PATHWAY CONNECTION BETWEEN LACROSSE AND BALL FIELDS
- (11) SKATEPARK
- (12) WATER SPRAY DECK/SPLASHPAD
- (3) NEW PLAYGROUND (5-12 YEAR OLD)
- (4) DEDICATED PICKLEBALL COURTS WITH LIGHTING
- 15 NEW PUBLIC RESTROOM BUILDING
- (16) REORIENTATION AND RELOCATION OF FIELD #3
- (17) REORIENTATION OF FIELD #5
- (18) NEW ACCESSIBLE PARKING LOT
- 19) NEW TRAIL ALIGNMENT FOR PEDESTRIAN, EQUESTRIAN USE
- 20 DEDICATED EQUESTRIAN PARKING AND EXIT TO ROUTE 20

ATTACHMENT C: AHRENS PARK MASTER PLAN



- 1 INCREASED PARKING CAPACITY, PULL-THROUGH LOT
- (2) NEW PLAYGROUND FEATURES (2-5 AND 5-12 YEAR OLD)
- (3) DEDICATED PICKLEBALL COURTS


- 4 ALL WHEELS PUMP TRACK
- (5) RESTORATION, LIGHTING FOR FOOTBALL/LACROSSE FIELD
- 6 PERIMETER WALKING PATHS (APPROXIMATELY 3/4 MILE)
- 7 RELOCATED LACROSSE FROM SALMON BROOK
- 8 ADJUSTMENT TO LACROSSE FIELD
- ADJUSTMENT TO LACROSSE FIELD

10) BACKCOUNTRY HIKING AND MOUNTAIN BIKE TRAILS WITH BROOK ACCESS






- 1 LANDSCAPED ENTRANCE, VETERAN'S MEMORIAL WALL/GARDEN
- (2) DEDICATED TENNIS COURTS
- 3 PARKING LOT EXPANSION AND RECONFIGURATION
- (4) 3-WAY STOP INTERSECTION
- (5) NEW PARKING CONFIGURATION AT SMALL PLAYGROUND
- 6 MULTIPLE FITCORE/ATHLETIC EXERCISE STATIONS ALONG PATH
- 7 REORIENTATION OF FIELD #1
- 8 WHEELCHAIR ACCESSIBLE PATHS TO PAVILIONS, BASKETBALL
- (9) NATURE PLAY AREA (ORIGINAL LARGE PLAYGROUND LOCATION)
- 10 PATHWAY CONNECTION BETWEEN LACROSSE AND BALL FIELDS
- (11) SKATEPARK FEATURE
- (12) WATER SPRAY DECK/SPLASHPAD FEATURE
- (13) NEW PLAYGROUND (5-12 YEAR OLD)
- (14) DEDICATED PICKLEBALL COURTS
- (15) NEW PUBLIC RESTROOM BUILDING
- (16) REORIENTATION AND RELOCATION OF FIELD #3
- (17) REORIENTATION OF FIELD #5
- (18) MINI-PITCH SOCCER FEATURE
- (19) NEW TRAIL ALIGNMENT FOR PEDESTRIAN, EQUESTRIAN USE
- (20) DEDICATED EQUESTRIAN PARKING AND EXIT TO ROUTE 20



- 1 INCREASED PARKING CAPACITY, PULL THROUGH LOT
- 2 NEW PLAYGROUND FEATURES (2-5 AND 5-12 YEAR OLD)
- 3 SPORTS/ATHLETIC CLUB HOUSE

- 4 DEDICATED PICKLEBALL COURTS
- (5) LOCATION ADJUSTMENT TO FOOTBALL/LACROSSE FIELD
- 6 PERIMETER WALKING PATHS (APPROXIMATELY 3/4 MILE)
- 7 RELOCATED LACROSSE FROM SALMON BROOK
- 8 ADJUSTMENT TO LACROSSE FIELD
- (9) CYCLE/SCOOTER PUMP TRACK FEATURE
- 10 RELOCATED LACROSSE FROM SALMON BROOK
- (1) ADJUSTMENT TO LACROSSE FIELD
- (12) BACKCOUNTRY HIKING/MOUNTAIN BIKE TRAILS FOR WATER, CREEK ACCESS



SOLIBORS LICONNICLEAR OF DEEP ONES NEARMAN

- 1 INCREASED PARKING CAPACITY, PULL THROUGH LOT
- 2 NEW PLAYGROUND FEATURES (2-5 AND 5-12 YEAR OLD)
- 3 SPORTS/ATHLETIC CLUB HOUSE

- 4 DEDICATED PICKLEBALL COURTS
- 5 LOCATION ADJUSTMENT TO FOOTBALL/LACROSSE FIELD
- 6 PERIMETER WALKING PATHS (APPROXIMATELY 3/4 MILE)
- 7 RELOCATED LACROSSE FROM SALMON BROOK
- 8 ADJUSTMENT TO LACROSSE FIELD
- CYCLE/SCOOTER PUMP TRACK FEATURE
- 10 RELOCATED LACROSSE FROM SALMON BROOK
- (11) ADJUSTMENT TO LACROSSE FIELD
- (2) BACKCOUNTRY HIKING/MOUNTAIN BIKE TRAILS FOR WATER, CREEK ACCESS



- (1) LANDSCAPED ENTRANCE, VETERAN'S MEMORIAL WALL/GARDEN
- 2 DEDICATED TENNIS COURTS
- 3 PARKING LOT EXPANSION AND RECONFIGURATION
- (4) 3-WAY STOP INTERSECTION
- 5 NEW PARKING CONFIGURATION AT SMALL PLAYGROUND
- (6) MULTIPLE FITCORE/ATHLETIC EXERCISE STATIONS ALONG PATH
- 7 REORIENTATION OF FIELD #1
- (8) WHEELCHAIR ACCESSIBLE PATHS TO PAVILIONS, BASKETBALL
- NATURE PLAY AREA (ORIGINAL LARGE PLAYGROUND LOCATION)
- (10) PATHWAY CONNECTION BETWEEN LACROSSE AND BALL FIELDS
- (11) SKATEPARK FEATURE
- (12) WATER SPRAY DECK/SPLASHPAD FEATURE
- (13) NEW PLAYGROUND (5-12 YEAR OLD)
- (14) DEDICATED PICKLEBALL COURTS
- (15) NEW PUBLIC RESTROOM BUILDING
- 16 REORIENTATION AND RELOCATION OF FIELD #3
- 17 REORIENTATION OF FIELD #5
- (18) MINI-PITCH SOCCER FEATURE
- (19) NEW TRAIL ALIGNMENT FOR PEDESTRIAN, EQUESTRIAN USE
- 20) DEDICATED EQUESTRIAN PARKING AND EXIT TO ROUTE 20



GRANBY MEMORIAL HIGH SCHOOL ATHLETIC FACILITY IMPROVEMENTS



Date: April 21, 2025

Prepared For: Karl Gates - Athletic Director & Student Activities Coordinator

Prepared By: Andrew Dyjak – Regional Vice President, New England

Chris Hulk, PE - Regional Vice President, New England

Jonathan Luster, PE – Regional Construction Manager, New England

Address: Granby Memorial High School | 54 N Granby Rd, Granby, CT 06035

FieldTurf pricing is based on the Capital Region Education Council (CREC) program. CREC is a member of The Association of Educational Purchasing Agencies (AEPA) program. The AEPA is a purchasing co-op that provides member schools with pre-determined preferential pricing by approved vendors. Since the product has already been bid at the national level, individual schools do not have to duplicate the formal bid process. AEPA IFB #024.



Click on the following AEPA hyperlink for more information: <u>AEPA IFB #24</u>

Master Review Approach:

FieldTurf has reviewed each site on the campus with School and Town staff to review both existing conditions and future development desires. Through this process FieldTurf has become familiar with the needs and wants of the School to best serve the School and Town moving forward. The recommendations that are proposed below are based on hundreds of Connecticut installations, the design build approach that has become the preferred procurement method of many municipalities in the New England area and by in house professional engineering staff design.

A conceptual layout plan has been developed for each site with associated budgets. These budgets are subject to change and be altered upon further refinement of scope between FieldTurf and the School/Town. FieldTurf will help develop the final scope of the project, then develop professionally engineered plans tailored to each site and finally assist the School/Town with obtaining permits.

FieldTurf is part of Tarkett Sports and has become the industry leader in synthetic turf, design build and athletic facility development. Through Tarkett Sports we have in house post tension concrete court division, synthetic track divisions, synthetic turf divisions, long term care divisions and partnerships with various lighting companies. All of these have helped to develop the attached scopes and budgets.



Overview Pricing:

Below are suggested project scope items for each site. Full break down has been included in individual budgets and may contain additional options for consideration.

-	Track and Field Option 2 Reconstruction Synthetic Turf Replacement Synthetic Track Renovation Ball Netting New Bleachers with Press Box	Suggested Budget	\$ 600,000 - \$750,000 \$ 675,000 - \$750,000 \$ 755,000 - \$940,000 \$ 135,000 - \$170,000 \$ 650,000 - \$ 750,000 \$2,815,000 - \$3,360,000
-	Baseball / Softball Field o Field Reconstruction o New Scoreboard o Athletic Field Lighting	Suggested Budget	\$ 2,850,000 - \$3,450,000 \$ 90,000 - \$ 125,000 \$ 675,000 - \$ 750,000 \$3,615,000 - \$4,325,000
-	Tennis Courts O Post Tension Concrete Courts O Walkways and Plantings	Suggested Budget	\$ 1,200,000 - \$ 1,300,000 \$115,000 - \$150,000 \$1,315,000 - \$1,450,000
-	Field 2	Suggested Budget	\$ 650,000 - \$ 700,000 \$ 45,000 - \$ 85,000 \$65,000 - \$ 95,000 <i>\$ 760,000 - \$ 880,000</i>

Suggested Referendum Proposal:

\$8,505,000 - \$10,015,000

The suggested referendum proposal is provided as an overall budget for the Town to procure funds for the overall project to be completed. FieldTurf will work with the Town to develop the final scope of the project to allow a firm price and project prior to development of a referendum. It is likely that the provided budget numbers will be revised after additional scope refinement.






- NOTES:

 1) ALL DESIGN AND EXISTING CONDITIONS MAPPING BASED ON AVAILABLE MAPPING AND SHOULD BE CONSIDERED APPROXIMATE.
- 2) THIS DESIGN IS THE SOLE PROPERTY OF FIELDTURF, USA AND REQUIRES A CERTIFIED FIELDTURF INSTALLER AND BUILDER TO IMPLEMENT THE PROPOSED CONDITIONS.
- 3) THIS DESIGN IS THE SOLE PROPERTY OF FIELDTURF, USA AND NO ATTEMPTS SHALL BE MADE TO DUPLICATE OR REPLICATE WITHOUT THE PREMISSION OF FIELDTURF.

GRANBY MEMORIAL HIGH SCHOOL ATHLETIC FACILITIES

39 SCHOOL STREET GRANBY, CONNECTICUTACHUSETTS



FULL SITE

APRIL 15, 2025



GRANBY MEMORIAL HIGH SCHOOL TRACK & FIELD IMPROVEMENTS







Existing Conditions Aerial

Conceptual Layout

Date: April 18, 2025

Prepared For: Karl Gates - Athletic Director & Student Activities Coordinator

Prepared By: Andrew Dyjak – Regional Vice President, New England

Chris Hulk, PE - Regional Vice President, New England

Jonathan Luster, PE – Regional Construction Manager, New England

Address: Granby Memorial High School | 54 N Granby Rd, Granby, CT 06035

This budget proposal encompasses all facets of the project, with FieldTurf offering a comprehensive, turnkey solution that includes design, project oversight, and construction. The budget is based on current site conditions, review meeting with the school, and the planned construction period in spring/summer 2026.

FieldTurf pricing is based on the Capital Region Education Council (CREC) program. CREC is a member of The Association of Educational Purchasing Agencies (AEPA) program. The AEPA is a purchasing co-op that provides member schools with pre-determined preferential pricing by approved vendors. Since the product has already been bid at the national level, individual schools do not have to duplicate the formal bid process. AEPA IFB #024.



Click on the following AEPA hyperlink for more information: AEPA IFB #24

Below is a detailed cost breakdown for site construction, turf installation and overall implementation of the project.



Project Description:

The existing track and field at Granby Memorial High School is in need of remediation efforts from sinks holes that have developed along the eastern side of the track / field. Based on geotechnical information provided by the Town, it appears that organic material has decayed below the eastern side of the track / field. The depths of this material are present up to 10' below existing grade.

Several options for remediation efforts have been developed with associated budgets. Final scope will require additional discussion and planning with the School and Town. FieldTurf has developed each option as a stand-alone project and also included several alternatives for consideration. For example, as part of Option 2, various areas of the track and field will need to be removed and based on the age and amount of removal it would be prudent to replace the full extent of the track surfacing and turf surfacing to begin new warranty period. Lastly, alternates have been included for site improvements such as LED lighting, press box, ball netting, etc...

Depending on final scope, the project is anticipated to be constructed in a ±3-4-month timeframe. It is also anticipated that access and staging areas will be available nearby. This budget is intended to assist the school in preparing for this project. Additional discussions, review and programming will be required to refine the scope and budget prior to construction.

FIELD REMEDIATION OPTIONS:

> Option 1 \$1,150,000 - \$1,300,000

- General Scope: Reconstruction of +/- 1/3 of Track/Field
 - Remove and dispose of existing track surfacing within limits shown
 - Cut and remove existing synthetic turf up to soccer field limits
 - Full depth mill of existing track pavement within limits shown
 - Excavate, remove and salvage existing field stone base and processed aggregate track base
 - Remove and dispose of existing turf anchor curb and track drain within limits shown
 - o Remove and salvage existing storm drainage piping
 - o Remove and dispose of existing electrical conduit and wiring within field area
 - Excavate and remove existing soils to a depth of approximately 10' to remove unsuitable soils
 - o Provided adequate shoring and safety measures
 - o Town provided 3rd party field testing agency
 - Furnish and install new subgrade materials, compact in lifts to geotechnical recommendations
 - o Furnish and install geogrid support mesh in 2 layers
 - o Reinstall drainage piping and electrical conduits
 - Furnish and install new ACO drain and concrete turf anchor curb
 - o Reinstall appropriate base materials for track and field areas
 - o Install new pavement from limits of removal
 - Furnish and install new track surfacing and striping within limits shown
 - o Furnish and install new synthetic turf within limits shown



> Option 2 \$600,000 - \$750,000

- General Scope: Extensive Exploration and Solidify
 - o GPS located major sink hole areas and record for future exploration use
 - o Remove and dispose of existing track surfacing within limits shown
 - o Remove existing infill and roll back existing synthetic turf to soccer limits
 - o Full depth mill of existing track pavement within limits shown
 - Excavate, remove and salvage existing field stone base and processed aggregate track base as necessary
 - Remove and dispose of existing turf anchor curb and track drain in various areas and install new
 - o Remove and replace damaged sections of drainage piping
 - Remove and dispose of existing electrical conduit and wiring if encountered during exploration
 - Conduct a series of 10' deep x 2' diameter augur holes along eastern side of track / field
 - o Remove and dispose of excavated material
 - Install flowable fill in all excavated holes to a depth of approximately 1' below finished grade
 - o Furnish and install geogrid support mesh prior to backfill
 - o Town provided 3rd party field testing agency
 - Furnish and install new subgrade materials, compact in lifts to geotechnical recommendations
 - o Reinstall drainage piping and electrical conduits as necessary
 - o Furnish and install new ACO drain and concrete turf anchor curb
 - o Reinstall appropriate base materials for track and field areas
 - o Install new pavement from limits of removal
 - o Furnish and install new track surfacing and striping within limits shown
 - o Furnish and install new synthetic turf within limits shown

SYNTHETIC TURF IMPROVEMENTS

Synthetic Turf Installation

\$675,000 - \$750,000

- Remove and recycle existing synthetic turf carpet and infill
- Laser grade base stone and supplement base stone as needed in order to achieve planarity prior to turf installation
- Furnish and install synthetic turf for field
- Synthetic turf with SBR rubber and sand infill
- Colored end zone
- Alternating turf panels
- Post installation GMAX field testing

End Zone Letters

\$15,000 - \$28,000

"GRANBY" end zone lettering

\$15,000 - \$20,000

Midfield Logo

Midfield Grizzly Style Logo



TRACK IMPROVEMENTS

> Track Base Reconstruction \$375,000 - \$450,000

- Remove and dispose of existing rubberized track surface
- Mill and dispose of existing asphalt base (Top 1.5")
- Pave 1.5" asphalt base
 - o Match grades to existing perimeter trench drain which is to remain

Track Surfacing BSS-100

\$350,000 - \$450,000

- Supply and install Beynon BSS-100 polyurethane track surfacing
 - o Base color: Beynon red
- · Perform track striping

OR

> Track Surfacing BSS-300

\$580,000 - \$650,000

- Supply and install Beynon BSS-300 polyurethane track surfacing
 - Base color: Beynon red
- Perform track striping

Colored Exchange Zones

\$30,000 - \$40,000

• (3) colored exchange zones

SITE IMPROVEMENTS

New Perimeter Chain Link Fencing (1500 L.F.)

\$70,000 - \$80,000

- Existing foundations and poles to remain and be painted
- Supply and install new 4' height chain link mesh, top and bottom rails, and hardware

20' Height Ball Safety Netting

\$80,000 - \$95,000

 Supply and install 20-foot-high ball safety netting in D-Zones, including foundations, sleeves, poles, netting, and hardware along the field end lines

> 10' Height Ball Safety Netting

\$55,000 - \$75,000

 Supply and install 10-foot-high ball safety netting in corners of field up to 20 yard line, including foundations, sleeves, poles, netting, and hardware along the field end lines

Press Box \$175,000 - \$225,000

- Furnish and install new press box behind existing bleachers
- Includes new foundation and support structure
- ADA access lift listed as separate item if needed

> ADA Lift \$95,000 - \$125,000

- Furnish and install new ADA accessible lift to press box
- Includes foundation and installation



Retrofit of Existing Athletic Lighting

\$200,000 - \$250,000

- Remove and dispose of existing light fixtures and replace with LED fixtures
- Poles to remain

New Bleachers with Press Box

\$650,000 - \$750,000

- Furnish and install new double sided bleachers to service both fields (+/- 400 seats)
- Furnish and install press box between fields for use for both fields
- Furnish and install concrete slab for bleachers
- Provide power supply

EXCLUSIONS

- Any costs associated with necessary charges relating to the delineation of the field
- The supply of manholes or clean-outs or grates, or supply of the manhole covers
- Any alteration or deviation from specifications involving extra costs, which alteration or deviation will be provided only upon executed change orders, and will become an extra charge over and above the offered price
- Soil stabilization or remediation of any type
- Mass Excavation as required to achieve subgrade
- > Rock excavation
- Offsite disposal of generated spoils

- Excavation or disposal of unsuitable or contaminated soils
- Site security
- Once subgrade has been established, a proof roll will be performed to ensure structural stability of the soils; in the event that unsuitable soils are encountered, a price to remedy these areas can be negotiated based on recommended methods per project Engineer
- > Testing or Inspection Fees
- Site restoration, sodding, landscaping or growin beyond disturbed areas
- Repair or resurfacing existing asphalt parking lot if damaged by truck traffic
- Bond fees and non-local permits

Please feel free to reach out to any member of our project team with questions about our offer:

Andrew Dyjak

Regional Vice President (860) 333-7839 Andrew.Dyjak@Fieldturf.com **Chris Hulk**

Regional Vice President 203-676-4445 christopher.hulk@fieldturf.com Jonathan Luster, PE

Regional Construction Manager (860) 227-4915

Jonathan.Luster@FieldTurf.com







EXAMPLE PROJECT 2

EXAMPLE PROJECT 3





EXAMPLE DOUBLE SIDED BLEACHER



EXAMPLE BALL NETTING



EXAMPLE SCOREBOARD




- NOTES:

 1) ALL DESIGN AND EXISTING CONDITIONS MAPPING BASED ON AVAILABLE MAPPING AND SHOULD BE CONSIDERED APPROXIMATE.
- 2) THIS DESIGN IS THE SOLE PROPERTY OF FIELDTURF, USA AND REQUIRES A CERTIFIED FIELDTURF INSTALLER AND BUILDER TO IMPLEMENT THE PROPOSED CONDITIONS.
- 3) THIS DESIGN IS THE SOLE PROPERTY OF FIELDTURF, USA AND NO ATTEMPTS SHALL BE MADE TO DUPLICATE OR REPLICATE WITHOUT THE PREMISSION OF FIELDTURF.

GRANBY MEMORIAL HIGH SCHOOL TRACK & FIELD

39 SCHOOL STREET GRANBY, CONNECTICUTACHUSETTS



TRACK & FIELD

APRIL 15, 2025



GRANBY MEMORIAL HIGH SCHOOL BASEBALL & SOFTBALL IMPROVEMENTS







Existing Conditions Aerial

Conceptual Layout

Date: April 21, 2025

Prepared For: Karl Gates - Athletic Director & Student Activities Coordinator

Prepared By: Andrew Dyjak – Regional Vice President, New England

Chris Hulk, PE - Regional Vice President, New England

Jonathan Luster, PE – Regional Construction Manager, New England

Address: Granby Memorial High School | 54 N Granby Rd, Granby, CT 06035

This budget proposal encompasses all facets of the project, with FieldTurf offering a comprehensive, turnkey solution that includes design, project oversight, and construction. The budget is based on current site conditions, review meeting with the school, and the planned construction period in spring/summer 2026.

FieldTurf pricing is based on the Capital Region Education Council (CREC) program. CREC is a member of The Association of Educational Purchasing Agencies (AEPA) program. The AEPA is a purchasing co-op that provides member schools with pre-determined preferential pricing by approved vendors. Since the product has already been bid at the national level, individual schools do not have to duplicate the formal bid process. AEPA IFB #024.



Click on the following AEPA hyperlink for more information: AEPA IFB #24

Below is a detailed cost breakdown for site construction, turf installation and overall implementation of the project.



Project Description:

This project proposes to reconstruct the existing baseball to a new all-weather synthetic turf field with baseball, softball and overlay fields.

The existing field will have all fencing, topsoil, irrigation, and clay removed. Earthmoving activities will be conducted to achieve proposed grades. The field will then have the concrete turf anchor curbing, stone base, and drainage system installed. Fencing of various heights and sizes will be installed and be integral to the concrete turf anchor curb. Additionally, a tension netting backstop system extending from one dugout to the other is proposed. Additional scope items such as new dugouts, new LED light fixtures, bleachers, and walkways have been added as alternates to the base bid.

Depending on final scope, the project is anticipated to be constructed in a ± 4-month timeframe. It is also anticipated that access and staging areas will be available nearby. This budget is intended to assist the town in preparing for this project. Additional discussions, review, and programming will be required to refine the scope and budget prior to construction.

Note: All plans will be developed by FieldTurf in house licensed professionally engineering staff

Site Civil Construction

- o Install Sediment and Erosion Controls Including Construction Entrance Pad
- Remove Existing Topsoil, Irrigation, And Fencing
 - Topsoil To Be Removed from Site
- Import / Export General Fill to Meet Proposed Field Grades
- Cut And Cap Existing Irrigation System
 - Install Turf Box with Quick Coupler Connection
- Furnish And Install All Concrete Turf Anchor Curbing
- Furnish And Install Fencing and Netting as Applicable
- Furnish And Install Storm Drainage Piping and Flat Panel Drains
- Installation Of Dynamic Stone Base Layers and Storm Drainage Overflow
- Furnish And Install Concrete Pads and Walkways
- Furnish And Install Tension Netting Backstop
- Furnish And Install Batting Cage/ Bullpen Area
- o Fine Grade Field in Preparation of Synthetic Turf
- Furnish And Install Concrete Slab for Dugouts and Portable Bleachers
- Improve Paved Access to Field
- Install Finish Materials and Restore Site to Pre-Construction Conditions

Synthetic Turf

- o Furnish And Install Synthetic Turf for Field
- Synthetic Turf with SBR Rubber and Sand Infill
- Colors And Field Markings as Shown on Rendering
- No logos or specialize lettering
- Post Installation GMAX Field Testing

SUGGESTED PROJECT BUDGET

\$ 2,900,000-\$ 350,000



- Contingency
 - A typical project of this type and scope we would suggest a contingency for design, general conditions, and construction of 8% - 10%. This contingency would provide the School / Town level of safety for unknown site conditions such as rock removal, unsuitable soils, etc.
- Alternate: New Scoreboard

\$90,000 - \$125,000

- o Furnish And Install Multi-Use Scoreboard
- o Assumed Programmable Boards with Display/Naming Panel Above Board
- Scoreboard (8'H X 25'W)
- Alternate: New LED Lighting Fixtures

\$675,000 - \$750,000

- o Furnish And Install New LED Light Fixtures on Existing Poles
- o Assumed 8 Pole System
- New Power Supply within 100' of Field

EXCLUSIONS

- Any costs associated with necessary charges relating to the delineation of the field
- The supply of manholes or clean-outs or grates, or supply of the manhole covers
- Any alteration or deviation from specifications involving extra costs, which alteration or deviation will be provided only upon executed change orders, and will become an extra charge over and above the offered price
- Soil stabilization or remediation of any type
- Mass Excavation as required to achieve subgrade
- > Rock excavation or ledge removal
- Offsite disposal of generated spoils

- Excavation or disposal of unsuitable or contaminated soils
- Site security
- Once subgrade has been established, a proof roll will be performed to ensure structural stability of the soils; in the event that unsuitable soils are encountered, a price to remedy these areas can be negotiated based on recommended methods per project Engineer
- > Testing or Inspection Fees
- Site restoration, sodding, landscaping or growin beyond disturbed areas
- Repair or resurfacing existing asphalt parking lot if damaged by truck traffic
- Bond fees and non-local permits

Please feel free to reach out to any member of our project team with questions about our offer:

Andrew Dyjak

Regional Vice President (860) 333-7839 Andrew.Dyjak@Fieldturf.com **Chris Hulk**

Regional Vice President 203-676-4445

christopher.hulk@fieldturf.com

Jonathan Luster, PE

Regional Construction Manager (860) 227-4915

<u>Jonathan.Luster@FieldTurf.com</u>












- NOTES:

 1) ALL DESIGN AND EXISTING CONDITIONS MAPPING BASED ON AVAILABLE MAPPING AND SHOULD BE CONSIDERED APPROXIMATE.

GRANBY MEMORIAL HIGH SCHOOL BASEBALL FACILITY IMPROVEMENTS

PLEASANT STREET GRANBY, CONNECTICUT



BASEBALL

APRIL 14, 2025



GRANBY MEMORIAL HIGH SCHOOL TENNIS COURT IMPROVEMENTS







Existing Conditions Aerial

Conceptual Layout

Date: April 18, 2025

Prepared For: Karl Gates - Athletic Director & Student Activities Coordinator

Prepared By: Andrew Dyjak – Regional Vice President, New England

Chris Hulk, PE - Regional Vice President, New England

Jonathan Luster, PE – Regional Construction Manager, New England

Address: Granby Memorial High School | 54 N Granby Rd, Granby, CT 06035

This budget proposal encompasses all facets of the project, with FieldTurf offering a comprehensive, turnkey solution that includes design, project oversight, and construction. The budget is based on current site conditions, review meeting with the school, and the planned construction period in spring/summer 2026.

FieldTurf pricing is based on the Capital Region Education Council (CREC) program. CREC is a member of The Association of Educational Purchasing Agencies (AEPA) program. The AEPA is a purchasing co-op that provides member schools with pre-determined preferential pricing by approved vendors. Since the product has already been bid at the national level, individual schools do not have to duplicate the formal bid process. AEPA IFB #024.



Click on the following AEPA hyperlink for more information: AEPA IFB #24

Below is a detailed cost breakdown for site construction, court installation and overall implementation of the project.



Project Description:

This project proposes to reconstruct the existing tennis courts to new post tension concrete courts. The existing tennis courts will be reclaimed in place and regrade to meet current standards. All existing vegetation, fencing, pavement and netting will be removed and disposed of. The reconstruction will also include all new post tension concrete courts, fencing, netting and court surfacing. Additionally, alternates have been added to the areas outside of the courts for new plantings, walkways, lighting, etc...

The project is expected to be completed in +/- 3 months. The courts will be constructed in two separate slabs to accommodate the grade changes and court layout. It is anticipated that access and staging areas will be available nearby. This budget is intended to assist the school in preparing for this project. Additional discussions, review and programming will be required to refine the scope and budget prior to construction.

Note: All plans will be developed by FieldTurf in house licensed professionally engineering staff

> TENNIS COURT RECONSTRUCTION

\$1,200,000 - \$1,300,000

- Tennis Court Reconstruction
 - o Install Sediment & Erosion Controls
 - o Remove Existing Site Features
 - Reclaim Existing Pavement In Place
 - Perform Mass Earthwork Operations
 - Cuts And Fills to Meet Proposed Subgrade
 - o Laser Grade Subgrade and Compact
 - o Furnish And Install Gravel Base and Processed Aggregate Base Materials
 - o Furnish And Install New Net Footings, Posts, Nets and Center Straps
 - o Furnish And Install 5-1/2" Post Tensioned Concrete Court Slab
 - Structural Warranty of 50 years is included
 - Furnish And Install Black Vinyl Coated Chain Link Fence and Gates
 - Surface Courts With Up To 2 Colors
 - o Furnish And Install All Court Striping

Alternate 1: Walkways and Planting

\$115,000 - \$150,000

- Furnish and install new concrete walkways
- o Furnish and install area for gazebo style covered area
- Furnish and install plantings

Alternate 2: Court Lighting

\$250,000 - \$350,000

- o Furnish and install new LED court lighting on 6 courts
- Supply power from nearby source within 100' of site
- Supply digital control system for access via phone or internet for light controls



EXCLUSIONS

- Any costs associated with necessary charges relating to the delineation of the field
- The supply of manholes or clean-outs or grates, or supply of the manhole covers
- Any alteration or deviation from specifications involving extra costs, which alteration or deviation will be provided only upon executed change orders, and will become an extra charge over and above the offered price
- Soil stabilization or remediation of any type
- Mass Excavation as required to achieve subgrade
- Rock excavation
- Offsite disposal of generated spoils


- Excavation or disposal of unsuitable or contaminated soils
- Site security
- Once subgrade has been established, a proof roll will be performed to ensure structural stability of the soils; in the event that unsuitable soils are encountered, a price to remedy these areas can be negotiated based on recommended methods per project Engineer
- > Testing or Inspection Fees
- Site restoration, sodding, landscaping or growin beyond disturbed areas
- Repair or resurfacing existing asphalt parking lot if damaged by truck traffic
- Bond fees and non-local permits

Please feel free to reach out to any member of our project team with questions about our offer:

Andrew Dyjak
Regional Vice President
(860) 333-7839
Andrew.Dyjak@Fieldturf.com

Chris Hulk
Regional Vice President
203-676-4445
christopher.hulk@fieldturf.com

Jonathan Luster, PE
Regional Construction Manager
(860) 227-4915
Jonathan.Luster@FieldTurf.com












- NOTES:

 1) ALL DESIGN AND EXISTING CONDITIONS MAPPING BASED ON AVAILABLE MAPPING AND SHOULD BE CONSIDERED APPROXIMATE.
- 3) THIS DESIGN IS THE SOLE PROPERTY OF FIELDTURF, USA AND NO ATTEMPTS SHALL BE MADE TO DUPLICATE OR REPLICATE WITHOUT THE PREMISSION OF FIELDTURF.

GRANBY MEMORIAL HIGH SCHOOL TENNIS FACILITY IMPROVEMENTS

PLEASANT STREET GRANBY, CONNECTICUT



TENNIS

APRIL 14, 2025



GRANBY MEMORIAL HIGH SCHOOL FIELD 2 IMPROVEMENTS







Conceptual Layout

Existing Conditions Aerial

Date: April 21, 2025

Prepared For: Karl Gates - Athletic Director & Student Activities Coordinator

Prepared By: Andrew Dyjak – Regional Vice President, New England

Chris Hulk, PE - Regional Vice President, New England

Jonathan Luster, PE – Regional Construction Manager, New England

Address: Granby Memorial High School | 54 N Granby Rd, Granby, CT 06035

This budget proposal encompasses all facets of the project, with FieldTurf offering a comprehensive, turnkey solution that includes design, project oversight, and construction. The budget is based on current site conditions, review meeting with the school, and the planned construction period in spring/summer 2026.

FieldTurf pricing is based on the Capital Region Education Council (CREC) program. CREC is a member of The Association of Educational Purchasing Agencies (AEPA) program. The AEPA is a purchasing co-op that provides member schools with pre-determined preferential pricing by approved vendors. Since the product has already been bid at the national level, individual schools do not have to duplicate the formal bid process. AEPA IFB #024.



Click on the following AEPA hyperlink for more information: AEPA IFB #24

Below is a detailed cost breakdown for site construction, turf installation and overall implementation of the project.



Project Description:

The project proposes to replace the existing synthetic turf carpet with new synthetic turf. The existing turf will be cut into sections, rolled up, and removed from the field. The existing infill will either be placed in sacks for reuse or removed from the field and brought to a recycling facility. The field will then be laser graded to achieve planarity before the new turf is laid down and installed on the field. If additional topping stone is needed to achieve planarity, more stone will be brought in. Additional scope items such as new LED lighting pole and fixtures, ball safety netting, and walkways have been added to the budget below as well.

Depending on final scope, the project is anticipated to be constructed in a ±2-3 month timeframe. It is also anticipated that access and staging areas will be available nearby. This budget is intended to assist the school in preparing for this project. Additional discussions, review and programming will be required to refine the scope and budget prior to construction.

SYNTHETIC TURF IMPROVEMENTS

> Synthetic Turf Installation

\$650,000 - \$700,000

- Remove And Recycle Existing Synthetic Turf Carpet And Infill
- Laser Grade Base Stone And Supplement Base Stone As Needed In Order To Achieve Planarity Prior To Turf Installation
- Furnish And Install Synthetic Turf For Field
- Synthetic Turf With SBR Rubber And Sand Infill
- Colors And Logos Per Rendering
- Post Installation GMAX Field Testing

Alternate: Midfield Logo

\$15,000 - \$20,000

• Midfield Grizzly Style Bear

> Alternate: Improved Ball Netting

\$45,000 - \$85,000

- o Remove Existing Ball Netting
- o Furnish And Install New Ball Netting
- Final Size And Location T.B.D.

> Alternate: New Scoreboard

\$65,000 - \$95,000

- o Furnish And Install Multi-Use Scoreboard
- Assumed Programmable Boards With Display/Naming Panel Above Board
- Scoreboard (8'h X 25'w)

Alternate 5: New Led Lighting Fixtures

\$475,000 - \$550,000

- o Furnish And Install New Led Light Fixtures On Existing Poles
- o Assumed 4 Pole System
- New Power Supply Within 100' Of Field



EXCLUSIONS

- Any costs associated with necessary charges relating to the delineation of the field
- The supply of manholes or clean-outs or grates, or supply of the manhole covers
- Any alteration or deviation from specifications involving extra costs, which alteration or deviation will be provided only upon executed change orders, and will become an extra charge over and above the offered price
- Soil stabilization or remediation of any type
- Mass Excavation as required to achieve subgrade
- Rock excavation
- Offsite disposal of generated spoils


- Excavation or disposal of unsuitable or contaminated soils
- Site security
- Once subgrade has been established, a proof roll will be performed to ensure structural stability of the soils; in the event that unsuitable soils are encountered, a price to remedy these areas can be negotiated based on recommended methods per project Engineer
- > Testing or Inspection Fees
- Site restoration, sodding, landscaping or growin beyond disturbed areas
- Repair or resurfacing existing asphalt parking lot if damaged by truck traffic
- Bond fees and non-local permits

Please feel free to reach out to any member of our project team with questions about our offer:

Andrew Dyjak
Regional Vice President
(860) 333-7839
Andrew.Dyjak@Fieldturf.com

Chris Hulk
Regional Vice President
203-676-4445
christopher.hulk@fieldturf.com

Jonathan Luster, PE
Regional Construction Manager
(860) 227-4915
Jonathan.Luster@FieldTurf.com





EXAMPLE PROJECT



EXAMPLE PROJECT



EXAMPLE BALL NETTING



EXAMPLE SCOREBOARD




- NOTES:

 1) ALL DESIGN AND EXISTING CONDITIONS MAPPING BASED ON AVAILABLE MAPPING AND SHOULD BE CONSIDERED APPROXIMATE.

GRANBY MEMORIAL HIGH SCHOOL FIELD 2

39 SCHOOL STREET GRANBY, CONNECTICUTACHUSETTS



FIELD 2

APRIL 15, 2025



Granby Memorial High School Turf Track and Field



Priority Funding for Turf Track and Field Replacement at Granby Memorial High School

A top priority for funding is the replacement of the turf track and field at Granby Memorial High School. Originally installed in 2013, the track has been meticulously maintained and serves as a source of pride and enjoyment for both the school district and the greater Granby community.

The track is a vital community asset, used daily by residents for walking, running, and athletic training. Granby students rely on the track and field for physical education, wellness, and recreation across three seasons each year. Additionally, Stadium Field is an essential facility that supports not only football but also boys' and girls' soccer, lacrosse, field hockey, and cheerleading. Beyond athletics, the field hosts major events such as the annual GMHS graduation ceremony, Bearcats football games, and community fundraisers, including the Alzheimer's Walk.

Urgent Need for Repairs

In recent years, the track and field have faced significant structural challenges, including the formation of sinkholes. These issues have progressed to the point where track and field meets can no longer be hosted, and safety concerns have led to restrictions on community access.

Turf fields generally have a lifespan of 8–10 years, which can be extended to 10–15 years under optimal conditions. However, as the GMHS field enters its 12th year, it has exceeded its expected lifespan, and due to unique environmental factors, a full replacement is both warranted and necessary.

Cost and Remediation Efforts

The estimated cost to replace the track and field, including the necessary remediation to address existing structural challenges, exceeds \$2 million.


In 2022, the geotechnical firm Haley Aldrich conducted subsurface testing, including seven 15-foot deep geoprobe test holes, to investigate the cause of recurring sinkholes and surface depressions. Their analysis revealed the


presence of air pockets and poorly graded soil beneath the track area. In 2024, GZA Geotechnical Services reviewed the initial findings, conducted a site visit, and confirmed the assessment.

Both firms concluded that organic materials, such as tree stumps left unexcavated during the original construction, are decomposing over time, creating air pockets that cause the sand layers to sink and surface layers to depress. Additionally, concerns were raised about significant levels of poorly graded sand and air pockets at depths ranging from 1 to 10 feet in various locations.

To ensure long-term stability, experts recommend a comprehensive remediation process, including soil removal, excavation, screening for organic materials, and multiple layers of soil compaction before reinstatement. Without these corrective measures, the risk of additional sinkhole formations in the coming years remains high.

The following samples illustrate the existing subsurface conditions at GMHS, with each container representing depths of up to 15 feet.





Unaffected Turf Field

Properly compacted soil (yellow)

Properly compacted / installed base (yellow)

Level base surface (blue)

Level turf surface (green)

Granby Turf Field

Uncompacted soil w/ pockets of debris and air (yellow)

Sinking levels of subsurface (blue)

Sinking base level (white)

Uneven, depressed, and sinking turf surface (red)



GRANBY MEMORIAL HIGH SCHOOL TRACK & FIELD IMPROVEMENTS







Existing Conditions Aerial

Conceptual Layout

Date: October 2, 2025

Prepared For: Karl Gates - Athletic Director & Student Activities Coordinator

Prepared By: Andrew Dyjak – Regional Vice President, New England

Chris Hulk, PE - Regional Vice President, New England

Jonathan Luster, PE – Regional Construction Manager, New England

Address: Granby Memorial High School | 54 N Granby Rd, Granby, CT 06035

This budget proposal encompasses all facets of the project, with FieldTurf offering a comprehensive, turnkey solution that includes design, project oversight, and construction. The budget is based on current site conditions, review meeting with the school, and the planned construction period in spring/summer 2026.

FieldTurf USA, Inc. is pleased to present the following proposal. FieldTurf pricing is based on the Capital Region Education Council (CREC) program. CREC is a member of The Association of Educational Purchasing Agencies (AEPA) program. The AEPA is a purchasing co-op that provides member schools with pre-determined preferential pricing by approved vendors. Since the product has already been bid at the national level, individual schools do not have to duplicate the formal bid process. AEPA IFB #024-A.



Click on the following AEPA hyperlink for more information: AEPA IFB #24-A.

Below is a detailed cost breakdown for site construction, turf installation and overall implementation of the project.



Project Description:

The existing track and field at Granby Memorial High School is in need of significant remediation efforts from sinks holes that have developed along the track / field. Based on the original geotechnical information provided by the Town, it appears that organic material has decayed below the eastern side of the track / field. The depths of this material are present up to 10' below existing grade. The Town then expanded the geotechnical investigation, to which the report indicated the entirety of the track and field area should be fully removed down to a depth of 5' and the compacted back in lifts. With this understanding, FieldTurf has developed two options for reconstruction.

Option 1:

The first option would be to complete the work as outlined in the geotechnical report. This would include removal of all track surfacing, removal of all synthetic turf, removal of all curbing, removal of all utilities, removal of all foundations, removal of all fencing and all existing subbase materials down to a depth of 5'. It is assumed that a large portion of this material will need to be removed from the site and supplemented with clean fill or gravel. Once the site has been excavated to a depth of 5' and in some indicated areas down to 10', the reconstruction would start to occur. Materials would be installed in lifts and a third party geotechnical engineer would be hired by the Town to oversee and test the work. The existing electrical, audio, storm and any other utilities would be replaced. The concrete turf anchor curb and football goal posts would be reinstalled. All new fencing and paved access paths around the site would be reconstructed. Finally, a new synthetic track and field would be installed on the newly reconstructed site. Several unknowns remain, such as if shoring is required around the existing bleachers, buildings, scoreboard and light poles given the depths of excavation. It is also unclear to what extent the 10' depth of excavation will be required. Field conditions may render the needed area to expand. Lastly, it is unknown is rock and ledge removal will be encountered to the depths that are shown. Rock removal and ledge removal is always an exclusion of any contract due to its unforeseen nature. The warranty for construction on this option would be a 1 year workmanship warranty, 8 year warranty on synthetic turf and 5 year warranty on track materials. With all of these considerations in mind, FieldTurf felt it was in the best interest of the Town to review a second option based on its ability to self-perform post-tension concrete tracks, fields, and courts.

Option 2:

This preferred option of FieldTurf would reconstruct the existing track and field area with post tension concrete. FieldTurf has completed both post tension tracks and post tension fields throughout the New England region and through out the country. This technology allows the majority of materials to stay in place and be spanned by the nature of how post tension concrete operates. Slabs of post tension concrete are designed to span areas of unsuitable soils, provide high strength and long lasting base for whatever the application may be. Many other types of construction use this technique for bridges, parking garage slabs, balconies, overhangs and other types of applications. The last major benefit is that FieldTurf, as part of Tarkett Sports, is able to provide a 25+ year warranty on the structural components of the installation. This means that the Town would be ensured to not be left in this type of situation again. The reconstruction efforts of this type of system would remove the track and field areas. Remove the top 4"-5" of materials, compact the existing subgrade, perform 20 augured holes in areas of known settlement, install flowable fill in those areas and then construct a new post tension concrete track and field. Improved drainage, ball netting and football goal posts would be installed. Fencing would be replaced and walkway areas around the track would be renovated to meet new grades. All surrounding site features including lights, bleachers, buildings, scoreboards can all remain in place without the need for additional shoring or replacement.



Lastly, alternates have been included for site improvements such as LED lighting, press box, ball netting, etc...

Depending on final Option and scope selected, the project is anticipated to be constructed in a ±4-12 month timeframe. It is also anticipated that access and staging areas will be available nearby. This budget is intended to assist the school in preparing for this project. Additional discussions, review and programming will be required to refine the scope and budget prior to construction.

FIELD REMEDIATION OPTIONS:

➤ Option 1 – FULL RECONSTRUCTION TO A DEPTH OF 5' OR MORE

\$9,370,000 - \$11,080,000

- General Scope: Reconstruction of entire track and field area up to limit of existing pavement beyond the existing fence line
 - Remove and dispose of existing track surfacing
 - Remove and dispose of existing synthetic turf surfacing
 - Remove and dispose all existing utilities, including storm drainage, electrical, audio and any other encountered utilities
 - Mill and remove all existing pavement and base materials. Salvage processed aggregate base for reuse.
 - o Excavate, remove and salvage existing field stone base
 - o Remove and dispose of existing turf anchor curb and track drain within limits shown
 - o Remove and salvage existing storm drainage piping and supplement as needed
 - Excavate and remove existing soils to a depth of approximately 5' along the entirety of the facility and up 10' in various areas to remove unsuitable soils
 - Provided shoring and safety measures around existing structures, such as light poles, bleachers, sheds, etc...
 - o Town provided 3rd party field testing agency for full time inspection of installed materials
 - Furnish and install new subgrade materials, compact in lifts to geotechnical recommendations
 - o Furnish and install geogrid support mesh in 2 layers
 - Install drainage piping
 - Furnish and install electrical conduits and electrical system
 - o Furnish and install new ACO drain and concrete turf anchor curb
 - Reinstall construct track base with appropriate base materials
 - o Pave new track system to a depth of 3.5" of pavement with virgin asphalt
 - o Furnish and install new dynamic stone base for field system
 - o Furnish and install new track surfacing and striping within limits shown
 - Furnish and install new synthetic turf within limits shown
 - o Furnish and install new 4' ht. chain link fencing
 - Furnish and install new paved access around field

> Synthetic Turf Installation

- Remove and recycle existing synthetic turf carpet and infill
- Furnish and install post tension concrete field base
- Furnish and install synthetic turf for field
- Synthetic turf with SBR rubber and sand infill



- Colored end zone
- Alternating turf panels
- Post installation GMAX field testing

> End Zone Letters

"GRANBY" end zone lettering

Midfield Logo

Midfield Grizzly Style Logo

> Track Base Reconstruction

- Remove and dispose of existing rubberized track surface
- Furnish and install post tension concrete track base
 - Match grades to existing perimeter trench drain which is to remain

> Track Surfacing BSS-300

- Supply and install Beynon BSS-300 polyurethane track surfacing
 - o Base color: Beynon red
- Perform track striping

Colored Exchange Zones

(3) colored exchange zones

ADDITIONAL SITE IMPROVEMENTS

> 20' Height Ball Safety Netting

Supply and install 20-foot-high ball safety netting in D-Zones, including foundations, sleeves, poles, netting, and hardware along the field end lines

10' Height Ball Safety Netting

 Supply and install 10-foot-high ball safety netting in corners of field up to 20 yard line, including foundations, sleeves, poles, netting, and hardware along the field end lines

Press Box

\$175,000 - \$225,000

\$80,000 - \$95,000

\$55,000 - \$75,000

- Furnish and install new press box behind existing bleachers
- Includes new foundation and support structure
- ADA access lift listed as separate item if needed

ΔDΔ Lift

\$95,000 - \$125,000

• Furnish and install new ADA accessible lift to press box

Includes foundation and installation

Retrofit of Existing Athletic Lighting

\$200,000 - \$250,000



- Remove and dispose of existing light fixtures and replace with LED fixtures
- Poles to remain

New Bleachers with Press Box

\$650,000 - \$750,000

- Furnish and install new double sided bleachers to service both fields (+/- 400 seats)
- Furnish and install press box between fields for use for both fields
- Furnish and install concrete slab for bleachers
- Provide power supply

POTENTIAL TOTAL OF OPTION 1 w/ ALL ALTERANTES

\$ 10,625,000 - \$ 12,600,000

EXCLUSIONS

- > Any costs associated with necessary charges relating to the delineation of the field
- The supply of manholes or clean-outs or grates, or supply of the manhole covers
- Any alteration or deviation from specifications involving extra costs, which alteration or deviation will be provided only upon executed change orders, and will become an extra charge over and above the offered price
- > Soil stabilization or remediation of any type beyond 5' depth
- Rock excavation and/or ledge removal
- Offsite disposal of generated spoils Excavation or disposal of unsuitable or contaminated soils
- > Site security
- Once subgrade has been established, a proof roll will be performed to ensure structural stability of the soils; in the event that unsuitable soils are encountered, a price to remedy these areas can be negotiated based on recommended methods per project Engineer
- > 3rd party testing or Inspection Fees
- > Site restoration, sodding, landscaping or grow-in beyond disturbed areas
- > Repair or resurfacing existing asphalt parking lot if damaged by truck traffic



Option 2 (FieldTurf Preferred Option)

\$5,150,000 - \$5,500,000

- General Scope: Extensive Exploration and Solidify
 - o GPS located major sink hole areas and record for future exploration use
 - Remove and dispose of existing track surfacing
 - Remove and dispose of existing synthetic turf surfacing
 - o Full depth mill of existing track pavement and remove
 - Excavate, remove and salvage existing field stone base and processed aggregate track base as necessary
 - o Remove and dispose of existing turf anchor curb around track and field
 - Remove and replace football goal posts
 - o Remove and replace damaged sections of drainage piping
 - o Remove and dispose of existing electrical conduit and wiring if encountered during exploration
 - o Replace and/or reset electrical boxes and drainage structures within field
 - o Conduct a series of 10' deep x 2' diameter augur holes along eastern side of track / field
 - Remove and dispose of excavated material
 - o Install flowable fill in all excavated holes to a depth of approximately 1' below finished grade
 - o Furnish and install geogrid support mesh prior to backfill
 - o Furnish and install new subgrade materials to achieve new grades
 - o Reinstall drainage piping and electrical conduits as necessary
 - o Furnish and install new ACO drain and concrete turf anchor curb as required
 - o Furnish and install new post tension concrete track and field
 - o Furnish and install new 4' ht. chain link fencing and gates
 - Furnish and install new access path around field
 - Furnish and install new track surfacing and striping within limits shown
 - o Furnish and install new synthetic turf and shock/drainage pad within limits shown
 - o Provide 25+ year structural warranty on all post tension concrete

Synthetic Turf Installation

- Remove and recycle existing synthetic turf carpet and infill
- Furnish and install post tension concrete field base
- Furnish and install shock / drainage pad
- Furnish and install synthetic turf for field
- Synthetic turf with SBR rubber and sand infill
- Colored end zone
- Alternating turf panels
- Post installation GMAX field testing
- Annual field maintenance. 1 visit per year for 8 years

End Zone Letters

"GRANBY" end zone lettering

Midfield Logo

Midfield Grizzly Style Logo



Track Base Reconstruction

- Remove and dispose of existing rubberized track surface
- Furnish and install post tension concrete track base
 - o Match grades to existing perimeter trench drain which is to remain

> Track Surfacing BSS-300

- Supply and install Beynon BSS-300 polyurethane track surfacing
 - o Base color: Beynon red
- Perform track striping

Colored Exchange Zones

• (3) colored exchange zones

ADDITIONAL SITE IMPROVEMENTS

> 20' Height Ball Safety Netting

\$80,000 - \$95,000

• Supply and install 20-foot-high ball safety netting in D-Zones, including foundations, sleeves, poles, netting, and hardware along the field end lines

10' Height Ball Safety Netting

\$55,000 - \$75,000

 Supply and install 10-foot-high ball safety netting in corners of field up to 20 yard line, including foundations, sleeves, poles, netting, and hardware along the field end lines

> Press Box \$175,000 - \$225,000

- Furnish and install new press box behind existing bleachers
- Includes new foundation and support structure
- ADA access lift listed as separate item if needed

> ADA Lift \$95,000 - \$125,000

- Furnish and install new ADA accessible lift to press box
- Includes foundation and installation

Retrofit of Existing Athletic Lighting

\$200,000 - \$250,000

- Remove and dispose of existing light fixtures and replace with LED fixtures
- Poles to remain

New Bleachers with Press Box

\$650,000 - \$750,000

- Furnish and install new double sided bleachers to service both fields (+/- 400 seats)
- Furnish and install press box between fields for use for both fields
- Furnish and install concrete slab for bleachers
- Provide power supply

POTENTIAL TOTAL OF OPTION 1 w/ ALL ALTERANTES

\$ 6,475,000 - \$ 7,100,000



EXCLUSIONS

- Any costs associated with necessary charges relating to the delineation of the field
- The supply of manholes or clean-outs or grates, or supply of the manhole covers
- Any alteration or deviation from specifications involving extra costs, which alteration or deviation will be provided only upon executed change orders, and will become an extra charge over and above the offered price
- Soil stabilization or remediation of any type
- Mass Excavation as required to achieve subgrade
- Rock excavation
- Offsite disposal of generated spoils

- Excavation or disposal of unsuitable or contaminated soils
- Site security
- Once subgrade has been established, a proof roll will be performed to ensure structural stability of the soils; in the event that unsuitable soils are encountered, a price to remedy these areas can be negotiated based on recommended methods per project Engineer
- > Testing or Inspection Fees
- Site restoration, sodding, landscaping or growin beyond disturbed areas
- Repair or resurfacing existing asphalt parking lot if damaged by truck traffic
- Bond fees and non-local permits

Please feel free to reach out to any member of our project team with questions about our offer:

Andrew Dyjak
Regional Vice President
(860) 333-7839
Andrew.Dyjak@Fieldturf.com

Chris Hulk
Regional Vice President
203-676-4445
christopher.hulk@fieldturf.com

Jonathan Luster, PE
Regional Construction Manager
(860) 227-4915
Jonathan.Luster@FieldTurf.com



HALEY & ALDRICH, INC. 465 Medford St. Suite 2200 Boston, MA 02129 617.886.7400

28 July 2025 File No. 0206711-100

Granby Public Schools 15-B North Granby Road Granby, CT 06035

Attention: Christopher DeGray, Director of Facilities

Subject: Subsurface Conditions and Geotechnical Data Report

Granby Public Schools – Turf Field and Track

Granby, CT

Ladies and Gentlemen:

This Report provides a summary of the subsurface explorations conducted within the limits of the existing synthetic turf field and track for Granby Public Schools (the School) located at 50 North Granby Road in Granby, Connecticut (subject site). The approximate location of the site is shown on Figure 1.

The purpose of the subsurface investigation program conducted within the limits of the existing turf field and track was to obtain information on subsurface conditions encountered at the site, evaluate site fill thickness, and identify presence of potential void spaces within near surface soils. The work reported herein was undertaken by Haley & Aldrich, Inc. (Haley & Aldrich) in accordance with our proposal dated 30 April 2025 and your subsequent written authorization

Existing Site Conditions

Based on historic aerial photographs, the subject site has been used as an athletic field and track since at least 1992. We understand that the current synthetic turf field and track surface was constructed between 2012 and 2013 and that the proposed site grade changes required for construction in the area of observed track settlement were not significantly greater than the existing site grades. Existing site grades are approximately Elevation (El.) 220 to 225 (NAVD88)¹ in the area of the track and athletic field surface.

Settlement has been observed in various areas on the existing track surface and causes puddling after rain events, creating unsatisfactory performance conditions for athletics.

-

¹ Elevations in this report are in feet and reference the North American Vertical Datum of 1988 (NAVD88).

Proposed Development

The School intends to replace the existing synthetic field and track surface within the next 5 years to bring them to performance-level standards for Granby Athletics. Athletic lighting structures are also proposed to support athletic events after sunset.

Subsurface Investigation Programs

PREVIOUS HALEY & ALDRICH SUBSURFACE EXPLORATION PROGRAM

Haley & Aldrich previously performed a subsurface investigation program in October 2022 on the site. The purpose was to observe the subsurface conditions specifically underlying the inside lane track in the northeast corner and evaluate the presence of possible void spaces beneath the track surface resulting in observed surficial settlement. On 20 October 2022, Seaboard Drilling, LLC of Chicopee, Massachusetts conducted a total of seven geoprobes designated HA-1 through HA-7. The drilling of geoprobes were observed by Haley & Aldrich.

The designation and approximate locations of the geoprobes are shown on Figure 2 and geoprobe logs are included in Appendix A.

RECENT SUBSURFACE EXPLORATION PROGRAM

The purpose of the recent subsurface investigation program was to collect data beneath the existing turf field and track that may indicate future areas of settlement. Explorations were not performed to support the athletic lighting structures at this time.

The designation and approximate location of subsurface explorations are indicated on Figure 2. The recent subsurface explorations were located in the field by Haley & Aldrich personnel by measuring from existing site features and therefore are considered approximate.

Between 23 and 25 June 2025, G&M Subsurface of North Dighton, Massachusetts conducted a total of twenty-seven (27) geoprobe explorations within the limits of the existing synthetic turf field and track, designated GP-01 through GP-27. GeoSurfaces of Woburn, Massachusetts performed the opening and repair of the synthetic turf surfaces at each of the geoprobe locations on the existing field. The geoprobes were drilled to depths ranging from 10 to 20 (feet) ft below ground surface (bgs) with the use of a track-mounted geoprobe rig and were observed by Haley & Aldrich. Refer to the Geoprobe Logs included in Appendix B for additional information.



Subsurface Conditions

SOIL CONDITIONS

Subsurface soil conditions encountered in the recent subsurface exploration program consisted of the following generalized sequence of subsurface units, listed in descending order of occurrence below ground surface. Refer to Table I – Summary of Subsurface Conditions for a summary of the explorations performed in 2022 and 2025.

Table I: Summary of Subsurface Conditions

Generalized Subsurface Stratum	Depth Top of Stratum (ft)	Stratum Thickness (ft)
Fill	0.3 to 1	0.4 to 15
Glaciofluvial Deposits	0.5 to 13	Not Determined

Note: one or more of the units may be absent at any specific location and may vary in thickness across the subject site. A detailed description of the units encountered is provided below.

<u>Fill</u> - The Fill encountered generally consisted of dark to light brown, red-brown, or gray-brown poorly-graded Sand or silty Sand with varying amounts of silt, gravel, topsoil, wood, and organic soil. At the recent geoprobe locations GP-03, GP-05, GP-13, GP-22, the fill noted buried wood and pockets of dark brown organic soil (topsoil) between 0.5 and 5 ft bgs.

The Fill layer was encountered in each of the geoprobes, except for GP-01, GP-06, and GP-08, and ranged from 0.4 to 15 ft in thickness. A 0.5-ft-thick layer of crushed stone was encountered at ground surface at the locations of geoprobes conducted within the existing synthetic turf field. An approximate 0.1-ft-thick layer of track rubber followed by about 0.4 to 0.5-ft-thick layer of crushed stone was encountered at ground surface at the locations of geoprobes conducted within the limits of the existing track.

The Fill layer was not fully penetrated at geoprobe GP-22 and HA-5 to a depth of 10 ft and at HA-6 to a depth of 15 ft.

<u>Glaciofluvial Deposits</u> - Glaciofluvial Deposits were encountered beneath the Fill at each geoprobe location except for geoprobes GP-01, GP-06, and GP-08 where the Glaciofluvial Deposits were encountered underlying the crushed stone. Glaciofluvial Deposits generally consisted of tan to light brown or red-brown poorly-graded Sand. Glaciofluvial Deposits were not fully penetrated at any of the geoprobe locations.



Granby Public Schools 28 July 2025 Page 4

GROUNDWATER LEVELS

Groundwater was not encountered within the geoprobes at the time of drilling.

Groundwater levels are influenced by precipitation, the presence of below-grade structures and utilities in the area, leakage into or out of utility pipes, the infiltration of surface water runoff, building underdrain systems, localized water recharging, and other factors. Groundwater conditions encountered during subsequent site visits and/or during construction may differ from those reported herein, and as additional groundwater measurements are obtained during subsequent design phases, this report will be updated.

Geotechnical Mitigation Considerations

Since areas of settlement have been observed within the turf field, the School has been performing routine maintenance consisting of a subcontractor removing the turf surface and filling in localized low spots. Additionally, the northeast corner of the track that was previously observed to experience settlement was patched and resurfaced between 2022 and 2023.

Of the recent geoprobe explorations, locations GP-03, GP-05, GP-13, GP-22 encountered buried wood and pockets of dark brown organic soil (topsoil) between 0.5 and 5 ft bgs within the Fill layer. These locations are spread out across the track and field and are not located in one central area, suggesting that other locations or areas between explorations may encounter similar conditions subject to future settlement.

Full-Depth Restoration (recommended)

To mitigate the risk of future settlement, we recommend that a full depth restoration of the field and track surface be performed prior to replacement of the surfaces. Full depth restoration shall include:

Site Preparation

- Strip, remove, and dispose of existing rubber track surface and synthetic turf field and crushed stone subbase.
- Excavate and remove the full depth of Fill up to a 5 ft depth beneath the track and field and 5 ft
 laterally outside the limits of the track. Within the limits shown on Figure 2, the northeast
 corner of the track is recommended to be excavated and removed up to 10 ft due to presence of
 deeper Fill materials that are unsuitable for subbase of the track.
- Segregate/screen/stockpile excavated Fill materials that are suitable for re-use as compacted granular fill beneath the track and field surface. Remove and dispose of unsuitable Fill material (buried topsoil, organic materials, wood, etc).
 - Reuse of any excavated soils will be dependent upon visual characterization of the materials and results of grain size analyses and laboratory compaction tests. Accordingly, we recommend to



the extent possible that an on-site location be established for segregating, processing, and stockpiling excavated soils.

Subgrade Preparation

- After the Fill has been excavated, the subgrade shall be compacted to 95% of the material's
 maximum dry unit weight (determined in accordance with ASTM D1557) using appropriate
 compactive efforts. As a minimum, the subgrade should receive four complete coverages with
 suitable compaction equipment. The excavated material may be reused after the wood or
 degradable materials are removed from the Fill material.
- Place a woven geotextile fabric (Mirafi 600X or similar) on top of the prepared and approved subgrade as well as on the sides of the excavation.
- The excavation shall be backfilled with previously excavated Fill material suitable for re-use or Granular Fill placed in loose lift thicknesses not exceeding 12 inches (in.), and the material shall be compacted to 95% of the material's maximum dry unit weight (determined in accordance with ASTM D1557) using appropriate compactive efforts. As a minimum, each layer of fill should receive four complete coverages with suitable compaction equipment.

Following backfill and compaction to design subgrade elevation, re-construct the track and field. Refer to recommendations in following sections.

Synthetic Turf Field

- Following completion of subgrade preparation to design subgrade elevation for the new turf
 system, prepare the subgrade using a large compaction roller to prepare a firm, dry and stable
 subgrade. If during static rolling of the subgrades pumping or weaving conditions are observed,
 alternative compaction techniques may be required and/or additional subgrade preparation
 may be recommended (e.g., removal and replacement of soft, compressible soils).
- At all times prior to placement of the turf system, we recommend maintaining a dry and
 undisturbed design subgrade to ensure a stable working surface to receive the turf system.
 Temporary re-grading outside the limits of the new field will be required to divert surface runoff
 away from the work areas. Construction dewatering is not anticipated; however, if it becomes
 necessary, efforts should be taken by the contractor to discharge dewatering effluent to an onsite recharge system at distances away from the work areas so as not to disturb subgrade
 preparation.
- For the permanent condition, the maintenance, protection and long-term performance of the synthetic turf field will require an effective stormwater runoff collection and management system. Anticipated subsurface soils at and/or within shallow depths of the anticipated design subgrade level for the new synthetic turf fields are likely to consist of fine-grained sandy silts/silty sands that have poor drainage characteristics vertically and laterally. Design of any sub-turf drainage systems must consider the effect these impermeable subgrade soils can have on the field's drainage capacity. At a minimum, the sub-turf drainage systems must be designed



such that the system is entirely and at all times above groundwater level. Design of the drainage system for the synthetic turf should be completed by a Civil Engineer. For this report, we recommend the subgrade be pitched to direct drainage towards the sub-turf drainage system that would be comprised of a minimum 10 to 12-in. thick layer of double-washed, 3/4-in. crushed stone with perforated HDPE pipes that are sized by the Civil Engineer and embedded within the crushed stone so as to effectively collect and transport by gravity any accumulated runoff water that filters from the turf layer above to an appropriately sized on-site collection/groundwater recharge tank or, alternatively, direct the discharge into a permitted storm drain. Prior to placing the crushed stone and perforated piping, a woven geotextile fabric (Mirafi 600X or similar) should be placed on top of the prepared and approved subgrade. Additionally, a backflow preventer at the outlet structure should be incorporated into the design of the drainage system.

• 3/4-in Crushed Stone shall consist of inert angular material derived from a stone quarry that is hard, durable, washed stone or crushed gravel, free from clay, loam, or other deleterious material, with a maximum size of 3/4 in, and conforming to the following:

Sieve Size	Percent Passing By Weight
1 in.	100
3/4 in.	90 – 100
1/2 in.	10 – 50
3/8 in.	0 – 20
No. 4	0 – 5

Synthetic Track

- Following preparation to subgrade elevation, provide a minimum 12-in. layer of Granular Fill for the subbase of the asphalt. Asphalt and rubberized track surface thickness should match original design drawings.
- Granular Fill shall be obtained from off-site sources and shall consist of naturally occurring or
 processed, inert material that is hard, durable natural stone and coarse sand, free from loam,
 clay, surface coatings, and deleterious materials.

Sieve Size	Percent Passing By Weight
3 in.	100
No. 4	30 – 90
No. 40	10 – 50
No. 200	0-8



Granby Public Schools 28 July 2025 Page 7

If portions of the proposed track extend beyond the existing plan limits of the existing track, we
recommend complete removal of the existing topsoil prior to compacting the subgrade and
placement and compaction of a minimum 12-in. thick lift of granular fill to design subgrade
elevation.

Track and Field Surface Restoration (alternate consideration with routine maintenance)

If project construction costs associated with the recommended over-excavation and backfilling are determined to not be acceptable to the School, the reduced scope of track and field surface restorations could be considered by the School as an alternate consideration that would not require the subgrade preparation in the full-depth restoration recommendation. This option would not mitigate the risk of potential long term field performance issues due to the presence of the remaining unsuitable soils below the over-excavation limits but could allow the track and field to be utilized in the short term and would require periodic maintenance of both the synthetic turf field and track.

For this consideration, the track and field surface restoration would consist of:

- Remove/mill track surface down to asphalt base layer, patch observed cracks and shim depressions in the asphalt, and replace with new synthetic track surface/system.
- Remove synthetic turf surface/carpet, raise grade with additional crushed stone where needed, and replace with new synthetic turf surface. Prior to installing the new synthetic turf, the existing drainage stone should be tested to confirm design infiltration rate of the drainage layer is consistent with the synthetic turf field provider's requirements. Additionally, an inspection of the existing drainage piping (lateral field and perimeter drain lines) should be completed to confirm the drainage system is functioning as originally designed and meets stormwater management requirements for the new turf field system.
- Surface track and synthetic turf surface restoration should be conducted by a specialty contractor familiar with the construction and repair of synthetic turf and track systems.

Limitations

This letter was prepared in accordance with our proposal dated 30 April 2025 and your subsequent written authorization. This letter has been prepared for the specific application to the Granby Public Schools synthetic turf field and track.

The nature and extent of variations in the subsurface conditions between explorations may not become evident until construction, and the project design may change from our current understanding. Any additional information pertaining to the project that becomes available should be provided to Haley & Aldrich, so that our conclusions and recommendations can be reviewed and modified, as necessary.



Granby Public Schools 28 July 2025 Page 8

We appreciate the opportunity to provide engineering services on this project. Please do not hesitate to call if you have any questions or comments.

Sincerely yours,

HALEY & ALDRICH, INC.

Megan H. Carlson, PE (NY)

Megan H. Carlson

Project Manager

R. Scott Goldkamp, PE (MA/NH)

Principal

Attachments:

Figure 1 – Site Locus


Figure 2 – Site and Subsurface Exploration Location Plan


Appendix A – Previous Geoprobe Logs

Appendix B – Recent Geoprobe Logs

\haleyaldrich.com\share\CF\Projects\0206711\Granby Public Schools\Report\2025-0728-HAI-Granby Public Schools-Geotechnical Data Report-F.docx







APPENDIX A Previous Geoprobe Logs

IDENTIFICATION AND DESCRIPTION OF SUBSURFACE MATERIALS

Hard

SOIL

Soil description on logs of subsurface explorations are based on Standard Penetration Test results, visual-manual examination of exposed soil and soil samples, and the results of laboratory tests on selected samples. The criteria, descriptive terms and definitions are as follows:

DENSITY OR CONSISTENCY

Density of Cohesionless Soils	Penetration Resistance (Blows per ft.)	Consistency of Cohesive Soils	Penetration Resistance (Blows per ft.)
Very Loose	0-4	Very Soft	0-2
Loose	5-10	Soft	3-4
Medium	11-30	Medium	5-8
Dense	31-50	Stiff	9-15
Very Dense	over 50	Very Stiff	16-30
-		Hard	over 30

PENETRATION RESISTANCE

Standard Penetration Test (ASTM D-1586) - Number of blows required to drive a standard 2 in. O.D. split spoon sampler 1 ft. with a 140 lb. weight falling freely through 30 in.

COLOR: Basic colors and combinations: black, brown, gray, vellow-brown, etc.

SUPPLEMENTAL SOIL TERMINOLOGY:

- 0 to 1/16 in. thick (cohesive) Laminae Parting - 0 to 1/16 in. thick (granular) - 1/16 to 1/2 in. thick Seam

- 1/2 to 12 in thick Layer Stratum - > 12 in. thick

Pocket - Small, erratic deposit less than 12 in. size Lens - Lenticular deposit larger than a pocket Occasional - One or less per 12 in. of thickness - More than one per 12 in. of thickness Frequent Interbedded - Alternating soil layers of differing composition

- Alternating thin seams of silt and clay Varved Mottled - Variation of color

GEOLOGIC INTERPRETATION

Deposit type - GLACIAL TILL, ALLUVIUM, FILL....

The natural soils are identified by criteria of Unified Soil Classification System (USCS), with appropriate group symbol in parenthesis for each soil description. Fill materials may not be classified by USCS criteria.

U.S. Standard Series Seive Clear Square Sieve Openings 12" 3" 3/4" 10 40 200 Gravel Sand Cobbles **Boulders** Silts and Clavs Coarse Fine Coarse Medium Fine 305 mm 76 mm 19 mm 4.75 mm 2.00 mm 0.43 mm 0.074 mm

UNIFIED SOIL CLASSIFICATION SYSTEM

Coarse grained soils: Coarse grained soils: More than half of coarse fraction is larger than number 4 sieve Coarse grained soils: More than half of coarse fraction is larger than number 4 sieve Coarse grained soils: More than half is larger than number 200 sieve Coarse grained soils: Sands Sands Sands with little or no fines Gravels with over 12% fines Gravels with over 12% fines Sands Sands with little or no fines Gravels with over 12% fines Sands Sands with little or no fines Sands Sands with little or no fines Gravels with over 12% fines Sands Sands with little or no fines Sands Sands with little or no fines Sands Sands with little or no fines	MAJOF	R DIVISIONS		Group Symbol	Graphi Symbo	
Coarse grained soils: Coarse grained soils: Coarse grained soils: Coarse grained soils: Silty gravels, poorly graded gravel-sand-silt mixtures		Gravels	Gravels with	GW		Well graded gravels, gravel-sand mixtures
than number 4 sieve than number 4 sieve than number 4 sieve than number 4 sieve Sands Sands with little or no fines More than half of coarse fraction is smaller than number 4 sieve Sands with over 12% fines Sands with little or no fines Sands with over 12% fines Sands with little or no fines Sands with over 12% fines Sands with little or no fines Sands with over 12% fines Sands with over 12% fines Sands with little or no fines Sands with over 12% fines Sands or clayey silts with slight plasticity Inorganic clays of low to medium plasticity, gravelly clays, sandy clays, silty clays, lean clays Sands or clayey silts with slight plasticity CL // Inorganic clays of low to medium plasticity, gravelly clays, sandy clays, silty clays, lean clays			little or no fines	GP		Poorly graded gravels, gravel-sand mixtures
sieve over 12% fines GC Clayey gravels, poorly graded gravel-sand-clay mixtures Well graded sands, gravelly sands SP Poorly graded sands, gravelly sands SP Clayey sands, poorly graded sand-silt mixtures SM Silty sands, poorly graded sand-silt mixtures SC Clayey sands, poorly graded sand-clay mixtures SC Clayey sands, poorly graded sand-clay mixtures SC Clayey sands, poorly graded sand-clay mixtures Inorganic silts and very fine sands, rock flour, silty or clayey fine sands or clayey silts with slight plasticity Inorganic clays of low to medium plasticity, gravelly clays, sandy clays, silty clays, lean clays	9		-,	GM		Silty gravels, poorly graded gravel-sand-silt mixtures
is larger than number 200 sieve More than half of coarse fraction is smaller than number 4 sieve Sands with little or no fines Sands with little or no fines SP Poorly graded sands, gravelly sands Silty sands, poorly graded sand-silt mixtures SC Clayey sands, poorly graded sand-clay mixtures Inorganic silts and very fine sands, rock flour, silty or clayey fine sands or clayey silts with slight plasticity CL Inorganic clays of low to medium plasticity, gravelly clays, sandy clays, silty clays, lean clays	555.	sieve	over 12% fines	GC		Clayey gravels, poorly graded gravel-sand-clay mixtures
More than half of coarse fraction is smaller than number 4 sieve Sands with over 12% fines Silts and Clays Fined-grained soils: More than half of coarse fraction is smaller than number 4 sieve Sands with over 12% fines Scands with over 12% fines Scan	is larger	Sands		sw		Well graded sands, gravelly sands
Fined-grained soils: Sands with over 12% fines Silty sands, poorly graded sand-silt mixtures Clayey sands, poorly graded sand-clay mixtures Inorganic silts and very fine sands, rock flour, silty or clayey fine sands or clayey silts with slight plasticity CL Inorganic clays of low to medium plasticity, gravelly clays, sandy clays, silty clays, lean clays			or no fines	SP		Poorly graded sands, gravelly sands
Tined-grained soils: Number 4 sieve 12% fines SC Clayey sands, poorly graded sand-clay mixtures		fraction is		SM		Silty sands, poorly graded sand-silt mixtures
Fined-grained soils: Silts and Clays Silts and Clays Liquid limit 50% or less ML			12% fines	sc		Clayey sands, poorly graded sand-clay mixtures
Fined-grained soils: Liquid limit 50% or less Liquid limit 50% or less CL // Inorganic clays of low to medium plasticity, gravelly clays, sandy clays, silty clays, lean clays		Silte	and Clave	ML		
Solis.			•	CL		
more than half		Elquia IIII	MK 3070 01 1000	OL		Organic clays and organic silty clays of low plasticity
smaller than number 200 Silts and Clays MH Inorganic silty, micaceous or diatomaceous fine sandy or silty soils, elastic silts	smaller than	Silts	and Clavs	МН		Inorganic silty, micaceous or diatomaceous fine sandy or silty soils, elastic silts
sieve Liquid limit greater than 50% CH Inorganic clays of high plasticity, fat clays			•	СН		Inorganic clays of high plasticity, fat clays
OH Organic clays of medium to high plasticity, organic silts				ОН		Organic clays of medium to high plasticity, organic silts

GENERAL NOTES

1. Logs of subsurface explorations depict soil, rock and groundwater conditions only at the locations specified on the dates indicated. Subsurface conditions may vary at other locations and at other times.

Highly organic soils

2. Water levels noted on the logs were measured at the times and under the conditions indicated. During test borings, these water levels could have been affected by the introduction of water into the borehole, extraction of tools on other procedures and thus may not reflect actual groundwater level at the test boring location. Groundwater level fluctuations may also occur as a result of variations in precipitation, temperature, season, tides, adjacent construction activities and pumping of water supply wells and construction dewatering systems.

PT Peat and other highly organic soils

ROCK

Rock descriptions noted on logs of subsurface explorations are based on visual-manual examination of exposed rock outcrops and core samples. The criteria, descriptive terms and definitions used are as follows:

FIELD HARDNESS: A measure of resistance to scratching.

Cannot be scratched with a knife point Very Hard

or sharp pick.

Can be scratched with a knife point or

sharp pick, only with difficulty.

Can be readily scratched with a knife Moderately Hard

point or pick.

Medium Hard Can be grooved or gouged 1/16 in. deep with firm pressure on a knife point or

sharp pick.

Soft Can be grooved or gouged easily with a

knife point or pick.

Very Soft Can be carved with a knife and excavated

with a pick point.

WEATHERING: The action of organic and inorganic and chemical

and physical processes resulting in alteration of

color, texture and composition.

Fresh-FR No visible sign of alteration, except

perhaps slight discoloration on major discontinuity surfaces.

Slight-SL

Discoloration of rock material and discontinuity surfaces. All rock may be

discolored and/or somewhat weaker

than in its fresh condition.

Moderate-MOD Less than half the rock material is decomposed

and/or disintegrated to a soil. Some fresh or discolored rock is present as either a continuous

framework or as corestones.

More than half the rock material is High-HIGH

decomposed and/or disintegrated to a soil. Fresh or discolored rock is present as either a discontinuous framework or as corestones.

Complete-COMP

All rock material is decomposed and/or disintegrated to soil. The original mass

structure is largely intact.

Residual Soil All rock material is converted to soil. The mass

structure and material fabric are destroyed. There has been a large change of volume, but

Individual grains invisible to the unaided eye.

the material has not been significantly transported.

COLOR: Basic colors and combinations: gray, light gray, brown,

Aphanitic

TEXTURE: Size, shape and arrangements of constituents.

<u>Size</u> Term Ianeous Sedimentary > 2 mm Coarse-grained > 5 mm 0.625 - 2 mm Medium-grained 1 - 5 mm < 0.625 mm Fine-grained < 1 mm

LITHOLOGY: Rock classification and modifiers;

accepted formation names.

DISCONTINUITIES:

Type

Joint A natural fracture along which no

displacement has occurred. May occur in parallel groups called sets.

Shear A natural fracture along which

displacement has occurred. Surface may be slickensided or striated.

A natural fracture along which Fault

displacement has occurred. Usually lined with gouge and slickensides.

Shear or Fault Zone of fractured rock and gouge Zone

bordering the displacement plane.

ORIENTATION/ATTITUDE:

Term	Angle (degrees)
Horizontal	0-5
Low Angle	6-35
Moderately Dipping	36-55
High Angle	56-85
Vertical	86-100

SPACING:

Discontinuity Term	Bedding Term	Inches
Extremely Close	Extremely Thin	< 3/4
Very Close	Very Thin	3/4 - 2.5
Close	Thin	2.5 - 8
Moderate	Medium	8 - 24
Wide	Thick	24 - 80
Very Wide	Very Thick	80 - 240
Extremely Wide	Extremely Thick	> 240

PERSISTENCE/CONTINUITY: APERTURE/GAP:

erm	Feet	Term	Distance
Very Low	0-3	Very Tight	< 0.1mm
_ow	3-10	Tight	0.1mm-0.25mm
Medium	10-35	Partly Open	0.25mm-0.5mm
High	35-65	Open	0.5mm-2.5mm
Very High	> 65	Moderately Wide	2.5mm-1cm
		Wide	> 1cm
		Very Wide	1cm-10cm
		Extremely Wide	10cm-1m

Cavernous

> 1m

POROSITY:

Type

Primary:

Pre-depositional and depositional inter- and intra- granular, particle, or crystalline pores.

Secondary:

Solution features including pits, vugs, caverns, molds, and channels. Fracture features including joints, shears, faults, shrinkage and breccia fabrics.

> Term Size Micro < 0.0625 mm Meso 0.0625-4.0 mm Mega 4.0-256 mm



SUBSURFACE EXPLORATION KEY

Н		PRIC	Н			GE	OP	ROBE REPOR	T				Во	rin	g N	No.		Н	A- 1	<u> </u>
Proj Clie Cor	-	R.	A.D. S	Y HIGH S SPORTS ard Drillin		OL TRACK	, 54	N GRANBY RD, GRANE	Y CT			St St	le N neet art nish	No). 1 C	206 of octol	1 ber	20,	202	
				Casing	Samp	oler Barre	el	Drilling Equipmen	t and P	rocedures			iller			1. Ke		20,	202	
Туре	е				G			Rig Make & Model: Geo	•	620		Н	&A F	Rep). J	. Sh	aw			
Insid	de Dia	meter	(in.)		1.5	5		Bit Type: Geoprobe Sp Drill Mud: None	oon				eva atun			22.0 IAVI				
Ham	nmer \	Neight	(lb)		Aut	to -		Casing: Push	4:			\vdash	cat			ee F				
Han	nmer I	Fall (in	ı.)			-		Hoist/Hammer: - Auton PID Make & Model: Not		immer										
ft)	Blows in.	No.	£ e	(ft)	Symbol	v	/ISUA	L-MANUAL IDENTIFICATIO	N AND [DESCRIPTION		-	avel	_	San	d			eld ΄	Те
Depth (ft)	ler B r 6 ir	Sample No. & Rec. (in.)	Sample Depth (ft)	Stratum Change Elev/Depth (ft)	Syr	(Dens	ity/consistency, color, GROL	JP NAME	E & SYMBOL,		Coarse	_ e	Coarse	Medium	<u>_</u>	Fines	Dilatancy	Toughness	icity
De	Sampler I per 6 i	Sam & R¢	Sa	ie√r Sie√r	nscs (S	tructure, odor, moisture, opt GEOLOGIC INTERPR	onal des ETATIO	criptions N)		% C	% Fine	% Co	% Me	% Fine	% Fin	Oilate	Long	Plasticity
0 -	U)	G1	0.0	221.9				-TRACK RUBB	ER-			Ħ						=		Ē
		42	5.0	0.1 221.4 0.6	SW	Grow to are	ny hra	-ASPHALT- wn well-graded SAND with		SIMA no otmiction	re re	5	10	10	20 15	55		\dashv	\dashv	_
				3.5	SP	odor, dry	ıy-bro	wii well-graded SAND With	graver (S	ovv), no structu	e, 110		15	10	15	συ				
								- FILL -												
						Light red-bi		to tan poorly-graded SAND	(SP), no	structure, no c	dor,									
						moist, trace	e orga	ai iios												
5 -		G2	5.0	1	SM	•		an SAND (SM), no structure	, no odo	r, wet, wood fra	gments,		10	10	20	45	15			
		36	10.0			trace organ	IICS													
					SM	Grav to ora	y-bro	own silty SAND (SM), no stru	icture n	o odor. moist ti	race		10	15	20	30	25			
10 -					Jivi	, ,	•	, trace organics		, 1110101, 1										
10		G3 36	10.0 15.0																	
			10.0	211.0 11.0	SP		n to ta	an poorly-graded SAND with	gravel (SP), no structu	re, no	5	10	10	20	55		\dashv	\dashv	
						odor, wet														
								- GLACIOFLUVIAL DI	EPOSITS	S -										
15 -				207.0				BOTTOM OF EXPLORA	TION 15	0 FT			-						4	_
				10.0				DOTTOW OF EAFLORA	. 1011 13											
		10/	ater !	evel Data				Cample ID	\\\	ell Diagram			<u> </u>	21155	ıma	n,				_
	_4		ГІ	psed	Depth	n (ft) to:	_+	Sample ID O - Open End Rod		Riser Pipe	Over	hur				<u>ry</u> 15				_
 	ate	Time		hr Bo	ottom Casing	Bottom of Hole Wa	ter	T - Thin Wall Tube		Screen Filter Sand	Rock			•	•		1.0			
								U - Undisturbed Sample S - Splitspoon Sample	۰ qi ه	Cuttings Grout	Sam			•	•		G3	3		
								G - Geoprobe	4 A	Concrete	Bori	ing	No	ο.			Н	A-1		
Field	d Tests	: ::				Rapid S - Slo			ity: N -	Bentonite Sea Nonplastic L -	Low M - N	Medi	um	Н-	High	1				_
ielo	d Tests	s:				Rapid S - Slo - Low M - Me			ity: N - rength:	Nonplastic L - N - None L - Lo	Low M - N w M - Me	Viedi ediur	um n H	H - I - H	High igh	ا ۷ - ۷	/ery	High	1	_

HAL	EY DRIC	Н				GEO	PROBE REPORT Boring No.	HA-2
Project Client Contrac	R.A	A.D. S	/ HIGH S PORTS rd Drillin		OL 7		er 20, 2022	
		(Casing	Samp	oler	Barrel	Drilling Equipment and Procedures Finish October Driller M. Ker	er 20, 2022 n
Type Inside Di Hammer	Weight	(lb)		G 1.t Aut	5	-	Rig Make & Model: Geoprobe 6620 H&A Rep. J. Sha Bit Type: Geoprobe Spoon Elevation 222.0 Drill Mud: None Datum NAVD Casing: Push Hoist/Hammer: - Automatic Hammer	(est.) 38
Hammer		.)				-	PID Make & Model: Not used	T = = .
Depth (ft) Sampler Blows	Sample No. & Rec. (in.)	Sample Depth (ft)	Stratum Change Elev/Depth (ft)	USCS Symbol	AL-MANUAL IDENTIFICATION AND DESCRIPTION Isity/consistency, color, GROUP NAME & SYMBOL, structure, odor, moisture, optional descriptions GEOLOGIC INTERPRETATION) Gravel Sand 9 9 8 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9	Dilatancy Toughness Plasticity Strength		
- 0 -	G1	0.0	221.9				-TRACK RUBBER-	
-	42	5.0	0.1 221.4 0.6	SW SP	odo Lig	or, dry	-ASPHALT- Town well-graded SAND with gravel (SW), no structure, no tan poorly-graded SAND with gravel (SP), no structure, no	
- 5	G2 24	5.0 10.0	_	CL SP	org Re dry	ganics, trace ed-brown to I /	ndy lean CLAY (CL), no structure, no odor, moist, trace wood, appears disturbed ight brown poorly-graded SAND (SP), no structure, no odor, vancing geoprobe sleeve, observed little to no resistance	0
					bet	tween 5.4 to		
							- FILL -	
			212.0	SP	Tai	n to light bro	own poorly-graded SAND (SP), no structure, no odor, dry 10 15 20 55	
- 10 -	G3 42	10.0 15.0	10.0	SP	Lig	ht brown to	tan poorly-graded SAND (SP), no structure, no odor, moist 10 15 30 45 -GLACIOFLUVIAL DEPOSITS-	
- 15			207.0 15.0				BOTTOM OF EXPLORATION 15.0 FT	
Date	W:	Flan	(hr \ Bo	Depth	Botto	om Water	Sample ID Well Diagram O - Open End Rod T - Thin Wall Tube U - Undisturbed Sample S - Splitspoon Sample Well Diagram Riser Pipe Screen Filter Sand Filter Sand Cuttings Cuttings Samples Overburden (ft) 15.0 Rock Cored (ft) 0.0 Samples	
							Grout Grout Concrete Boring No.	HA-2
Field Tes	ts:					d S - Slow v M - Mediur		ry High

H	ALE	PRIC	н			G	EOF	PROBE REPOR	Т			Bo	rin	g N	lo.		Н	A- 3	3			
Proje Clier	ect	GR R.	A.D. S	Y HIGH S PORTS rd Drillin	Drilling								No. 0206711-000 t No. 1 of 1 October 20, 2022 n October 20, 2022									
				Casing	Samp	oler Ba	ırrel	Drilling Equipmen	t and Procedures		1	nish iller			l. Ke		20,	202				
Туре)				G			Rig Make & Model: Geo	•		Н	&A F	₹ер	. J.	Sh	aw						
Hamı	mer V	meter Veight Fall (in	(lb)		Bit Type: Geoprobe Spoon Drill Mud: None Casing: Push Hoist/Hammer: - Automatic Hammer PID Make & Model: Not used						Da	atun	itum I			222.0 (e NAVD88 See Plar						
	NS N	o 🗇		(L	 		\/ICI I				Gr	avel	5	Sano	t		Fi	eld	Te:			
Depth (ft)	Sampler Blows per 6 in.	Sample No. & Rec. (in.)	Sample Depth (ft)	Stratum Change Elev/Depth (ft)	USCS Symbol		(Dens	AL-MANUAL IDENTIFICATIO sity/consistency, color, GROL structure, odor, moisture, opti GEOLOGIC INTERPR	JP NAME & SYMBOL, ional descriptions		% Coarse	% Fine	% Coarse	% Medium	% Fine	% Fines		SS	Plasticity			
0 +	0)	G1	0.0	221.9		\		-TRACK RUBB	ER-	/	F								=			
		36	5.0	0.1 221.4 0.6	SW SP	odor, dry		-ASPHALT- own well-graded SAND with an poorly-graded SAND (SP	gravel (SW), no structu	,	5			20 20								
5 —					SP	J		orown poorly-graded SAND (,					20								
		G2 36	5.0 10.0		SP	Tan to lig	ght brov	wn poorly-graded SAND (SP -FILL-), no structure, no odoi	, dry		10	15	20	55							
10 —		G3 36	10.0 15.0	212.5 9.5 - 212.0 10.0	SM SP	•		y SAND (SM), no structure, r an poorly-graded SAND (SP - GLACIOFLUVIAL DE), no structure, no odor	, moist				20 30	40 55	40						
15 —				207.0 15.0				BOTTOM OF EXPLORA	TION 15.0 FT													
Da	ate	Wa Time			Depth ottom I	n (ft) to: Bottom of Hole	/ater	Sample ID O - Open End Rod T - Thin Wall Tube U - Undisturbed Sample S - Splitspoon Sample G - Geoprobe	Well Diagram ☐ Riser Pipe ☐ Screen ☐ Filter Sand ☐ Cuttings ☐ Grout ☐ Concrete	Over Rock Sam	Co ples	den ored	(ft		15	.0 G3	A-3					
				Dilatano	w P F) 	Ol N	I None Plactic	Bentonite Se city: N - Nonplastic L -	al	_			Hiah	1				—			
Field												uill	11-									

HALE	Y DRIC	Н				GEO	PROBE REPOR	Г		E	301	rin	g N	lo.		Н	A -4	4				
Project Client Contracto	R.A	A.D. SI	PORTS	HIGH SCHOOL TRACK, 54 N GRANBY RD, GRANBY CT ORTS I Drilling							File No. 0206711-000 Sheet No. 1 of 1 Start October 20, 2022 Finish October 20, 2022											
			Casing Sampler Barrel Drilling Equipment and Procedures								ıısn Iler			icto I. K		20,	202	22				
Туре			G Rig Make & Model: Geoprobe 6620 Bit Type: Geoprobe Spoon							Н8	A F	Rep	. J.	. Sh	aw							
Inside Dia	meter ((in.)		1.5	5		Bit Type: Geoprobe Spo Drill Mud: None	oon			evat tum) (e D88	est.))					
Hammer \	Veight	(lb)		Aut	to	-	Casing: Push		-		cati				Plar							
Hammer I	all (in.	.)				-	Hoist/Hammer: - Auton PID Make & Model: Not															
Sampler Blows per 6 in.	No.	æ (£)	Stratum Change Elev/Depth (ft)	Symbol		VISU	IAL-MANUAL IDENTIFICATIO	N AND DESCRIPTION	- t		vel		Sand	d			ield တွ	Tes	st			
Depth (ft) ampler Blov per 6 in.	ec. (Sample Depth (ft)	tratur hang Dept	S Syl		(Der	nsity/consistency, color, GROL			% Coarse	Fine	Coarse	Medium	ne	Fines	Dilatancy	Toughness	icity				
Samp Pe	Sample No. & Rec. (in.)	S e	Elev/	nscs			structure, odor, moisture, opti GEOLOGIC INTERPR			ŏ %	% Fi	ŏ %	W %	% Fine	% Fi	Dilat	Toug	Plasticity				
0	G1	0.0	221.9				-TRACK RUBB	ER-											Ē			
	30	5.0	0.1 221.4 0.6	SW SP	Gra	v to grav-b	-ASPHALT- rown well-graded SAND with	aravel (SW), no structure, n	_1	5	10 10	10 15	20 20	55 55					Ī			
					odo	r, dry	oorly-graded SAND (SP), no s															
					Ligi	it brown po	ony graded of the (or), he o	nactare, no caor, ary														
5	G2 12	5.0 10.0		SP	Ligh dry	nt brown to	red-brown poorly-graded SAN	ID (SP), no structure, no oc	or,		10	15	20	55								
						e: Upon ad ween 5.4 to	vancing geoprobe sleeve, ob 5.8 ft.	served little to no resistance														
10																						
	G3 42	10.0 15.0		SP	poc		n poorly graded SAND (SP), r k brown organics, occasional					10	20	70								
			209.0 13.0	SP	Ligh	nt brown po	oorly-graded SAND with grave	I (SP), no structure, no odo		5	10	15	20	50					L			
					dry																	
			207.0	SM	Ligr	nt drown sii	ty SAND (SM), no structure, r	o odor, ary					20	40	40							
15			207.0 15.0		<u> </u>		- GLACIOFLUVIAL DE BOTTOM OF EXPLORAT		-1										l			
				<u> </u>																		
	Wa		vel Data	Depth	h (ft)	to:	Sample ID	Well Diagram Riser Pipe					ma						-			
Date	Time	Elap Time	(hr Bo	ttom	Bottor	n Mater	O - Open End Rod T - Thin Wall Tube	Screen	Overb Rock			`	,		5.0							
			10T C	asing	of Hol	е	U - Undisturbed Sample S - Splitspoon Sample	Cuttings	Rock Samp			(IL)	C).0 G3	3						
							G - Geoprobe	Grout	3orir							, Д-4	L		-			
			1			1																

HA	LEY	H	Sompler Barrel Drilling Equipment and Procedures Simpler Barrel Drilling Equipment and Procedures Sampler Barrel Drilling Equipment and Procedures Bit Type: Geoprobe Spoon Driller M. Kern	5												
Project Client Contra	ct GRANBY HIGH SCHOOL TRACK, 54 N GRANBY RD, GRANBY CT tractor Sea Board Drilling Casing Sampler Barrel Drilling Equipment and Procedur						Sheet No. 1 of 1 Start October	Sheet No. 1 of 1 Start October 20, 2022								
	ET GRANBY HIGH SCHOOL TRACK, 54 N GRANBY RD, GRANBY CT RAD. SPORTS sector See Board Drilling Casing Sampler Barrel Drilling Equipment and Procedures Orbital Start Final Control of the Casing Sampler Barrel Drilling Equipment and Procedures Orbital Start Final Control of Casing Push High Start Push Push Push Push Push Push Push Push		, -													
Туре	GRANBY HIGH SCHOOL TRACK, 54 N GRANBY RD, R.A.D. SPORTS ctor Sea Board Drilling Casing Sampler Barrel Drilling Ed. Casing Sampler Barrel Drilling Ed. G. Rig Make & Mod. Bit Type: Geop. Drill Mud: None. Casing: Push Hoist/Hammer: - PID Make & Mod. VISUAL-MANUAL IDENT (Density/consistency, col. structure, odor, mol. SP. Gray to gray-brown well-graded SA.D. v. Mote: Upon advancing geoprobe si between 2.4 to 2.6 ft. Water Level Data Water Level Data SP. Light brown to red-brown poorly-graded SAND (SM), wood, dark lenses of organics, post disturbed Water Sex Depth (ft) to: - O'	Di Tamani G														
		` ′					Drill Mud: None Datum NAVD8	3								
Hamm	er Fall(i				to	GEOPROBE REPORT TRACK, 54 N GRANBY RD, GRANBY CT File No. 0206711-000 Sheet No. 1 of 1 Shart October 20, 2022 File Barrel Drilling Equipment and Procedures Filish October 20, 2022 Bit Type: Geoprobe Spoon Drill Mud: None Casing: Push H&A Rep. J. Shaw Elevation 222.0 (est.) Datum NAVD88 Location See Plan VISUAL-MANUAL IDENTIFICATION AND DESCRIPTION (Idensity/consistency, colorr, GROUP NAME & SYMBOL, structure, no odor, moist under the structure of the structure, no odor, moist notice; Casing: Plant Type 1 Structure, no odor, moist notice; Casing: Plant Type 1 Structure, no odor, moist notice; Casing: Plant Type 1 Structure, no odor, moist notice; Casing: Plant Type 1 Structure, no odor, moist notice; Casing: Plant Type 1 Structure, no odor, moist notice; Casing: Plant Type 1 Structure, no odor, moist notice; Casing: Plant Type 1 Structure, no odor, moist notice; Casing: Plant Type 1 Structure, no odor, moist notice; Casing: Plant Type 1 Structure, no odor, moist notice; Casing: Plant Type 1 Structure, no odor, moist notice; Casing: Plant Type 1 Structure, no odor, moist notice; Casing: Plant Type 1 Structure, no odor, moist notice; Casing: Plant Type 1 Structure, no odor, moist notice; Casing: Plant Type 1 Structure, no odor, moist notice; Casing: Plant Type 1 Structure, no odor, moist notice; Casing: Plant Type 1 Structure, no odor, moist notice; Casing: Plant Type 1 Structure, no odor, moist notice; Casing: Plant Type 1 Structure, no odor, moist notice; Casing: Plant Type 1 Structure, no odor, moist notice; Plant Type 1 Structure, no odor, moist notice; Plant Type 1 Structure, no odor, moist notice; Plant Type 1 Structure, no odor, notice; Plant Type 1 Structure, no odor, notice; Plant Type 1 Structure, no odor, notice; Plant Type										
(ft) Slows	Contractor Sea Board Drilling Start Casing Sampler Barrel Drilling Equipment and Procedures Finish Casing Sampler Barrel Drilling Equipment and Procedures Finish Driller Finish Casing Sampler Barrel Drilling Equipment and Procedures Finish Casing Finish Casing Sampler Barrel Drilling Equipment and Procedures Finish Casing Sampler Samp		Test													
Depth (ft)	per 6 ii Sample & Rec. (Samp Depth	Stratur Chang Elev/Dept	JSCS Sy		(Der	nsity/consistency, color, GROUP NAME & SYMBOL, structure, odor, moisture, optional descriptions GEOLOGIC INTERPRETATION)	Dilatancy Toughnes	Plasticity							
0	G1		221.9				-TRACK RUBBER-									
	36	5.0	221.4 0.6		Gra	ay to gray-bi	/ 3 10 10 20 33									
					odo Lig	or, dry ht brown po										
-					1	•										
5							-FILL-									
				SP			red-brown poorly-graded SAND (SP), no structure, no odor,									
10			212.0 10.0	SM					_							
					\dis	turbed	BOTTOM OF EXPLORATION 10.0 FT									
					<u> </u>											
	W				h (ff) to:	Ricar Pine									
Date	e Time		hr Bo	ottom	Botto	Motor	T - Thin Wall Tube Screen Screen Rock Cored (ft) 0.0									
							U - Undisturbed Sample S - Splitspoon Sample S - Splitspoon Sample Grout Samples Grout	2								
							l (i - Geoprope	A-5								
	ests:		Dilatano	cy : R-I	Rapic	d S - Slow		/ High								

ALDRICH		GEOPROBE REPORT						Boring No. HA-											
Projec Client	et	GR/ R.A	ANBY	PORTS							File No. 0206711-000 Sheet No. 1 of 1 Start October 20, 20 Finish October 20, 20								
				Casing	Sampler Barrel Drilling Equipment and Procedures						iller			1. K		20,	202		
Туре					G	i	Rig Make & Model: Ge	-		Нδ	&A F	Rep	. J.	. Sh	aw				
Inside Diameter (in.) Hammer Weight (lb) Hammer Fall (in.) Babel Blows O Babel Blows O Gamble No. (ir.) Gamble No. (ir.) Gamble So Gamble So. 2 Gamble So. 2 Gamble So. 2 Gamble So. 36 Gamble So.			1.5	5	Bit Type: Geoprobe Spoon Drill Mud: None									est.)					
Hamm	roject GRANB R.A.D. Sontractor Sea Board Grant G	(lb)		Au	to -	Casing: Push			Datum Location					NAVD88					
Hammer Fall (in.))			-		Hoist/Hammer: - Automatic Hammer PID Make & Model: Not used												
f) ows		. (-)	⊕£	Œ	loge	VIS	SUAL-MANUAL IDENTIFICATION				avel		Sand	d				Те	::
oth (.e i	ple i	mpl xh (i	atun ange Jepth	Symbol	(De	ensity/consistency, color, GRC			Coarse	ā	Coarse	Medium	ā	es	ncy	Seuc	city	
Deg	be ,	& Re	Sa Dep	Str Sch	nscs (,	structure, odor, moisture, op GEOLOGIC INTERP	itional descriptions RETATION)		% Co	% Fine	% Co	% Me	% Fine	% Fines	Dilatancy	Toughness	Jasti	
0			0.0	221.9			-TRACK RUBI	BER-		6	0	0	6	6	0,			=	:
				0.1 221.4 0.6	SW		-ASPHAL1	-		5	10	10	20	55					22
				0.0	SP	Gray to gray- odor, dry	brown well-graded SAND with	gravel (SW), no structure	, no	5	10	15	20	50					
							poorly-graded SAND with grav	el (SP), no structure, no o	dor,										
5 —		1																	
10					SM SP	occasional da	o tan silty SAND (SM), no stru ark brown organic lenses poorly-graded SAND (SP), no wood						20						
			15.0			Dottom o m. v	- FILL-												
15				207.0 15.0	SP		o tan poorly-graded SAND (S lenses, trace brick particles,				10	15	20	55				_	
						middle of san	•	, ,	/										
		Wa	ter Le	evel Data	a	1	Sample ID	Well Diagram		1		Sum	ıma	ry				=	-
- 15 Date	•	Time	Elap Time	(hr Bo	ottom	h (ft) to: Bottom of Hole Wate	U - Undisturbed Sample S - Splitspoon Sample	Riser Pipe Screen Filter Sand Cuttings Grout		burden Cored		. ,		10.0 0.0 G		3			
							G - Geoprobe	Concrete Bentonite Seal	Bori	_	No.				H	A- 6	; 		
	ests:			Dilatano	y : R-	Rapid S - Slow	N - None Plast	icity: N - Nonplastic L - Lo	w M-M	ledi	um	Н-	High	1			h		•

ALDRICH		GEOPROBE REPORT						Boring No. HA-7									
Project Client	GRAI R.A.[File No. 0206711-000 Sheet No. 1 of 1 Start October 20, 2022 Finish October 20, 2022								
		Casing	Samp	oler Barrel	Drilling Equipmer	nt and Procedures			nısn iller			ictoi I. Ke		20,	20	22	
Type			G Rig Make & Model: Geoprobe 6620						&A F	₹ер	. J.	Sh	aw				
Client R.A.D. SF Contractor Sea Boar		'	1.5 Auto		Bit Type: Geoprobe Spoon Drill Mud: None Casing: Push					Elevation 222.0 (est.) Datum NAVD88 Location See Plan							
				Hoist/Hammer: - Automatic Hammer - PID Make & Model: Not used													
ft) lows	o (÷ d	(E) (E)	lodin	VISU	JAL-MANUAL IDENTIFICATIO	ON AND DESCRIPTION	t t		avel	_	Sand	d					!
Depth (Sampler B	Sample & Rec. (Depth (Stratur Chang	USCS Syr	(Der	nsity/consistency, color, GROU structure, odor, moisture, opt GEOLOGIC INTERPR	tional descriptions		% Coarse	% Fine	% Coarse	% Medium	% Fine	% Fines	Dilatancy	Toughness	Plasticity	
0		221.9	\vdash		-TRACK RUBB	ER-										F	
	42 5	5.0 221.4 0.6	SW	Gray to gray h	-ASPHALT- rown well-graded SAND with			5	10	10	20 20	55			_		-
		221.0	52	odor, dry	TOWN WEN-GLAUEU SAND WILL	graver (GVV), no structure	110		10	15	20	55					
				1	- FILL -		į										
					brown poorly-graded SAND ((SP), no structure, no odo	-, dry,										22 22 Test
				trace brick													
			HIGH SCHOOL TRADORTS Drilling asing Sampler B G 1.5 Auto		- FILL -												
5	G2 :	5.0															
	1 1																
		045.0															
		7.0	SP	Tan to light red no odor, dry	d-brown poorly-graded SAND	with gravel (SP), no struc	ture,	5	10		20	65					
					- GLACIOFLUVIAL D	EPOSITS -											
10																	
			SP	Light red-brow	n poorly-graded SAND (SP),	no structure, no odor, dry						100					722 722 Test
15		207.0 15.0			BOTTOM OF EXPLORA	TION 15.0 FT										<u> </u>	-
																	_
		r Level Dat		/ft\ +-:	Sample ID	Well Diagram					ıma	ry				_	-
Date	1 1111111111111111111111111111111111111		Bottom Bottom Water T - Thin Wall Tube Screen						red	•	•						
					G - Geoprobe	Grout		oring No						<u>н</u> А-7			
	s:	Dilatan	cv R-F	Ranid S - Slow	N - None Plastic	city: N - Nonplastic L - Lo	w M-M	edi	um	H-	Hiah	1			h		

APPENDIX B
Recent Geoprobe Logs

Н		Y	н				GEO	PROBE REPOR	Т		E	Зоі	rin	g N	No.		GI	P-0)1	
Clie	oject ent ntracto	GR	ANBY	/ PUBLI / PUBLI BSURF	C SCI			FIELD AND TRACK, GRA	ANBY, CT		Sho Sta	eet art	No		of 23 J	1 une	202			
			(Casing	Sam	pler	Barrel	Drilling Equipment	t and Procedures			ish Iler		∠ B. V			202	23		
Han	de Dia nmer \ nmer I	meter (Weight Fall (in.	(lb)		1. AU	5	- - -	Rig Make & Model: Geo Bit Type: Geoprobe Spo Drill Mud: None Casing: Push Hoist/Hammer: Winch PID Make & Model: Not	oon Automatic hammer		Ele Da	A F evat tum cati	Rep tion). I	C. 22 NA	Cra		st.)		
Depth (ft)	Sampler Blows per 6 in.	Sample No. & Rec. (in.)	Sample Depth (ft)	Stratum Change Elev/Depth (ft)	USCS Symbol		VISU	JAL-MANUAL IDENTIFICATION (Color, GROUP NAME, may structure, odor, moisture, option GEOLOGIC INTERPRI	N AND DESCRIPTION c. particle size [†] , onal descriptions		% Coarse as	_	% Coarse	% Medium	% Fine	% Fines		e ssaudbnoL		
- 0 -	0)	G-1	0.0	1				-CRUSHED STC	DNE-									$\dot{\exists}$		-
- -		44	5.0	222.5 0.5	SP	Light	brown po	oorly-graded SAND (SP), no st				5	20	50	20	5				
- 5 - - -		G-2 30	5.0	-	SP	Tanı	to light bro	own poorly-graded SAND (SP), no structure, no odor, dr	у		5	5	30	55	5				
- 10 -				213.0				BOTTOM OF EXPLORAT	FION 40.0 FT											
		Wa	ater Le	evel Dat				ion backfilled upon completion	well Diagram			9	Sum	nma	ry					
D	ate	Time	Elap	sed		h (ft) t Bottom		O - Open End Rod	Riser Pipe Screen	Overb	urc					10.0)			
			Time			of Hole	I WYSTAR	U - Undisturbed Sample	Filter Sand Cuttings	Rock			(ft	•		0.0				
								S - Splitspoon Sample G - Geoprobe	Grout Concrete	Samp) .	G	i <u>Z</u>	GF	P-0 ⁻	1		
Field	d Tests	L ;:	1	Dilatan	cy: R-	Rapid	S - Slow		Bentonite Seal ity: N - Nonplastic L - Low rength: N - None L - Low							\/or	, µ:~			
† No	ote: Ma			e size is	determ	ined by	y direct ol	m H - High Dry Sti bservation within the limitation isual-manual methods of the	ns of sampler size.							very	ITIG	<u>'</u>		

Н		Y	н				GEO	PROBE REPOR	Ī		E	Bo	rin	g N	lo.		G	P-0)2	
Clie	oject ent ntracto	GR	RANBY	' PUBLI ' PUBLI BSURF.	C SCF			FIELD AND TRACK, GRA	NBY, CT		Sh Sta		No	. 1 2	of 3 J	1 une	20: 20:			
				Casing	Sam	oler	Barrel	Drilling Equipment	and Procedures			nish iller		∠ B. \			20.	25		
Han	de Dia nmer \ nmer I	meter Veight Fall (in	(lb)		G 1.5 AUT	5	- - -	Rig Make & Model: Geo Bit Type: Geoprobe Spo Drill Mud: None Casing: Push Hoist/Hammer: Winch PID Make & Model: Not	oon Automatic hammer		Ele	&A F eva atum ocati	Rep tion า	١.	C.	Cra 2.5 4VE	avir (e: 088 n			
Depth (ft)	Sampler Blows per 6 in.	Sample No. & Rec. (in.)	Sample Depth (ft)	Stratum Change Elev/Depth (ft)	USCS Symbol		VISL	JAL-MANUAL IDENTIFICATION (Color, GROUP NAME, max structure, odor, moisture, option GEOLOGIC INTERPRESE	N AND DESCRIPTION a. particle size [†] , conal descriptions		% Coarse 요	% Fine	% Coarse	% Medium	% Fine	% Fines		Loughness ei	Plasticity 3	
- 0 -		G-1 38	0.0	222.0 0.5		Dorle	brown oil	-CRUSHED STO				10	10	30	20	20				
-		36	5.0	221.0	SM	Dark	. Drown Sii	ty SAND (SM), no structure, n	o odor, ary											
-			ructure, no odor, dry			5	20	50	20	5										
- 5 - - -		, no structure, no odor, dr	у		5	5	40	45	5											
				212.5 10.0																
- 10 -				TON 10.0 FT																
		Wa	ater Le	evel Dat	a	Note	: Explorat	ion backfilled upon completion	vell Diagram			S	Sum	ıma	ry					
	ate	Time	Flan	sed	Deptl	ր (ft)		Sample ID O - Open End Rod	Riser Pipe	Overb	our					10.0)			_
L	ait	riille	Time			Bottom of Hole	Water		Screen Filter Sand	Rock	Со	red	•)		0.0				
								S - Splitspoon Sample G - Geoprobe	Grout Concrete Bentonite Seal	Samp) .	G	2	GF	P-0:	2		
Field	d Tests	;: :		Dilatano Toughn	cy: R-l	Rapid - <u>L</u> ow	S - Slow M - Mediu		ity: N - Nonplastic L - Low rength: N - None L - Low							Verv	<u>/ H</u> ia	<u>h</u>		
† No	ote: Ma			e size is	determ	ined b	y direct ol	oservation within the limitation isual-manual methods of the	ns of sampler size.											

Н	ALE	Y	Н				GEO	PROBE REPOR	Г		I	Во	rin	g N	No.		G	P-0	13	
Pro Clie Cor	-	GF	RANB	Y PUBLI Y PUBLI IBSURF.	C SCF			FIELD AND TRACK, GRA	ANBY, CT		Sh Sta	eet art	No). 1 2	of 23 J	une	20 20 20			
				Casing	Sam	pler	Barrel	Drilling Equipmen	t and Procedures			nish iller		ے B. \				25		
Тур	е			-	G		-	Rig Make & Model: Geo			Н8	&A F	Rep).	C.	Cra	avir	ıho		
Insid	de Dia	meter	(in.)	-	1.5	5	-	Bit Type: Geoprobe Spo Drill Mud: None	oon			eva atun	tion	1) (e:)88			
Han	nmer \	Veight	(lb)	-	AUT	го	-	Casing: Push Hoist/Hammer: Winch	Automatic hammar					S		Pla				
Han		all (in	1.)	-	_		-	PID Make & Model: Not												
Œ	Sampler Blows per 6 in.	Sample No. & Rec. (in.)	le (ft)	Stratum Change Elev/Depth (ft)	Symbol		VISU	JAL-MANUAL IDENTIFICATIO	N AND DESCRIPTION			avel	_	Sano F				ield g		
Depth (ft)	oler E er 6 i	nple tec. (Sample Depth (ft)	tratui hang Dept	S Sy			(Color, GROUP NAME, max structure, odor, moisture, opti			Coarse	Fine	Coarse	Medium	Fine	Fines	Dilatancy	Toughness	Plasticity	Strength
۵	Sam	Sar & F	S	Elev	USCS			GEOLOGIC INTERPR	ETATION)		%	% F	8	№ №	% F	% F	Dila	Lou	Plas	Stre
- 0 -		G-1 40	0.0	222.5 0.5	SP-	_		-CRUSHED STO	·· ·			_	-	45	00	10				
-		40 5.0 0.5 SP- Tan to light brown poorly-graded SAND with silt (SP-SM), no odor, dry -FILL-										5	20	45	20	10				
_															ĺ					
															ĺ					
_																				
-																				
- 5 -		G-2	no odor, dry, occasional d			Ļ.	<u> </u>	10	30	60		$\vdash \downarrow$	$\vdash \dashv$	-						
		60	5.0 10.0	l/loess soil horizon	air				10	30					ĺ					
-				215.5 7.5												ĺ				
-				7.5	POSITS-															
_																				ĺ
				213.0															ĺ	
- 10 -				213.0 10.0				BOTTOM OF EXPLORAT	TION 10.0 FT									П		
					٦.															
																				ĺ
																				ĺ
																				ĺ
																				ĺ
																				ĺ
																				ĺ
																				ĺ
		W	ater Le	evel Dat	 a			Sample ID	Well Diagram				Sum	ıma	rv		Ш			
П	Depth (ft) to: O - Open End Rod Server												(ft			10.0	—)			
<u> </u>		Time (hr. Bottom Bottom Water T - Thin Wall Tube Screen Filter Sand U - Undisturbed Sample Filter Sand											(ft	′		0.0				
								S - Splitspoon Sample	Cuttings Grout	Samp	oles	i		G	2					
G - Geoprobe G - Geoprobe Concrete Bentonite Seal											No	ο.			GF	P-0	3			
Field	d Tests	:	'				S - Slow M - Mediu	N - None Plastic m H - High Dry Str	ity: N - Nonplastic L - Lorength: N - None L - Low	w M - N M - Med	ledi diun	um n H	H - I - Hi	High igh	า V -	Very	/ Hig	jh		

Н		Y	Н				GEO	PROBE REPOR	Т		E	301	rin	g N	No.		G	P-0)4	
Clie	ject ent ntracto	GF	RANB	/ PUBLI / PUBLI BSURF	C SCI			FIELD AND TRACK, GRA	ANBY, CT		Sh Sta	eet art	No		of 23 J	1 une	20 20 20			
			(Casing	Sam	pler	Barrel	Drilling Equipmen	t and Procedures			nish iller		ے B. \				20		
Тур	е			-	G	;	-	Rig Make & Model: Geo	-			&A F			C.	Cr	avir	ıho		
Insid	de Dia	meter	(in.)	-	1.	5	-	Bit Type: Geoprobe Spo Drill Mud: None	oon			evat atum		ı	22 N	22.0 AV/) (e:)88	st.)		
		Veight	` ′	-	AU	го	-	Casing: Push Hoist/Hammer: Winch	Automatic hammer	-		cati		S	ee					
Han		-all (in	.)	-	-		-	PID Make & Model: Not												
Œ	Sampler Blows per 6 in.	Sample No. & Rec. (in.)	⊕ Œ	Stratum Change Elev/Depth (ft)	Symbol		VISL	JAL-MANUAL IDENTIFICATIO	N AND DESCRIPTION	 -	_	avel	_	Sano				ield g		
Depth (ft)	oler E er 6 i	nple tec. (Sample Depth (ft)	tratui hang/ Dept	SSy			(Color, GROUP NAME, max structure, odor, moisture, opti			Coarse	Fine	Coarse	Medium	Fine	Fines	Dilatancy	Toughness	Plasticity	Strength
۵	Sam	San & R	യപ്പ	Ee o s	nscs			GEOLOGIC INTERPR	ETATION)		ပ %	% F	% C	W %	% F	% F	Dilat	Lough	Plas	Stre
- 0 -		G-1	0.0	221.5				-CRUSHED STO			5	40								
-		38 5.0 0.5 SM Dark brown silty SAND with gravel (SM), no structure, no odor, dr										10	10	25	30	20				
-								- FILL -												
), no structure, no odor, di	У		5	20	50	20	5										
-				EPOSITS -																
- 5 -		G-2	5.0), no structure, no odor, di	v		5	20	50	20	5									
		40	j, no structure, no odor, di	y			20	30	20											
-																				
-																				
_																				
				212.0 10.0																
- 10 -		TION 10.0 FT																		
		n.																		
		Water Level Data Sample ID Well Diagram Label Flapsed Depth (ft) to: One Depth Rod												ıma	ırv	<u> </u>		Ш		
П	ate	Time	Riser Pipe	Overb	urc					10.0	—)									
ــــّـا			Time			Bottom of Hole		T - Thin Wall Tube U - Undisturbed Sample	Screen Filter Sand	Rock	Со	red	•	•		0.0				
								S - Splitspoon Sample G - Geoprobe	្រី: ។ Cuttings Grout	Samp	es			G	2					
								G - Geoprope	Concrete Bentonite Seal	Borin	ıg	No).			GI	P-0	4		
Field	d Tests	:	'				S - Slow M - Mediu	N - None Plastic m H - High Dry Str	city: N - Nonplastic L - Low rength: N - None L - Low	v M - Me M - Med	ediu ium	ım H r	H - I - H	High	า V -	Very	/ Hig	jh		

Н		Y	н				GEO	PROBE REPOR	Γ		ı	Во	rin	g N	lo.		GI	P-0)5	
Clie	oject ent ntracto	GR	ANBY	' PUBLI ' PUBLI BSURF.	C SCH			FIELD AND TRACK, GRA	NBY, CT		Sh St	e N neet art	No	· 1	of 3 J	1 une	202			
			(Casing	Sam	pler	Barrel	Drilling Equipment	and Procedures		ı	nish iller		ے B. V			202	23		
Han	de Dia nmer \	meter (Weight Fall (in.	(lb)	- - -	1.5 AU ⁻	5	- - -	Rig Make & Model: Geo Bit Type: Geoprobe Spo Drill Mud: None Casing: Push Hoist/Hammer: Winch PID Make & Model: Not	oon Automatic hammer		El Da	&A F eva atum cati	Rep tion า	١.	C.	Cra 3.0 AVE	avin (es 088 n			
Depth (ft)	Sampler Blows per 6 in.	Sample No. & Rec. (in.)	Sample Depth (ft)	Stratum Change Elev/Depth (ft)	USCS Symbol		VISL	JAL-MANUAL IDENTIFICATIOI (Color, GROUP NAME, may structure, odor, moisture, optimature, optimature)	N AND DESCRIPTION a. particle size [†] , conal descriptions		% Coarse	avel % Eine	% Coarse	% Medium	% Fine	% Fines		Loughness e	Plasticity a	
- 0 -	0,	G-1 39	0.0 5.0	222.5 0.5 221.5 1.5	SM		brown sil	-CRUSHED STC ty SAND with gravel (SM), no material - FILL -		ace	5	10			30	20				
- - -		, no structure, no odor, di	/у		5	20	50	20	5											
- 5 - - -		G2 40	, no structure, no odor, di	у	5	5	20	45	20	5										
- 10 -				213.0 10.0				BOTTOM OF EXPLORAT	TION 40 0 FT											
		Wæ	ater Le	evel Dat	a	Note	e: Explorat	ion backfilled upon completion				S	Gum	ıma	ry					
	ate	Time	Flan	sed	Dept	h (ft)		Sample ID O - Open End Rod	Riser Pipe	Overl	bur					10.0				_
L	ale	Tille	Time			Bottom of Hole	Water	T - Thin Wall Tube U - Undisturbed Sample	Screen Filter Sand	Rock	Сс	red	•)		0.0				
								S - Splitspoon Sample G - Geoprobe	Cuttings Grout Concrete Bentonite Seal	Samp Bori	ng	No		G		GF	P-0	5		
L	d Tests			Toughn	<u>ess: L</u>	- Low		m H - High Dry Str	ity: N - Nonplastic L - Lovength: N - None L - Low							Very	/ Hig	h		
_ [™] No	ote: Ma							oservation within the limitation sual-manual methods of th		y Hale	y &	Ald	lric	n, Ir	ıc.					

Н		Y	Н				GEO	PROBE REPOR	Т		E	301	rin	g N	10.		G	P-0)6	
Clie	ject ent ntracto	GF	RANB	/ PUBLI / PUBLI BSURF.	C SCF			FIELD AND TRACK, GRA	ANBY, CT	3	She Sta	eet art	o. No). 1 2	of 23 J	1 une	20			
			(Casing	Sam	pler	Barrel	Drilling Equipment	t and Procedures			iish Iler		ے B. V			: 20.	23		
Тур	е			-	G	;	-	Rig Make & Model: Geo		ŀ	4&	ΑF	Rep	١.	C.	Cra	avir	ıho		
Insid	de Dia	meter	(in.)	-	1.5	5	-	Bit Type: Geoprobe Spo Drill Mud: None	oon	I .		evat tum	tion	l	22 N/	23.0 AVE	(e:	st.)		
Han	nmer \	Veight	(lb)	-	AU	го	-	Casing: Push Hoist/Hammer: Winch	Automotic homens	—			ion	S	ee l					
Han		Fall (in	1.)	-	-		-	PID Make & Model: Not												
Œ	Sampler Blows per 6 in.	No.	(#)	Stratum Change Elev/Depth (ft)	Symbol		VISU	JAL-MANUAL IDENTIFICATION	N AND DESCRIPTION	-		ıvel	-	Sand				ield ဖွ		st
Depth (ft)	oler B	oldı ec. (Sample Depth (ft)	tratur hang Dept	Syl			(Color, GROUP NAME, max			Coarse	Fine	Coarse	Medium	Fine	Fines	ancy	Toughness	icity	gth
De	Samp	Sample No. & Rec. (in.)	S	Elev Si	nscs			structure, odor, moisture, opti GEOLOGIC INTERPRI	ETATION)	3	္ %	% Fi	% Cc	W W	% Fi	% Fi	Dilatancy	Toug	Plasticity	Strength
- 0 -	0,	G-1	0.0	222.5 0.5				-CRUSHED STC			Ħ	\dashv	F					Ħ		
-	39 5.0 0.5 SP- Light brown poorly-graded SAND with silt (SP-SM), no structure, SM dry											5	20	45	20	10				
		- GLACIOFLUVIAL DEPOSITS -																		
_		POSITS -																		
- 5 - -		G-2 35	5.0 10.0	tructure, no odor, dry			5	20	40	35										
- - - - 10 -				213.0				DOTTOM OF EVOLODA	TION 40 0 FT											
	Note: Exploration backfilled upon completion.																			
		Well Diagram				Sum		ry		_										
D	ate	Riser Pipe Screen	Overb			•	•		10.0											
			Time	of C	Casing	of Hole	Water	U - Undisturbed Sample	Filter Sand	Rock ((ft	:) G		0.0				
	S - Splitspoon Sample G - Geographe Grout												 D.			GI	P-0	6		
Field	d Tests	<u>.</u>		Dilatan	cv: R-	Rapid	S - Slow	N - None Plastic	Bentonite Seal ity: N - Nonplastic L - Lov	Borin M - Me	_			High	— 1					
L		-						ım H - High Dry Stı	rength: N - None L - Low	M - Medi	<u>um</u>	<u> </u>	<u>ı - Hi</u>	gh	<u>V - '</u>	Very	/ Hig	h_		

Note: Maximum particle size is determined by direct observation within the limitations of sampler size.

Note: Soil identification based on visual-manual methods of the USCS as practiced by Haley & Aldrich, Inc.

Н		Y	н				GEO	PROBE REPOR	Γ		ı	Bo	rin	g N	lo.		GI	>-0	7	
Clie	oject ent ntracto	GR	ANBY	' PUBLI ' PUBLI BSURF.	C SCH			FIELD AND TRACK, GRA	NBY, CT		Sh Sta	eet art	No		of 3 J	1 une	202			
			(Casing	Sam	pler	Barrel	Drilling Equipment	and Procedures			nish iller		ے B. V			202	23		
Han	de Dia nmer \ nmer I	meter Weight Fall (in	(lb)	- - -	1.5 AU	5	- - -	Rig Make & Model: Geo Bit Type: Geoprobe Spo Drill Mud: None Casing: Push Hoist/Hammer: Winch PID Make & Model: Not	oon Automatic hammer		Ele	&A F eva atum ocati	tion		22	3.0 AVE				
Depth (ft)	Sampler Blows per 6 in.	Sample No. & Rec. (in.)	Sample Depth (ft)	Stratum Change Elev/Depth (ft)	USCS Symbol		VISL	JAL-MANUAL IDENTIFICATION (Color, GROUP NAME, max structure, odor, moisture, option GEOLOGIC INTERPRI	c. particle size [†] , onal descriptions ETATION)		% Coarse	level %	% Coarse	% Medium	% Fine	% Fines		SS	Plasticity sal	
- 0 -		G-1 34	0.0 5.0	222.5 0.5	SM	Dark	brown sil	-CRUSHED STO ty SAND with gravel (SM), no			5	10	10	25	30	20			\dashv	
-				222.0 1.0	SP	Tan	to liaht bro	- FILL - own poorly-graded SAND (SP)), no structure, no odor, dr	/		5	5		30				7	
-							ng	- GLACIOFLUVIAL DE		,										
- 5 - -		G-2 60), no structure, no odor, dr	у		5	5	45	45											
- - 10 -				213.0 10.0				BOTTOM OF EXPLORAT	TION 10.0 FT											
D	pate	Wa	Flan	evel Dati	Dept	h (ft) Botton	to:	Sample ID O - Open End Rod T - Thin Wall Tube U - Undisturbed Sample S - Splitspoon Sample	Well Diagram ☐ Riser Pipe ☐ Screen ☐ Filter Sand ﴿*** Cuttings	Overt Rock Samp	Со	den ored	(ft	•	,	10.00				
								G - Geoprobe	Grout Concrete Bentonite Seal	Bori	ng	No				GF	P-0	7		
L.	d Tests			Toughn	<u>ess: L</u>	- Low		m H - High Dry Str	ity: N - Nonplastic L - Lov rength: N - None L - Low							Very	/ Hig	h		
_ [™] No	ote: Ma							oservation within the limitation sual-manual methods of th		y Hale	y &	Ald	Iricl	n, Ir	ıc.					

Н		PRIC	Н				GEO	PROBE REPORT	Г		E	3or	ring	g N	lo.		G	P-0	8	
Clie	oject ent ntracto	GR	ANB)	Y PUBLI Y PUBLI JBSURF	C SCI			FIELD AND TRACK, GRA	ANBY, CT	1	Sho Sta		No). 1 2	of 3 J	1 une	20 20			
			-	Casing	Sam	pler	Barrel	Drilling Equipment	t and Procedures			iish Iler		ے B. V			, 20	20		
Тур	е			-	G	}	-	Rig Make & Model: Geo	•	—		A F			C.	Cra	avir	ıho		
Insi	de Dia	meter ((in.)	-	1.	5	-	Bit Type: Geoprobe Spo Drill Mud: None	oon			evat itum) (e:)88			
		Veight	` '	-	AU ⁻	ТО	-	Casing: Push Hoist/Hammer: Winch	Automatic hammer		Lo	cati	on	S	ee l	Pla	n			
Har		Fall (in.	.)	-	-		-	PID Make & Model: Not			_				_					
Œ	Sampler Blows per 6 in.	Sample No. & Rec. (in.)	ē (≢	Stratum Change Elev/Depth (ft)	Symbol		VISU	JAL-MANUAL IDENTIFICATION	N AND DESCRIPTION	-		ivel	-	Sand				ield		
Depth (ft)	pler ser 6	mple Rec.	Sample Depth (ft)	Stratu Chan //Dep	SS			(Color, GROUP NAME, max structure, odor, moisture, option	onal descriptions	١,	Coarse	Fine	Coarse	Medium	Fine	Fines	Dilatancy	Toughness	Plasticity	Strength
	Sarr	Sa 8 F	۵ ۵	Ele	nscs			GEOLOGIC INTERPRI			%	∃ %	% (٧ %	% F	% F	Dile	길	Pla	Stre
- 0 -		G-1 36	0.0 5.0	222.5 0.5	SP	Tan	to light bro	-CRUSHED STO own poorly-graded SAND (SP)		,	4	5	5	55	30	5				
-	- GLACIOFLUVIAL DEPOSITS -																			
- - 5 - -		G-2 30	5.0 10.0	_), no structure, no odor, dry	,			5	45	50									
- 10 -				213.0 10.0				BOTTOM OF EXPLORAT	TION 10 0 FT		_							Ш		
D	Pate	Wa Time	Elap		Dept	h (ft) Bottom of Hole	to:	U - Undisturbed Sample S - Splitspoon Sample	Well Diagram ☐☐☐☐☐☐☐☐☐☐☐☐☐☐☐☐☐☐☐☐☐☐☐☐☐☐☐☐☐☐☐☐☐☐☐	Overbi Rock (Sampl	Coi	den red	(ft	•	,	10.0				
								G - Geoprobe	Grout - ^ Concrete	Borin).			GF	P-0	8		
Field	d Tests	i					S - Slow		Bentonite Seal ity: N - Nonplastic L - Low rength: N - None L - Low							\/er	, Hia			
† No	ote: Ma	aximum No	partic te: S	le size is	determ	nined b	y direct ol	m H - High Dry Str pservation within the limitation sual-manual methods of the	ns of sampler size.							v CI)	, , , , 119	<u>''</u>		

Н		Y	н				GEO	PROBE REPOR	Γ		ı	Bo	rin	g N	No.		GI	>-0	9	
Clie	oject ent ntracto	GR	ANBY	/ PUBLI / PUBLI BSURF	C SCI			FIELD AND TRACK, GRA	NBY, CT		Sh Sta	eet art	No). 1 2	of 23 J	une	202			
			(Casing	Sam	pler	Barrel	Drilling Equipment	and Procedures			nish iller			.o o Nils		202	23		
Han	de Dia nmer \	meter Weight Fall (in	(lb)	- - -	1. AU	5	- - -	Rig Make & Model: Geo Bit Type: Geoprobe Spo Drill Mud: None Casing: Push Hoist/Hammer: Winch PID Make & Model: Not	oon Automatic hammer		Ele	&A Feva eva etum ecati	tion)	22 N/					
(#)	Slows n.	No.		t e a tr	Symbol		VISU	JAL-MANUAL IDENTIFICATION				avel	_	San	d			eld g		
Depth (ft)	Sampler Blows per 6 in.	Sample No. & Rec. (in.)	Sample Depth (ft)	Stratum Change Elev/Depth (ft)	USCS Sy			(Color, GROUP NAME, max structure, odor, moisture, opti GEOLOGIC INTERPRE	onal descriptions		% Coarse	% Fine	% Coarse	% Medium	% Fine	% Fines	Dilatancy	Toughness	Plasticity	Strength
- 0 -		G-1 41	0.0 5.0	222.0 0.5	SM	Dark	brown sil	-CRUSHED STO ty SAND with gravel (SM), no			5	10	10	25	30	20				
-								- FILL -												
				220.0 2.5	SP	Tan	to light bro	own poorly-graded SAND (SP)	, no structure, no odor, d	ry		5	5	55	30	5				
								- GLACIOFLUVIAL DE	POSITS -											
_																				
- 5 -		G-2 33	5.0 10.0		SP	Tan	to light bro	own poorly-graded SAND (SP)	, no structure, no odor, d	ry		5	5	55	30	5				
-																				
=																				
-																				
-				040.5																
- 10 -				212.5 10.0				BOTTOM OF EXPLORAT	TION 10.0 FT											
						Note	: Explorat	ion backfilled upon completior	1.											
		\ \ \	.4					T - :	M-HD:				<u>_</u>							
<u> </u>	ate	Time	Elap	l D.	Dept	h (ft)		Sample ID O - Open End Rod	Well Diagram ☐☐ Riser Pipe ☐☐ Screen	Overl	our			<u>nma</u>)		10.0	—)			
Ľ.			Time		ottom Casing	Bottom of Hole	Water	U - Undisturbed Sample	Screen Filter Sand Cuttings	Rock	Со	red	•	()		0.0				
								S - Splitspoon Sample G - Geoprobe	Grout A Concrete	Samp Bori).	G	ı ∠	GF	- 06	9		
Field	d Tests	 s:		Dilatan	cy: R-	Rapid	S - Slow		Bentonite Seal ity: N - Nonplastic L - Lov rength: N - None L - Low	w M-N	1ediu	um	H -			Ven		<u> </u>		
† No	ote: Ma			e size is	determ	ined b	y direct ol	m H - High Dry Str bservation within the limitation isual-manual methods of th	ns of sampler size.							very				

Н		Y	н				GEO	PROBE REPOR	Г		E	Boı	rin	g N	lo.		GI	P-1	0	
Clie	oject ent ntracto	GR	ANBY	' PUBLI ' PUBLI BSURF.	C SCH			FIELD AND TRACK, GRA	ANBY, CT		Sh Sta		No	. 1 2	of 4 Ju	1 une	202			
				Casing	Sam	pler	Barrel	Drilling Equipment	t and Procedures			nish iller		ے B. V			202	20		
Han	de Dia nmer \	meter Weight Fall (in	(lb)	- - -	1.5 AU ⁻	5	- - -	Rig Make & Model: Geo Bit Type: Geoprobe Spo Drill Mud: None Casing: Push Hoist/Hammer: Winch PID Make & Model: Not	oon Automatic hammer		Ele	&A F evat etum cati	Rep tion า	-	C.	Cra 3.0 AVE				
Depth (ft)	Sampler Blows per 6 in.	Sample No. & Rec. (in.)	Sample Depth (ft)	Stratum Change Elev/Depth (ft)	USCS Symbol		VISL	JAL-MANUAL IDENTIFICATION (Color, GROUP NAME, max structure, odor, moisture, option GEOLOGIC INTERPRI	N AND DESCRIPTION c. particle size [†] , onal descriptions		% Coarse	% Fine	% Coarse	% Medium	Fine	% Fines		Longhness e		
- 0 - - -		G-1 41	0.0 5.0	222.9 0.1 222.5 0.5 222.0 1.0	SM SP			- TRACK RUBBER AND -CRUSHED STC rown silty SAND with gravel (\$ - FILL - own poorly-graded SAND (SP) - GLACIOFLUVIAL DE	ONE- SM), no structure, no odor,), no structure, no odor, dry		15	10 5			25 30					
- 5 - - -		G-2 55), no structure, no odor, dry	,		5	5	55	30	5										
- 10 -				213.0 10.0				BOTTOM OF EXPLORAT	FION 40 0 FT											
		W	stor La			Note	: Explorat	ion backfilled upon completion	n.											
			Flan	evel Data		h (ft)	to:	Sample ID O - Open End Rod	Well Diagram Riser Pipe	0.45	hu			ımaı \		10.0				_
	ate	Time	Time	(hr Bo	ottom	Botton of Hole	1 Water		Screen Filter Sand	Overl Rock			•	•		10.0 0.0				
								S - Splitspoon Sample G - Geoprobe	ণ্ডিপ্র Cuttings Grout	Samp Bori).	G	2		P-1()		
Fiel	d Tests	s:	<u>'</u>	Dilatano Toughn	cy: R- less: L	Rapid - Low	S - Slow M - Mediu		eity: N - Nonplastic L - Low rength: N - None L - Low							Very	Higl	1		
† No	ote: Ma			e size is	determ	ined b	y direct ol	oservation within the limitation is ual-manual methods of the	ns of sampler size.											

Н		Y	н				GEO	PROBE REPOR	Т		ı	Boı	rin	g N	lo.		GI	P-1	1	
Clie	oject ent ntracto	GR	ANBY	' PUBLI ' PUBLI BSURF	C SC			FIELD AND TRACK, GRA	ANBY, CT		Sh Sta	eet art	No		of 24 J	1 une	202			
			(Casing	Sam	pler	Barrel	Drilling Equipmen	t and Procedures		l .	nish iller		∠ B. \			: 202	23		
Han	de Dia nmer \	meter (Weight Fall (in.	(lb)		1.6 AU	5	- - -	Rig Make & Model: Geo Bit Type: Geoprobe Spo Drill Mud: None Casing: Push Hoist/Hammer: Winch PID Make & Model: Not	oon Automatic hammer		Ele Da	RA Fevaratum	Rep tion า	١.	C.	Cra 2.0 AVE	avin (es 088 n			
Depth (ft)	Sampler Blows per 6 in.	Sample No. & Rec. (in.)	Sample Depth (ft)	Stratum Change Elev/Depth (ft)	USCS Symbol		VISU	JAL-MANUAL IDENTIFICATIO (Color, GROUP NAME, may structure, odor, moisture, opti GEOLOGIC INTERPRI	N AND DESCRIPTION x. particle size [†] , ional descriptions		% Coarse	% Fine	% Coarse	% Medium	% Fine	% Fines		SS	Plasticity Les	
- -		G-1 40	0.0 5.0	221.9 0.1 221.5 0.5 221.0 1.0	SP- SM SP	struc	cture, no c	- TRACK RUBBER AND -CRUSHED STC rown poorly-graded SAND wit dor, dry - FILL - own poorly-graded SAND (SP)	DNE- th silt and gravel (SP-SM),	/	10	15 10		20 45						
- 5 -		G-2	EPOSITS -), no structure, no odor, dr			5	5	55												
-		50		•																
- 10 -																				
D	Water Level Data Water Level Data Sample ID Well Diagram Summary Date Time Elapsed Depth (ft) to: O - Open End Rod Overburden (ft) 10.0																			
			Time	` 101 C	Casing	of Hole	Water	U - Undisturbed Sample S - Splitspoon Sample G - Geoprobe	Filter Sand Grout Concrete Rentonite Seal	Rock Samp Bori	oles	;) <u>G</u>		0.0 GF	P-1	1		
Fiel	d Tests	└ 5 :		Dilatan	cy: R-	Rapid	S - Slow		Bentonite Seal city: N - Nonplastic L - Low rength: N - None L - Low							Ven	/ Hia	h		
† No	ote: Ma			e size is	determ	ined b	y direct o	bservation within the limitation isual-manual methods of the	ns of sampler size.							v CI Y	ring	1		<u> </u>

Н		Y	Н				GEO	PROBE REPOR	г			Во	rin	g N	No.		G	P-1	2	
Clie	ject ent ntracto	GF	RANB	/ PUBLI / PUBLI BSURF.	C SCF			FIELD AND TRACK, GRA	ANBY, CT		Sh St	neet art	No). 1 2		1 une	001 e 20 e 20			
			(Casing	Sam	pler	Barrel	Drilling Equipmen	t and Procedures			nish iller			.4 J Wils			23		
Тур	е			-	G	i	-	_	-			&A I				_	avir			
			` ′	-	1.5	5	-	Drill Mud: None	oon			eva atun		1	22 N	22.0 AVE) (e: 088	st.)		
	nmer I	all (in	` '	-	-	ГО	-	Hoist/Hammer: Winch			Lc	cat			ee	Pla	n			
Œ	3lows n.	No. (in.)	(ff)	E ge H	lodm		VISU	JAL-MANUAL IDENTIFICATIO	N AND DESCRIPTION			avel	_	San				ield s		
Depth (ft)	sampler E per 6 i	Sample & Rec.	Samp Depth	Stratul Chang Elev/Depl	JSCS Sy			structure, odor, moisture, opti	onal descriptions		% Coarse	% Fine	% Coarse	% Medium	% Fine	% Fines	Dilatancy	Toughness	Plasticity	Strength
- 0 -	0)	G-1	0.0	221.9														Ė		
-	structure no odor dry										15	20	15	25	15	10				
	220.0 structure, no odor, dry 2.0 SP - FILL -											5								
		220.0 2.0 SP - FILL -											5	55	30	5				
	G-1 45 5.0 221.9																			
- - 5 -	structure, no odor, dry - FILL - Tan to light brown poorly-graded SAND (SP), no structure, no odor, - GLACIOFLUVIAL DEPOSITS - SP Tan to light brown poorly-graded SAND (SP), no structure, no odor,											5	5	45	40	5				
-	De Ge Goprobe 7822DT Bit Type: Geoprobe Spoon Drill Mud: None Casing: Push Hoist/Hammer: Winch Automatic hammer PID Make & Model: Not used VISUAL-MANUAL IDENTIFICATION AND DESCRIPTION (Color, GROUP NAME, max. particle size†, structure, odor, moisture, optional descriptions GEOLOGIC INTERPRETATION) G-1 45 G-1 5.0 G-2 5.0 G-2 5.0 G-2 5.0 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, or optional control of the color																			
- - - 10 -				212.0																
	0 212.0 BOTTOM OF EXPLORATION 10.0 FT																			
	Note: Exploration backfilled upon completion.																			
	Water Level Data Sample ID Well Diagram Flansed Depth (ft) to: Open Find Red Riser Pipe													nma			_			_
D	ate	Time Elapsed Depth (ft) to: O - Open End Rod Time (hr.) Bottom Of Casing Bottom Of Hole Depth (ft) to: O - Open End Rod T - Thin Wall Tube U - Undisturbed Sample S - Solitspoon Sample Cuttings Riser Pipe Screen Filter Sand Cuttings C											(ft (ft	·)		10.0 0.0				
								G - Geoprobe	Grout Concrete	Samp Bori) .		_	GI	P-1	2		
Field	d Tests	:					S - Slow M - Mediu	N - None Plastic m H - High Dry Str	Bentonite Seal Sity: N - Nonplastic L - Low rength: N - None L - Low	M - N	1edi	um	Н-	High	า V -	Very	y Hig	Jh		

HA	LD)	RICH	1				GEO	PROBE REPOR	г		E	Зоі	rin	g N	lo.		GI	P-1	3	
Project Client Contra		GRA	ANBY	' PUBLI ' PUBLI BSURF	C SCI			FIELD AND TRACK, GRA	ANBY, CT	9	She Sta	eet art	No		of 4 J	1 une	202			
			(Casing	Sam	pler	Barrel	Drilling Equipment	t and Procedures			ish Iler		ے B. V			202	-0		
Туре				-	G	i	-	Rig Make & Model: Geo	-	ŀ	4&	A F	Rep	٠.	C.	Cra	avin	ho		
Inside	Diame	eter (i	in.)	-	1.4	5	-	Bit Type: Geoprobe Spo Drill Mud: None	oon			evat tum	tion า				(es 088	st.)		
Hamm	er We	eight ((lb)	-	AU ⁻	го	-	Casing: Push Hoist/Hammer: Winch	Automatia hammar	—			ion	S	ee l					
Hamm		ll (in.))	-	-		-	PID Make & Model: Not												
(ft)		. (.i.	æ€	n (ff)	Symbol		VISU	JAL-MANUAL IDENTIFICATION	N AND DESCRIPTION	-	\neg	vel	-	Sand	t			eld တ္က		t
Depth (ft) Sampler Blov	per 6 in.	& Rec. (in.)	Sample Depth (ft)	Stratum Change Elev/Depth (ft)	USCS Sy			(Color, GROUP NAME, max structure, odor, moisture, opti GEOLOGIC INTERPRI	onal descriptions	(% Coarse	% Fine	% Coarse	% Medium	% Fine	% Fines	Dilatancy	Toughness	Plasticity	Strength
0	- (G-1	0.0	222.5				- TRACK RUBBER AND			╛									
-		46	5.0	0.5 222.0 1.0	SP-	Gray	to gray-b	-CRUSHED STC rown poorly-graded SAND wit		0 1	5	20	15	25	15	10		-		
-					SM SP		cture, no o to light bro	dor, dry own poorly-graded SAND (SP)), no structure, no odor, dry			5	5	55	30	5				
-								-FILL-												
- 5 		G-2 38	5.0 10.0	218.0 5.0	SM			own silty SAND (SM), no struc k brown organic soil	sture, no odor, dry, frequent			5	5	50	20	20			_	
-								-FILL-												
_	SM Brown silty SAND (SM), no structure, no odor, moist													20	40	40				
10		G-3 42	10.0	10.0	SP	Tan	to light bro	own poorly-graded SAND (SP)), no structure, no odor, moi	st		5	5	40	30	20				
-		42	15.0					-GLACIOFLUVIAL DE	POSITS-											
-				210.0 13.0	SM	Brov	vn silty SA	ND (SM), no structure, no odo		+	- 🕂			20	40	40	-+	-+	-+	
				209.0 14.0	SP-		to light hr	own poorly-graded SAND (SP	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \		5		40	30	30		_	-4	_	
- 15					35	Tall	to light bit	1 30	,	51	,	5	40	30	20					
				208.0 15.0				BOTTOM OF EXPLORAT	ΓΙΟΝ 15.0 FT											
						Note	: Explorat	ion backfilled upon completior	n.											
\vdash		Wat	ter Le	vel Data	 a_			Sample ID	Well Diagram		_		<u> </u>	ma	ry					_
Date	-	Time	Elap Time	(hr Bo	ttom	h (ft) Bottom of Hole	1 Water	O - Open End Rod T - Thin Wall Tube U - Undisturbed Sample	Riser Pipe Screen Filter Sand	Overbu Rock (Coi	len	(ft)	,	15.0 0.0				
								S - Splitspoon Sample G - Geoprobe	Grout	Sample		<u> </u>		G	3	Ci	P-1;	2		
Field To	ests:						S - Slow	N - None Plastic	Bentonite Seal		diu	ım	H -							
† Note:	Maxi			e size is	determ	ined b	y direct ol	m H - High Dry Stu pservation within the limitation sual-manual methods of the								very	rig	1		_

Н	XLE	Y	Н				GEO	PROBE REPOR	т		ı	Во	rin	g N	No.	1	G	P-1	4	
Clie		GF	RANB	Y PUBLI	C SCI			FIELD AND TRACK, GRA	ANBY, CT		Sh Sta	eet art	No). 1 2	of 24 J	une	e 20			
				Casing	Sam	pler	Barrel	Drilling Equipmen	t and Procedures									20		
Тур	е			-	G	;	-	_	-						C.	Cr	avir	ıho		
Insid	de Dia	meter	(in.)	-	1.5	5	-	Drill Mud: None	oon					1						
		•	` '	-	AU	ТО	-	Casing: Push Hoist/Hammer: Winch	Automatic hammer	Ī	Lo	cat	ion	S	ee	Pla	n			
Han		,	.)	-	-			1			_									
Œ	Blows in.	No. (in.)	æ Œ	H (ft)	lodm		VISL	JAL-MANUAL IDENTIFICATIO	N AND DESCRIPTION	t t		avel	_					SS		
əpth	pler E er 6 i	nple ?ec.	amp	tratu hang/ Depi	S Sy						oars	ine	oars	lediu	ine	ines	tancy	ghne	sticity	ngth
	Sam	Sar & F	S	S	nsc						%	% F	0 %	№ №	% F	% F	Dila	Tou	Plas	Stre
- 0 -		G-1	0.0	223.9							15	20	45	0.5	45	40				
-		43	5.0	0.5	52	1					15	20	15	25	15	10				
-	G-1 43 5.0 223.5 0.5 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 5 5 55 30 5																			
	G-1 0.0 223.9 - TRACK RUBBER AND ASPHALT CRUSHED STONE- 15 20 15 25 15 10 SP Service of the structure of																			
	VISUAL-MANUAL IDENTIFICATION AND DESCRIPTION COLOR, GROUP NAME, max. particle size ¹ , structure, odor, moisture, optional descriptions GEOLOGIC INTERPRETATION) Garage Sand Sand Sand Sand Sand Sand Sand Sand																			
-), no structure, no odor, dr	у		5	5	55	30	5								
- 5 -		G-2	5.0	+), no structure, no odor, m	oist		5	5	50	35	5								
-		40			EPOSITS -															
	Prope File File																			
-				8.0			 	Ė:												
-				8.5), no structure, no odor, m	oist		5	5	50	35	5								
- 10 -				214.0	FIONI 40 0 FT									Ш						
				10.0																
	4.0 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, moist - GLACIOFLUVIAL DEPOSITS - 216.0 215.5 8.5 SP Tan to light brown poorly-graded SAND (SM), no structure, no odor, moist SM Brown silty SAND (SM), no structure, no odor, moist SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, moist 220 40 40 DEPOSITS - 230 40 40 240 40 DEPOSITS - SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, moist SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, moist SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, moist																			
	220.0 4.0 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 5 55 30 5 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, moist 5 5 50 35 5 - GLACIOFLUVIAL DEPOSITS - SM Brown silty SAND (SM), no structure, no odor, moist 215.5 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, moist 5 5 5 50 35 5 Tan to light brown poorly-graded SAND (SP), no structure, no odor, moist 5 5 5 50 35 5 BOTTOM OF EXPLORATION 10.0 FT																			
	4.0 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, moist - GLACIOFLUVIAL DEPOSITS - SM Brown silty SAND (SM), no structure, no odor, moist 216.0 8.0 215.5 8.5 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, moist 5 5 5 50 35 5 214.0 10.0 BOTTOM OF EXPLORATION 10.0 FT																			
				<u> </u>					1		_					<u>_</u>				
<u> </u>			Пол	evel Data osed	a Dept	h (ft)	to:	Sample ID O - Open End Rod	Well Diagram Riser Pipe	Overh				nma N		10 (
L^{D}	ate	Time	Time	hr Bo	ottom	Botton of Hole	n Water	T - Thin Wall Tube	Screen Filter Sand	Overb Rock			•	•		10.0 0.0				
								U - Undisturbed Sample S - Splitspoon Sample	Cuttings Grout	Samp			`		2					
								G - Geoprobe	Concrete Bentonite Seal	Bori	ng	No	ο.			GF	P-1	4		
Field	d Tests	:					S - Slow M - Mediu	N - None	city: N - Nonplastic L - Low rength: N - None L - Low	v M - M M - Med	edii liun	um n H	H - I - H	High igh	า V -	Ver	y Hig	 Jh		

Н		Y	н				GEO	PROBE REPOR	Т		l	Boı	rin	g N	No.		GI	P-1	5	
Clie	oject ent ntracto	GR	ANBY	' PUBLI ' PUBLI BSURF.	C SCI			FIELD AND TRACK, GRA	ANBY, CT		Sh Sta	e Noneet	No). 1 2	of 24 J	1 une	202			
			(Casing	Sam	pler	Barrel	Drilling Equipmen	t and Procedures			nish iller			Vils		: 202	25		
Han	de Dia nmer \	meter (Weight Fall (in.	(lb)	- - -	1. AU	5	- - -	Rig Make & Model: Geo Bit Type: Geoprobe Spo Drill Mud: None Casing: Push Hoist/Hammer: Winch PID Make & Model: Not	oon Automatic hammer		Ele	&A F evat atum ocati	tion	l	22	4.0 \VE	avin (es 088 n			
Depth (ft)	Sampler Blows per 6 in.	Sample No. & Rec. (in.)	Sample Depth (ft)	Stratum Change Elev/Depth (ft)	USCS Symbol		VISU	JAL-MANUAL IDENTIFICATION (Color, GROUP NAME, may structure, odor, moisture, opti GEOLOGIC INTERPRI	N AND DESCRIPTION x. particle size [†] , onal descriptions		% Coarse	% Fine	% Coarse	% Medium	% Fine	% Fines		Longhness e		Strength #
- 0 - - -		G-1 44	0.0 5.0	223.9 0.1 223.5 0.5	SP- SM			- TRACK RUBBER AND -CRUSHED STO red-brown poorly-graded SAN to odor, dry	NE-	SM),	15	20	15	25	15	10				
-	5 G-2 5.0 39 10.0 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 10 80 5																			
- 5 - -	4.0 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry G-2 5.0 39 10.0 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 10 80 5																			
-	39 10.0 - GLACIOFLUVIAL DEPOSITS - 214.0 10.0 BOTTOM OF EXPLORATION 10.0 FT																			
- 10 -	10 214.0 BOTTOM OF EXPLORATION 10.0 FT Note: Exploration backfilled upon completion.																			
		Wa	ater Le	evel Dat	a	Note	: Explorat	ion backfilled upon completion	n. Well Diagram			S	Sum	nma	ıry					
П	ate	Time	Elap	sed	Dept	h (ft) i		O - Open End Rod	Riser Pipe	Overb	our					10.0)			_
Ľ	alo	11116	Time		ottom Casing	Bottom of Hole	Water	T - Thin Wall Tube U - Undisturbed Sample	Filter Sand	Rock	Со	red	•	()		0.0				
								S - Splitspoon Sample G - Geoprobe	Bentonite Seal	Samp Bori ı	ng	No		G		GF	P-1	5		
L	d Tests			Toughn	iess: L	- Low		m H - High Dry St	:ity : N - Nonplastic L - Low rength : N - None L - Low							Very	/ Hig	h		
_ [™] No	ote: Ma							bservation within the limitation is ual-manual methods of the		/ Haley	y &	Ald	lric	h, Ir	nc.					

Н		Y	Н				GEO	PROBE REPORT	Γ		l	Воі	rin	g N	No.		GI	P-1	6	
Clie	ject ent ntracto	GR	RANBY	′ PUBLI ′ PUBLI BSURF.	C SCH			FIELD AND TRACK, GRA	NBY, CT		Sh Sta	e No leet art	No	· 1	of 24 J	1 une	202			
			(Casing	Sam	pler	Barrel	Drilling Equipment	and Procedures			nish iller			ع ا Vils		202	25		
Han	de Dia nmer \	meter Weight Fall (in	(lb)	- - -	1.5 AU ⁻	5	- - -	Rig Make & Model: George Bit Type: Geoprobe Spor Drill Mud: None Casing: Push Hoist/Hammer: Winch / PID Make & Model: Not	oon Automatic hammer		Ele	RA F evat etum cati	tion		22	3.5 VE	avin (es)88 n			
Depth (ft)	Sampler Blows per 6 in.	Sample No. & Rec. (in.)	Sample Depth (ft)	Stratum Change Elev/Depth (ft)	USCS Symbol		VISL	JAL-MANUAL IDENTIFICATION (Color, GROUP NAME, max structure, odor, moisture, option GEOLOGIC INTERPRE	N AND DESCRIPTION a. particle size [†] , conal descriptions		% Coarse	% Fine	% Coarse	% Medium	% Fine	% Fines		SS	Plasticity	Strength
- 0 - - -		G-1 43	0.0 5.0	223.4 0.1 223.0 0.5	SP- SM	,		- TRACK RUBBER AND -CRUSHED STO red-brown poorly-graded SAN o odor, dry	NE-	SM),	15	20	15	25	15	10				
=				219.5				- FILL -												
- - 5 -		G-2 42	5.0 10.0	4.0	SP SP		Ū	own poorly-graded SAND (SP)				5	5		30 40					
- -			POSITS -																	
- 10 - - - -																				
- 15 -				208.5 15.0				BOTTOM OF EXPLORAT	TION 15.0 FT										+	
						Note	: Explorat	ion backfilled upon completior												
			Flan	evel Data		h (ft) 1	:0:	Sample ID	Well Diagram Riser Pipe	0:::-:				ıma \						_
	ate	Time	Time	(hr Bo	ottom	Bottom of Hole	Water	O - Open End Rod T - Thin Wall Tube U - Undisturbed Sample	Screen Filter Sand	Overb Rock			•	•		15.0 0.0				
								S - Splitspoon Sample G - Geoprobe	Grout Concrete Reptopite Seal	Samp Bori ı) .	G	3	GF	P-1(6		
Field	d Tests	: ::		Dilatan	cy: R-	Rapid	S - Slow M - Mediu		Bentonite Seal ity: N - Nonplastic L - Low rength: N - None L - Low							Ven	, Hia			
† No	ote: Ma			e size is	determ	ined b	direct ol	oservation within the limitation sual-manual methods of the	ns of sampler size.							v GI Y	i iigi	-		

Н		PRIC	н				GEO	PROBE REPOR	Г		Вс	rir	ıg I	No.	i	GI	P-1	7	
Clie	oject ent ntracto	GR	'ANB	Y PUBLI Y PUBLI JBSURF	C SCI			FIELD AND TRACK, GRA	ANBY, CT	5	ile N Shee Start	t No	o. 1	of 24 J	1 une	001 = 202 = 202			
				Casing	Sam	pler	Barrel	Drilling Equipmen	t and Procedures		inis Irille			Wils					
Тур	е			-	(3	-	Rig Make & Model: Geo		F	l&A	Re	ο.	C.	. Cr	avin	ho		
Insid	de Dia	meter	(in.)	-	1.	.5	-	Bit Type: Geoprobe Spo Drill Mud: None	oon		Eleva Datu		n			5 (es 088	st.)		
Han	nmer \	Weight	(lb)	-	AU	ТО	-	Casing: Push Hoist/Hammer: Winch	Automatic hammer	-	oca		5	See					
Han		Fall (in	.)	-	_		-	PID Make & Model: Not											
Œ	Sampler Blows per 6 in.	Sample No. & Rec. (in.)	<u>ə</u> €	Stratum Change Elev/Depth (ft)	Symbol		VISU	JAL-MANUAL IDENTIFICATIO	N AND DESCRIPTION	-	irave	+-	Sar				ield g		
Depth (ft)	pler E er 6 i	nple Rec.	Sample Depth (ft)	tratul thang Dept	S Sy			(Color, GROUP NAME, max structure, odor, moisture, opti		2	Fine	Coarse	Medium	Fine	Fines	Dilatancy	Toughness	Plasticity	Strength
	Sam	Sar & F	တ္ထ	S	nscs			GEOLOGIC INTERPR		0 %	8 8 8	8	N %	% F	% F	Dila	Tou	Plas	Stre
- 0 -		G-1 40	0.0	223.4 0.1 223.0	SP-			- TRACK RUBBER AND -CRUSHED STO			5 20	145	25	15	10				_
-		40	5.0	0.5	SM-			red-brown poorly-graded SAN		—	5 20	וים ויכ	25	15	10				
-	no structure, no odor, dry - FILL -																		
	-																		
	219.5 4.0 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 5 55 30 5																		
-	4.0 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 5 55 30 5																		
- 5 -	4.0 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 5 55 30 5																		
_	4.0 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 5 5 50 40 5																		
	5 G-2 5.0 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 50 40 5																		
	5 G-2 5.0 35 10.0 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 50 40 5																		
-	5 G-2 5.0 35 10.0 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 5 55 30 5 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 5 50 40 5 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 5 50 40 5 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 5 50 40 5 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 5 50 40 5 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 5 50 40 5 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 5 50 40 5 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 5 50 40 5 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 5 50 40 5 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 5 50 40 5 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 5 50 40 5 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 5 50 40 5 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 5 50 40 5 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 5 50 40 5 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 5 50 40 5 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 5 50 40 5 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 5 50 40 5 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 5 50 40 5 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 5 50 40 5 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 5 50 40 5 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 5 50 40 5 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 5 50 40 5 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 5 50 40 5 SP Tan to light brown poorly-graded SAND (SP), no																		
-	10 213.5 10.0 BOTTOM OF EXPLORATION 10.0 FT																		
- 10 -	10 213.5 10.0 BOTTOM OF EXPLORATION 10.0 FT																		
"	213.5 BOTTOM OF EXPLORATION 10.0 FT Note: Exploration backfilled upon completion.																		
						Note	e: Explorat	ion backfilled upon completion	1.										
											\perp					Ш			
		Wa		evel Dat		th /#\	to	Sample ID	Well Diagram Riser Pipe			Sur		ary					_
D	ate	Time			ottom	th (ft) Bottor	n Water	O - Open End Rod T - Thin Wall Tube	Screen	verbu		•	•		10.0				
				<u>` 10f C</u>	Casing	of Hol	ea.or	U - Undisturbed Sample S - Splitspoon Sample	Cuttings S	lock C ample		u (I	,	32	0.0	1			
								G - Geoprobe	Grout	orin		Ο.			GI	P-17	7		
Field	d Tests	<u> </u>		Dilatan	cv: R-	Rapid	S - Slow	N - None Plastic	Bentonite Seal				· Hia	h					
			partic	Toughr	<u>iéss: L</u>	<u> - Low</u>	M - Mediu		rength: N - None L - Low M						Very	/ Higl	h		_
		No	te: S	Soil iden	tificati	ion ba	sed on vi	sual-manual methods of the	ne USCS as practiced by I	laley	& Al	dric	h, I	nc.					

Н		PRIC	Н				GEO	PROBE REPOR	т		В	ori	ing	g N	lo.		GI	P-1	8	
Clie	oject ent ntracto	GR	'ANB	Y PUBLI Y PUBLI JBSURF	C SCI			FIELD AND TRACK, GRA	ANBY, CT	9	She Star	et l t		. 1 2		1 une	202			
				Casing	Sam	pler	Barrel	Drilling Equipmen	t and Procedures		Finis Drill		E		√ ils		202			
Тур	е			-	G	3	-	Rig Make & Model: Geo		H	H& <i>F</i>	۱R	ер.		C.	Cra	avin	ho		
Insid	de Dia	meter ((in.)	-	1.	.5	-	Bit Type: Geoprobe Spo Drill Mud: None	oon		Ele\ Datı					2.0 AVD	(es	st.)		
		Veight	` '	-	AU	то	-	Casing: Push Hoist/Hammer: Winch	Automatic hammer	-	Loc			S	ee F					
Har		Fall (in.	.)	-	-	.	-	PID Make & Model: Not												
Œ	Sampler Blows per 6 in.	Sample No. & Rec. (in.)	<u>a</u> €	Stratum Change Elev/Depth (ft)	Symbol		VISU	JAL-MANUAL IDENTIFICATIO	N AND DESCRIPTION	+	Grav Φ	_	_	Sand E		, }		ield S		
Depth (ft)	pler per 6	mple Rec.	Sample Depth (ft)	Stratu Chang	SS SS			(Color, GROUP NAME, max structure, odor, moisture, opti			Coarse	Line	Coarse	Medium	Fine	Fines	Dilatancy	Toughness	Plasticity	Strength
	Sam	Sar & F	ഗ്ര്	lo o e	nscs			GEOLOGIC INTERPR		;	S 2	S :	%	% №	₩ F	₩ ₽	Dila	린	Plas	Stre
- 0 -		G-1 40	0.0 5.0	221.9	SP-			- TRACK RUBBER AND -CRUSHED STO			15 1	20 -	15	25	15	10				
-		40	5.0	0.1 221.5 0.5	SM		,	red-brown poorly-graded SAN			3 2		13	23	13	10				
-	no structure, no odor, dry - FILL -																			
	218.0 4.0 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 5 55 30 5																			
-	4.0 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 5 5 30 5																			
- 5 -	4.0 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 5 5 30 5 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 30 60 5																			
-	4.0 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 SO																			
	5 G-2 5.0 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 30 60 5																			
	5 G-2 5.0 4.0 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 5 55 30 5 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 30 60 5 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 30 60 5 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 30 60 5 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 30 60 5 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 30 60 5 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 30 60 5 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 30 60 5 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 30 60 5 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 30 60 5 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 30 60 5 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 30 60 5 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 30 60 5 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 30 60 5 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 30 60 5 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 30 60 5 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 30 60 5 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 30 60 5 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 30 60 5 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 80 60 5 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 80 60 60 5 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 80 60 60 5 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 80 60 60 5 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 6 80 60 60 60 6																			
-	5 G-2 5.0 4.0 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 5 5 55 30 5 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 30 60 5 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 30 60 5 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 30 60 5 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 30 60 5 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 30 60 5 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 30 60 5 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 30 60 5 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 30 60 5 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 30 60 5 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 30 60 5 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 30 60 5 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 30 60 5 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 30 60 5 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 30 60 5 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 30 60 5 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 30 60 5 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 30 60 5 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 30 60 5 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 30 60 5 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 30 60 5 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 80 60 60 5 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 80 60 60 5 SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry 5 80 60 60 5 SP																			
-	10 212.0 10.0 BOTTOM OF EXPLORATION 10.0 FT																			
- 10 -	10 212.0 BOTTOM OF EXPLORATION 10.0 FT																			
	212.0 BOTTOM OF EXPLORATION 10.0 FT Note: Exploration backfilled upon completion.																			
						NOLE	e: Explorat	ion backililed upon completion	n.											ĺ
																				ĺ
																				ĺ
		\//ء	ater I	evel Dat	<u></u> а			Sample ID	Well Diagram	<u></u>	_	<u> </u>	ım	ma	rv	_	\perp			
_	ate	Time	Ela	psed	Dept	th (ft)		O - Open End Rod	Riser Pipe	Overbu						10.0	——)			_
	-ui6	111110	Time		ottom Casing	Botton of Hole		T - Thin Wall Tube U - Undisturbed Sample	Filter Sand F	Rock (٠,			0.0				
								S - Splitspoon Sample G - Geoprobe	Grout	Sampl				G						
L								G - Geoplone	Concrete Bentonite Seal	Borin	g N	No.				GF	P-18	В		
Field	d Tests): 					S - Slow M - Mediu		city: N - Nonplastic L - Low rength: N - None L - Low M							√ery	/ Higl	h		
† No	ote: Ma	aximum No	partic	le size is	detern	nined b	y direct ol	oservation within the limitation sual-manual methods of the	ns of sampler size. ne USCS as practiced by	Haley	& <i>P</i>	ldr	ich	ı, İn	IC.	_				_

Н		Y	Н				GEO	PROBE REPOR	Т		ı	Во	rin	g N	No.	ı	G	P-1	9	
Clie	ject ent ntracto	GF	RANB	Y PUBLI Y PUBLI JBSURF	C SC			FIELD AND TRACK, GRA	ANBY, CT		Sh Sta	neet art	No		of 24 J	1 une	20			
				Casing	Sam	pler	Barrel	Drilling Equipmen	t and Procedures			nish iller		ے B. \			20	25		
Тур	e			-		3	-	Rig Make & Model: Geo	probe 7822DT		Нξ	&A I					avir	nho		
Insid	de Dia	meter	(in.)	_	1.	.5	_		oon			eva		1			(e			
Han	nmer \	Veight	(lb)	-	AU	то	-	Casing: Push		_		atun ocat		S	ee		088 n			
Har		-all (in	ı.)	-	-		-													
æ	swo .		(n.∓	, €	loqu		VISI	•				avel	_	San	d		F		Tes	st
Depth (ft)	er Bl	ole N	mple th (f	atum ange	Sym			(Color, GROUP NAME, max	x. particle size [†] ,		Coarse	a o	Coarse	Medium	a o	es	ncy	Toughness	ξ	돭
Dep	per	am Re	Sai	Str. Str.	SCS			structure, odor, moisture, opti	onal descriptions		Š	Fine	Š	Me	% Fine	Fines	Dilatancy	ough	Plasticity	Strength
- 0 -	Š				Ď				<u> </u>		%	%	%	%	%	%	Ω	F	<u>_</u>	S
		G-1 46	0.0 5.0	0.1	SP-	$\langle - \rangle$				/ /	15	20	15	25	15	10			\vdash	
-				0.5	SM				ND with silt and gravel (SP	-SM),	l l									
-						no st	ructure, r	no odor, dry - FILL -			l l									
											l									ĺ
-											l									ĺ
-		G-1 0.0 222.9 - TRACK RUBBER AND ASPHALT - 46 5.0 222.5 SP - CRUSHED STONE- 0.5 SM Gray-brown to red-brown poorly-graded SAND with silt and gravel (SP-S) no structure, no odor, dry											5	55	30	5				<u> </u>
٦		PID Make & Model: Not used VISUAL-MANUAL IDENTIFICATION AND DESCRIPTION (Color, GROUP NAME, max. particle size†, structure, odor, moisture, optional descriptions GEOLOGIC INTERPRETATION) Fig. 1																		ĺ
- 5 -		Per Fall (in.) The Fall (in.)											5	50	40	5				ĺ
-		T Fall (in.) T																		
		iameter (in.) r Weight (lb) r Fall (in.) - 1.5 - Drill Mud: None Casing: Push Hoist/Hammer: Winch Automatic hammer PID Make & Model: Not used VISUAL-MANUAL IDENTIFICATION AND DESCRIPTION (Color, GROUP NAME, max. particle size ¹ , structure, odor, moisture, optional descriptions GEOLOGIC INTERPRETATION) G-1 46 - 1.0.0 - TRACK RUBBER AND ASPHALT - CRUSHED STONE- Gray-brown to red-brown poorly-graded SAND with silt and gravel (SP no structure, no odor, dry - FILL - SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry - GLACIOFLUVIAL DEPOSITS - Bit Type: Geoprobe Spoon Drill Mud: None Casing: Push Hoist/Hammer: Winch Automatic hammer PID Make & Model: Not used VISUAL-MANUAL IDENTIFICATION AND DESCRIPTION (Color, GROUP NAME, max. particle size ¹ , structure, odor, moisture, optional descriptions GEOLOGIC INTERPRETATION) - TRACK RUBBER AND ASPHALT CRUSHED STONE- Gray-brown to red-brown poorly-graded SAND with silt and gravel (SP no structure, no odor, dry - FILL - SP Tan to light brown poorly-graded SAND (SP), no structure, no odor, dry - GLACIOFLUVIAL DEPOSITS - BOTTOM OF EXPLORATION 10.0 FT																		ĺ
				l									ĺ							
-											l									
											l									
											l									
- 10 -				213.0 10.0				BOTTOM OF EXPLORA	TION 10.0 FT										$\mid \cdot \mid$	
											l									ĺ
											l									
											l									ĺ
											l									ĺ
											l									ĺ
											l									ĺ
											l l									
											l									ĺ
											l l									
											l									ĺ
											l									ĺ
											l l									ĺ
		W	ater L	evel Dat	a a	1		Sample ID	Well Diagram			<u></u>	Sum	ıma	ırv		<u> </u>			_
	ate	Time	Fla	psed	Dept	th (ft)		O - Open End Rod	Riser Pipe	Overb	our,					10.0)			
Ľ	ui6	111116	Tim		ottom Casing	Bottom of Hole		T - Thin Wall Tube U - Undisturbed Sample	Screen Filter Sand	Rock			-			0.0				
								S - Splitspoon Sample	Cuttings Grout	Samp				G						
								G - Geoprobe	Concrete	Boriı	ng	No	ο.			GI	P-1	9		
Field	d Tests	<u>. </u>		Dilatan	cv·R-	Rapid	S - Slow	N - None Plastic	Bentonite Seal Sity: N - Nonplastic L - Low					Hiał	า					
-iei	นาษรเร	••		Toughr	iess: L	Low	M - Mediu		rength: N - None L - Low							Ver	/ Hio	h		

Н		PRIC	Н			GEO	OPROBE REPOR	т		l	Boı	rinç	g N	No.		G	P-2	20	_
Pro Clie Cor	•	GR	ANB	/ PUBLI / PUBLI BSURF	C SCF		RF FIELD AND TRACK, GR	ANBY, CT		Sh Sta	eet art	No	. 1 2		1 une	20:			
			(Casing	Sam	pler Barre	Drilling Equipmer	nt and Procedures			nish iller			vils Nils		202	25		
Тур	е			-	G	i -	Rig Make & Model: Geo	•		Н8	&A F	? ер				bins	son		
Insid	de Dia	meter	(in.)	-	1.5	5 -	Bit Type: Geoprobe Sp Drill Mud: None	ooon			evat atum	tion				(e:	st.)		
	nmer F	Veight all (in	` '	-	AU1	го -	Casing: Push Hoist/Hammer: Winch PID Make & Model: No			_	cati		S	ee l					-
(ft)	lows 1.	No.	æ (±	n e h (ft)	Symbol	VIS	SUAL-MANUAL IDENTIFICATIO	ON AND DESCRIPTION		 	avel		Sand	d			ield g	Те	s
Depth (Sampler Blows per 6 in.	Sample No. & Rec. (in.)	Sample Depth (ft)	Stratum Change Elev/Depth (ft)	USCS Syl		(Color, GROUP NAME, ma structure, odor, moisture, opt GEOLOGIC INTERPR	tional descriptions		% Coarse	% Fine	% Coarse	% Medium	% Fine	% Fines	Dilatancy	Toughness	Plasticity	
0 -	Р	G1	0.0	221.7 0.3	SP-	Dank may to	-TRACK RUBBER AND		CM	10	20	20	20	20	10				Ī
	U S H		5.0		SM SP	no structure,	0 , 1 , 0	• • • • • • • • • • • • • • • • • • • •	-SIVI),	10	15	25	20	30					
							- FILL -												
5 -																			
5 -	P U	G2	5.0 10.0																
	S H																		
10 -	P	G3	10.0																
	U S		15.0																
	Н			210.0 12.0	SM		silty SAND with gravel (SM), no	-			-	-+	25	60	15				H
				209.0 13.0	SP	Red-brown to	regular dark brown sandy SILT o tan poorly-graded SAND (SP	. , ,	ace	0	0	10	40	50					l
						clayey sand													
15 –	Р	G4	15.0	_			- GLACIOFLUVIAL D	EPOSITS -											
	U S	U 20.0 S 20.0																	
	Н			205.0 17.0		Tan silty SAI	ND (SM), no structure, no odor					_		70	30				_
								,											
20 -				202.0			BOTTOM OF EXPLORA	TION 20.0 FT											
						Note: Explor	ation backfilled upon completic												
		Wa	ater Le	⊥ evel Data	<u></u> а		Sample ID	Well Diagram			S	um	ma	ry	_			<u> </u>	_
D	ate	Time		sed	Deptl	h (ft) to:	O - Open End Rod	Riser Pipe Screen	Over		den	(ft))		20.0)		_	
			IIIIE			of Hole Wate	U - Undisturbed Sample	Filter Sand	Rock Sami			(ft)) G		0.0				
							S - Splitspoon Sample G - Geoprobe	Grout Concrete Bentonite Seal	Bori).	G		GF	P-2 (0		_
	d Tests		1	Dilatano	v R-	Rapid S - Slow	/ N - None Plasti	city: N - Nonplastic L - Lo	w M-N	/ledii	ım	H - I	Hiah						-

Н		Y	н				GEO	PROBE REPOR	Γ		ı	Boı	rin	g N	lo.		G	P-2	 !1	
Clie	oject ent ntracto	GR	RANBY	′ PUBLI ′ PUBLI BSURF	C SCF			FIELD AND TRACK, GRA	INBY, CT		Sh Sta	eet art	No		of 25 J	1 une	20:			
			(Casing	Sam	oler	Barrel	Drilling Equipment	and Procedures			nish iller		ے B. V			: 20.	23		
Han	de Dia nmer \	meter Weight Fall (in	(lb)	- - -	G 1.5 AUT	5	- - -	Rig Make & Model: Geo Bit Type: Geoprobe Spo Drill Mud: None Casing: Push Hoist/Hammer: Winch PID Make & Model: Not	oon Automatic hammer		Ele	eva atun	Rep tion 1 ion		22	2.0 AVE	bins (e: 088 n			
Depth (ft)	Sampler Blows per 6 in.	Sample No. & Rec. (in.)	Sample Depth (ft)	Stratum Change Elev/Depth (ft)	USCS Symbol		VISL	JAL-MANUAL IDENTIFICATION (Color, GROUP NAME, may structure, odor, moisture, option GEOLOGIC INTERPRI	N AND DESCRIPTION c. particle size [†] , onal descriptions		% Coarse	% Fine	% Coarse	% Medium	% Fine	% Fines		SS	Plasticity al	
- 0 - - -	P U S H	G1	0.0 5.0	221.6 0.4 221.2 0.8	SP- SM/ SP	no st	ructure, n	-TRACK RUBBER AND ray-brown poorly-graded SANI o odor - FILL -	ASPHALT- D with silt and gravel (SP-	-SM),			20	20 25	20	10		-		S
- 5 -	Red-brown to tan poorly-graded SAND (SP), bedded, no odor, dry - GLACIOFLUVIAL DEPOSITS - P G2 5.0 U S H 212.0 10.0 BOTTOM OF EXPLORATION 10.0 FT Note: Exploration backfilled upon completion.																			
- 10				10.0		Note	: Explorat													
D	ate	Time	Flan	(hr Bo	Depti	n (ft) t Bottom of Hole	Water	Sample ID O - Open End Rod T - Thin Wall Tube U - Undisturbed Sample S - Splitspoon Sample G - Geoprobe	Well Diagram Riser Pipe Screen Filter Sand Cuttings Grout Concrete Bentonite Seal	Overl Rock Samp	Co	den red	(ft	•	,	10.0 0.0		1		
L.	d Tests ote: Ma	aximum		Toughn e size is	ess: L determ	- Low ined by	y direct ol		ity: N - Nonplastic L - Lov rength: N - None L - Low ns of sampler size.	M - Me	diun	1 H	- Hi	gh	V - '	Very	/ Hig	h		

Н		Y	Н				GEO	PROBE REPOR	т		Вс	rir	ng I	No.	i	G	P-2	22	
Clie	ject ent ntracto	GF	RANB	Y PUBLI Y PUBLI IBSURF	C SCI			FIELD AND TRACK, GRA	ANBY, CT	St St	nee art	t N		of 25 J	1 lune	001 = 20 = 20			
				Casing	Sam	pler	Barrel	Drilling Equipmen	t and Procedures		nisl ille			Wils			20		
Тур	е			-	G	;	-	Rig Make & Model: Geo		Н	&A	Re	p.	E.	Ro	bin	son		
Insid	de Dia	meter	(in.)	_	1.	5	_	Bit Type: Geoprobe Spo Drill Mud: None	oon			atio	n) (e			
Han	nmer \	Veight	(lb)	-	AU ⁻	то	-	Casing: Push			atui oca	tior	n S	iv. See		D88 n			
Han	nmer I	all (in	ı.)	-	-		-	Hoist/Hammer: Winch PID Make & Model: Not											
æ	swo .	٦. ا.)	æ£	€	lodi		VISU	JAL-MANUAL IDENTIFICATION		-	ave	+-	San			F	ield		st
Depth (ft)	er Bl	ple N	mple oth (f	atum ange Septh	Symbol			(Color, GROUP NAME, max		Coarse	l o	Coarse	Medium	Ф	es	ncy	Toughness	city	gt
Dep	ampl	amı k Re	Sal Dep	Str Ch	scs			structure, odor, moisture, opti GEOLOGIC INTERPRI	onal descriptions ETATION)	Ö	Ë	Ö	We We	% Fine	% Fines	Dilatancy	ough	Plasticity	Strength
- 0 -									·	8	%	8	%	%	8		\vdash	<u>а</u>	S
	Ü	G1	0.0 5.0	0.4	SP-	Dark	k gray to g			M), 10	20	20	20	20	10	Н			
	S				SM				hedded no odor dry			25	5 20	55					
-						Itteu	-biowii to	. , ,	, bedded, 110 odor, dry										
- FILL -																			
	P G1 0.0 221.6 5.0 SP-SM SM SP Dark gray to gray-brown poorly-graded SAND with silt and gravel (SP-SM), no structure, no odor Red-brown to tan poorly-graded SAND (SP), bedded, no odor, dry - FILL -																		
_																			
- 5 -	_			217.0	L		4-	Ļ.	\downarrow	<u>Ļ</u> .	100		Ļ.			Ĺ.			
		G2		5.0	n organic soil pockets,		5		5	30	60								
-																			
-	l ''																		
	P G1 0.0 221.6 SP- SM SM SP Sed-brown poorly-graded SAND with silt and gravel (SP-SM), no structure, no odor Red-brown to tan poorly-graded SAND (SP), bedded, no odor, dry - FILL - 5 P G2 5.0 10.0 5.0 ML Dark brown sandy SILT (ML) with dark brown organic soil pockets, occasional wood pieces (from tree?) -FILL-																		
-																			
- 10 -				212.0	FION 10.0 ET														
				10.0															
						n.													
		W	ater Le	evel Dat	a			Sample ID	Well Diagram			Sur	nma	ary					
l D	ate	Time		osed		h (ft) Botton	-	O - Open End Rod	Riser Pipe Screen	Overbur	der	n (1	ft)		10.0	0			
$oxed{oxed}$			Time			of Hole		T - Thin Wall Tube U - Undisturbed Sample	Filter Sand	Rock Co		d (1	ft)		0.0)			
								S - Splitspoon Sample G - Geoprobe	Grout	Samples	3		C	32	_				
		G - Geoprobe Concrete Bentonite Seal Boring No. GP-22																	
Field	d Tests	:					S - Slow M - Mediu	N - None	city: N - Nonplastic L - Low rength: N - None L - Low N	M - Medi 1 - Mediur	um n l	H H - H	- Hig High	h _V -	<u>V</u> er	<u>y</u> Hic	 ah		

Note: Maximum particle size is determined by direct observation within the limitations of sampler size.

Note: Soil identification based on visual-manual methods of the USCS as practiced by Haley & Aldrich, Inc.

Project Care	Н		Y	Н				GEO	PROBE REPOR	Γ			Во	rin	ıg N	No.	1	G	P-2	23	
Type	Clie	ent	GF	RANB	Y PUBLI	C SCF			FIELD AND TRACK, GRA	NBY, CT		Sh	neet). 1 2	of 25 J	1 lune	20:			
Type					Casing	Sam	oler	Barrel	Drilling Equipment	and Procedures									25		
Bill Types Geoprobe Spoon Dilayamater (In.) Substitution	Тур	e				G		_	Rig Make & Model: Geo	probe 7822DT									son		
Hammer Weight (b) -			meter	(in.)	_	1.5	5	_		oon					1						
Figure Face	Han	nmer V	Veight	(lb)	-	AU	го	-	Casing: Push						S						
Time	Han		-all (in	.)	-	-		-													
Time	(£)	lows I.	No.	e Ê	(E)	loqu		VISU	JAL-MANUAL IDENTIFICATION	N AND DESCRIPTION			1	1	1 _		Г				st
Time	oth (ler B r 6 in	ple I ec. (i	mpl oth (ratun nange Depth	Syr						arse	l e	arse	diun	<u>e</u>	sət	ancy	hnes	icity	gth
Time	De	samp pe	Sam & Re	Ss	 	JSC8			structure, odor, moisture, option GEOLOGIC INTERPRI	onal descriptions ETATION)		S %	% Fir	ပိ %	W We	% Fir	% Fir	Dilate	Toug	Plast	Stren
S H S S S S S S S S S S S S S S S S S S	- 0 -			0.0					-TRACK RUBBER AND	ASPHALT-										Ē	Ë
H Water Level Data Date Time Elapsed Depth (ff) to: Time (hr. Bottom Storem others other	-			5.0	221.0					ND with silt and gravel (GV	V-							Ш		L	
- 5 - P G2 5.0 10.0					1.0	SP	\		- FILL -		/		10	23	20	40					
Water Level Data Date Time Elapsed Depth (ft) to: Gasing of Hole Time (ft) Gasing of Hole T							ı	brown to	tan poorly-graded SAND with (gravel (SP), bedded, no od	lor,	ı									
Note: Exploration backfilled upon completion. Sample ID Well Diagram Summary	-								- GLACIOFLUVIAL DE	POSITS -		ı									
Note: Exploration backfilled upon completion. Sample ID Well Diagram Summary	-											ı									
Note: Exploration backfilled upon completion. Sample ID Well Diagram Summary	- 5 -																				
Water Level Data Date Time Elapsed Time (hr. of Casing of Hole) Time (hr. of Casing of Hole) Distance: R. Rapid S. Silow N. None Plasticity: N. Nonpaistric Seal Field Tests: Distance: R. Rapid S. Silow N. None Plasticity: N. Nonpaistric Seal BOTTOM OF EXPLORATION 10.0 FT Note: Exploration backfilled upon completion. BOTTOM OF EXPLORATION 10.0 FT Note: Exploration backfilled upon completion. BOTTOM OF EXPLORATION 10.0 FT Note: Exploration backfilled upon completion. Sample ID Well Diagram Size Pipe Size Pipe Size Pipe Concrete Size Pipe Size Pipe Concrete Size Pip			G2																		
BOTTOM OF EXPLORATION 10.0 FT Note: Exploration backfilled upon completion. Note: Exploration backfilled upon completion. Sample ID Well Diagram Summary S	-	S																			
Water Level Data Date Time Time Time (hr., of Casing of Hole of Casing of Hole Field Tests: Dilatancy: R. Rapid S - Slow N. None Note: Exploration backfilled upon completion. Note: Exploration backfilled upon completion. Note: Exploration backfilled upon completion backfilled upon completion. Note: Exploration backfilled upon completion backfilled upon completion backfilled upon completion backfilled upon completion. Note: Exploration backfilled upon completion b	F								ı												
Water Level Data Date Time Time Time (hr., of Casing of Hole of Casing of Hole Field Tests: Dilatancy: R. Rapid S - Slow N. None Note: Exploration backfilled upon completion. Note: Exploration backfilled upon completion. Note: Exploration backfilled upon completion backfilled upon completion. Note: Exploration backfilled upon completion backfilled upon completion backfilled upon completion backfilled upon completion. Note: Exploration backfilled upon completion b	_																				
Water Level Data Date Time Time Time (hr., of Casing of Hole of Casing of Hole Field Tests: Dilatancy: R. Rapid S - Slow N. None Note: Exploration backfilled upon completion. Note: Exploration backfilled upon completion. Note: Exploration backfilled upon completion backfilled upon completion. Note: Exploration backfilled upon completion backfilled upon completion backfilled upon completion backfilled upon completion. Note: Exploration backfilled upon completion b								ı													
Water Level Data Date Time Time Time (hr., of Casing of Hole of Casing of Hole Field Tests: Dilatancy: R. Rapid S - Slow N. None Note: Exploration backfilled upon completion. Note: Exploration backfilled upon completion. Note: Exploration backfilled upon completion backfilled upon completion. Note: Exploration backfilled upon completion backfilled upon completion backfilled upon completion backfilled upon completion. Note: Exploration backfilled upon completion b												ı									
Water Level Data Date Time Elapsed Time Elapsed Time Casing Of Hole Of Of Of Casing Of Hole Of Of Of Of Casing Of Hole Of	- 10 -				212.0 10.0				BOTTOM OF EXPLORAT	ION 10.0 FT								H			
Water Level Data Date Time Elapsed Time Elapsed Time Casing Of Hole Of Of Of Casing Of Hole Of Of Of Of Casing Of Hole Of							Note	: Explorat	tion backfilled upon completion	1.											
Date Time Elapsed Depth (ft) to: O - Open End Rod T - Thin Wall Tube U - Undisturbed Sample S - Splitspoon Sample G - Geoprobe							•														
Date Time Elapsed Depth (ft) to: O - Open End Rod T - Thin Wall Tube U - Undisturbed Sample S - Splitspoon Sample G - Geoprobe											ı										
Date Time Elapsed Depth (ft) to: O - Open End Rod T - Thin Wall Tube U - Undisturbed Sample S - Splitspoon Sample G - Geoprobe																					
Date Time Elapsed Depth (ft) to: O - Open End Rod T - Thin Wall Tube U - Undisturbed Sample S - Splitspoon Sample G - Geoprobe																					
Date Time Elapsed Depth (ft) to: O - Open End Rod T - Thin Wall Tube U - Undisturbed Sample S - Splitspoon Sample G - Geoprobe																					
Date Time Elapsed Depth (ft) to: O - Open End Rod T - Thin Wall Tube U - Undisturbed Sample S - Splitspoon Sample G - Geoprobe																					
Date Time Elapsed Depth (ft) to: O - Open End Rod T - Thin Wall Tube U - Undisturbed Sample S - Splitspoon Sample G - Geoprobe																					
Date Time Elapsed Depth (ft) to: O - Open End Rod T - Thin Wall Tube U - Undisturbed Sample S - Splitspoon Sample G - Geoprobe																					
Date Time Elapsed Depth (ft) to: O - Open End Rod T - Thin Wall Tube U - Undisturbed Sample S - Splitspoon Sample G - Geoprobe																					
Date Time Elapsed Depth (ft) to: O - Open End Rod T - Thin Wall Tube U - Undisturbed Sample S - Splitspoon Sample G - Geoprobe											ı.										
Date Time Elapsed Depth (ft) to: O - Open End Rod T - Thin Wall Tube U - Undisturbed Sample S - Splitspoon Sample G - Geoprobe																					
Date Time Elapsed Depth (ft) to: O - Open End Rod T - Thin Wall Tube U - Undisturbed Sample S - Splitspoon Sample G - Geoprobe		1.4.	_4. •					T	M-II-D:		_	<u>L</u>	<u>_</u>			<u>_</u>	Щ		<u>_</u>	<u> </u>	
Time (hr.) Bottom of Casing Bottom of Hole U - Undisturbed Sample S - Splitspoon Sample G - Geoprobe S - Splitspoon Sample G - Geoprobe S - Splitspoon Sample G - Geoprobe S - Splitspoon Sample S - Splitspoon Sample G - Geoprobe S - Splitspoon Sample S - Splitspoon Sam	_			Flai			n (ft) t	to:		Riser Pipe	Overh						10 (
S - Splitspoon Sample G - Geoprobe S - Splitspoon Sample G - Geoprobe S - Splitspoon Sample G - Geoprobe S - Splitspoon Sample G - Grout S - Concrete Bentonite Seal S - Samples G - GP-23 Boring No. GP-23 Field Tests: Dilatancy: R - Rapid S - Slow N - None Plasticity: N - Nonplastic L - Low M - Medium H - High		ate	lime		hr Bo	ottom	Bottom	Water	T - Thin Wall Tube	 				-							
Field Tests: Dilatancy: R - Rapid S - Slow N - None Plasticity: N - Nonplastic L - Low M - Medium H - High						-3			S - Splitspoon Sample	ি প্র ্র Cuttings											
Field Tests: Dilatancy: R - Rapid S - Slow N - None Plasticity: N - Nonplastic L - Low M - Medium H - High									G - Geoprobe	Concrete	Boriı	ng	N	ο.			GI	-2	3		
	Field	d Tests	: :							ity: N - Nonplastic L - Low											

[†] Note: Maximum particle size is determined by direct observation within the limitations of sampler size.

Note: Soil identification based on visual-manual methods of the USCS as practiced by Haley & Aldrich, Inc.

Н		Y	Н				GEO	PROBE REPORT	Γ		ı	Во	rin	g N	lo.		GI	P-2	4	
Clie	ject ent ntracto	GR	ANBY	' PUBLI ' PUBLI BSURF	C SCF			FIELD AND TRACK, GRA	NBY, CT		Sh St	eet art	No		of 5 J	1 une	202			
				Casing	Sam	pler	Barrel	Drilling Equipment	and Procedures		ı	nish iller		ے B. V			202	23		
	de Dia	meter	` ′	-	G 1.	5	-	Rig Make & Model: Geor Bit Type: Geoprobe Spo Drill Mud: None			Εŀ	&A F eva atun	tion		22	2.5	bins (es			
	nmer I	Veight Fall (in.	` ′	-	AU ⁻	го	-	Casing: Push Hoist/Hammer: Winch A PID Make & Model: Not				cat			ee l	Plar				
Depth (ft)	Sampler Blows per 6 in.	Sample No. & Rec. (in.)	Sample Depth (ft)	Stratum Change Elev/Depth (ft)	USCS Symbol		VISL	JAL-MANUAL IDENTIFICATION (Color, GROUP NAME, max structure, odor, moisture, optic GEOLOGIC INTERPRE	a. particle size [†] , onal descriptions		% Coarse	% Fine	% Coarse	% Medium	% Fine	% Fines		Longhness a		
- 0 -	P U	G1	0.0 5.0	222.1 0.4	SP-	Dork	arov to a	-TRACK RUBBER AND ray-brown poorly-graded SANE		SM)	10	20	20	20	20	10				
-	S		5.0	221.5 1.0	SM		ructure, n		J with silt and graver (OF -	SIVI), /			l	25						
-	Н				SP	\		- FILL -												
						Red- dry	brown to	tan poorly-graded SAND with ເ	gravel (SP), bedded, no o	dor,										ĺ
-						ury		- GLACIOFLUVIAL DE	POSITS -											
- 5 - - -	- GLACIOFLUVIAL DEPOSITS - P G2 5.0 U S H																			
- - 10 - - -	U S H																			
-				207 5	SP	Red	to red-bro	wn poorly-graded SAND with o	gravel (SP), no structure,	no					100					
- 15 -				15.0		odor,	dry	BOTTOM OF EXPLORAT	ION 15.0 FT	/										
		Wa		evel Data		180		Sample ID	Well Diagram			5	Sum	nma	ry					_
D	ate	Time	Elap Time	(hr Bo	ottom	h (ft) t Bottom of Hole	Water	O - Open End Rod T - Thin Wall Tube	Riser Pipe Screen Filter Sand	Overl Rock			•	•		15.0 0.0				
				5, 0	20119	<u> </u>		U - Undisturbed Sample S - Splitspoon Sample	ির Cuttings	Samp			ν	G		J.U				
								G - Geoprobe	Grout Concrete Bentonite Seal	Bori						GF	P-2	4		
Field	d Tests	:		Dilatano Toughn	cy: R- less: L	Rapid - <u>Low</u>	S - Slow M - Mediu		ity: N - Nonplastic L - Lov ength: N - None L - Low							<u>Ve</u> rv	/ Hig	h_		
† No	ote: Ma	eximum No	particl	e size is	determ	ined by	direct ol	oservation within the limitation sual-manual methods of th	ns of sampler size.											

GEOPROBE REPORT										Boring No. GP-25													
Project GRANBY PUBLIC SCHOOLS- TURF FIELD AND TRACK, GRANBY, CT Client GRANBY PUBLIC SCHOOLS Contractor G&M SUBSURFACE												File No. 0206711-001 Sheet No. 1 of 1 Start 25 June 2025 Finish 25 June 2025											
			(Casing	Sam	pler	Barrel	Drilling Equipment	and Procedures		Finish 25 June 2025 Driller B. Wilson												
Тур	е			-	G	i	-	Rig Make & Model: Geor			Н8	kA F	Rep).	E.	Ro	bins	son					
Insid	de Dia	meter	(in.)	-	1.4	5	-	Bit Type: Geoprobe Spo Drill Mud: None	oon				tion	l			(e:	st.)					
Han	nmer \	Weight	(lb)	-	AU ⁻	го	-	Casing: Push	Casing: Push				Datum NAVD88 Location See Plan										
Han		Fall (in	.)	-	-		-	Hoist/Hammer: Winch A PID Make & Model: Not															
£	Sampler Blows per 6 in.	No.	e Ê	Stratum Change Elev/Depth (ft)	Symbol		VISU	JAL-MANUAL IDENTIFICATION	N AND DESCRIPTION		 	vel	_	Sand	t			ield σ	Tes	st .			
Depth (ft)	ler B r 6 in	ple l	Sample Depth (ft)	ratun nange Depti	Syn			(Color, GROUP NAME, max			Coarse	e	Coarse	Medium	e	səı	ıncy	hnes	city	gth			
Dep	amp	Sample No. & Rec. (in.)	Sa Der	g Ω []	nscs			structure, odor, moisture, optio GEOLOGIC INTERPRE	onal descriptions ETATION)		°C %	% Fine	% Co	% Me	% Fine	% Fines	Dilatancy	Toughness	Plasticity	Strength			
- 0 -	υ P	G1	0.0	222.2 0.3				-TRACK RUBBER AND	ASPHALT-										_	0,			
_	U S		5.0	221.5	SP- SM		gray to g ructure, n	ray-brown poorly-graded SANI	O with silt and gravel (SP-	-SM),				20		10							
	H			1.0	SP	\		- FILL -		/	0	0	10	40	50								
-								tan poorly-graded SAND (SP), raded bedding coarse to fine s		ice													
-							,, 9	- GLACIOFLUVIAL DE															
-								- GLACIOI LOVIAL DE	00110 -														
- 5 -	P	G2	5.0	1																			
-	U S		10.0																				
	Н																						
-																							
-																							
- 10 -																							
10	P U	G3	10.0 15.0																				
-	S H		10.0																				
-																							
-																							
- 15 -				207.5 15.0				BOTTOM OF EXPLORAT	ION 15 0 ET														
				13.0																			
						Note	: Explorat	ion backfilled upon completion	1.														
		10/-	nter! -	Vol Dat				01-75	Well Diagram				21	ıma	n.								
Dat -		Water Level Dat			Dept	h (ft) 1		Sample ID O - Open End Rod	Riser Pipe	Over	bur					15.0)						
Date		Time	Time	(hr Bo	ttom	Bottom of Hole	n Water	T - Thin Wall Tube	Screen Filter Sand	Rock			•	′		0.0							
								U - Undisturbed Sample S - Splitspoon Sample	Cuttings Grout	Sam			•	G									
G - Geoprobe					G - Geoprobe	Concrete	Bori	ng	No).			GI	P-2	5								
Field	d Tests	: :		Dilatano	y : R-	Rapid	S - Slow		Bentonite Seal ity: N - Nonplastic L - Lo														
† No	ote: Ma	aximum	particl	e size is	determ	ined b	y direct ol	oservation within the limitation	ength: N - None L - Low ns of sampler size.							very	/ Hig	n		_			
Щ		No	te: S	oil iden	<u>tificati</u>	on bas	sed on vi	sual-manual methods of th	e USCS as practiced b	y Hale	<u>y &</u>	Ald	Iric	h, Ir	IC.								

GEOPROBE REPORT										Boring No. GP-26													
Project GRANBY PUBLIC SCHOOLS- TURF FIELD AND TRACK, GRANBY, CT Client GRANBY PUBLIC SCHOOLS Contractor G&M SUBSURFACE												File No. 0206711-001 Sheet No. 1 of 1 Start 25 June 2025 Finish 25 June 2025											
			(Casing	Sam	pler Barrel Drilling Equipment and Procedures					Finish 25 June 2025 Driller B. Wilson												
Тур	е			-	G		-	Rig Make & Model: Geo			Н	&A F	Rep).	E.	Ro	bins	son					
Insi	de Dia	meter	(in.)	-	1.5	5	-	Bit Type: Geoprobe Spo Drill Mud: None	oon			eva		1			es	st.)					
Han	nmer \	Veight	(lb)	-	AU	го	-	Casing: Push					Datum NAVD88 Location See Plan										
Har		all (in	.)	-	-		-	PID Make & Model: Not			Gravel Sand Field Test												
Œ	Sampler Blows per 6 in.	No.)	æ Œ	Stratum Change Elev/Depth (ft)	Symbol		VISU	JAL-MANUAL IDENTIFICATION	N AND DESCRIPTION			avel	1	San	_			SS					
Depth (ft)	pler E er 6 i	Sample No. & Rec. (in.)	Sample Depth (ft)	tratu Shang /Depi	SSy			(Color, GROUP NAME, max structure, odor, moisture, opti			Coarse	Fine	% Coarse	% Medium	ine	% Fines	Dilatancy	Toughness	Plasticity	Strength			
	Sam	Sar & F	S	S	nscs			GEOLOGIC INTERPRI	ETATION)		S %	% F	S %	№ №	% Fine	% F	Dila	Tou	Plas	Stre			
- 0 -	P U	G1	0.0		SP-			ray-brown poorly-graded SAN	D with silt and gravel (SP-	SM),	10	20	20	20	20	10							
-	S		5.0	221.5 1.0	SM	no s	tructure, n	o odor		/	0	0	10	40	50	\vdash							
-	H					Red	-brown to	- FILL - tan poorly-graded SAND (SP)	hedded no odor dry tra	ce													
								raded beds, coarse grain on to		00													
								- GLACIOFLUVIAL DE	POSITS -														
F																							
- 5 -	Р	G2	5.0	1																			
-	U S		10.0																				
	H																						
-																							
-																							
- 10 -				212.5 10.0																			
				10.0				BOTTOM OF EXPLORAT															
						Note	: Explorat	ion backfilled upon completior	1.														
L	<u> </u>					<u> </u>								<u> </u>			\bigsqcup			L			
Water Level Data Sample ID Well Diagram Pate Time Elapsed Depth (ft) to: O - Open End Rod Riser Pipe										nma													
Date		Time	Elap	(hr Bo	ottom	Bottom Water		O - Open End Rod T - Thin Wall Tube	Screen	Overl Rock			•	•		10.0							
				Or C	Casing	of Hole		U - Undisturbed Sample S - Splitspoon Sample	Filter Sand Cuttings	Samp			(11	G		0.0							
								G - Geoprobe	Grout Concrete	Bori) .			GF	P-2	6					
Fiel	d Tests	 :		Dilatan	cy: R-	Rapid	S - Slow		Bentonite Seal ity: N - Nonplastic L - Lov	v M - N	1edi	um	Н-			<u> </u>							
L.		aximum		e size is	determ	ined b	y direct o	oservation within the limitation								Very	/ Hig	h					
Щ		No	te: S	oil iden	tificati	on ba	sed on vi	sual-manual methods of th	e USCS as practiced b	y Hale	y &	Alc	Iric	h, Ir	ıc.								

Fig. Contractor Cashae Public Schools Turk FletD AND TRACK, GRANBY, CT Stat Schools Schools Stat Schools	GEOPROBE REPORT										Boring No. GP-27																
Type	Client GRANBY PUBLIC SCHOOLS												Sheet No. 1 of 1 Start 25 June 2025														
Inside Diameter (in.)	Casing Sampler Barrel Drilling Equipment and Procedures											1 1111311															
Hammer Weight (tib) AUTO - Casing Push Hammer Fall (in) Casing Push Ha			meter	(in.)	-		G - Rig Make & Model: Geoprobe 7822DT Bit Type: Geoprobe Spoon						Elevation 222.0 (est.)														
P		nmer I	J	` '	-	-	ГО	Casing: Push Hoist/Hammer: Winch Automatic hammer							Location See Plan												
P	£	ows	л.) Г.)	e £	£ (#)	loqu		VISU	JAL-MANUAL IDENTIFICATION	N AND DESCRIPTION			ivel	_		t				Tes	st						
S		Sampler B per 6 in	Sample I & Rec. (i	Sampl Depth (Stratun Change Elev/Depth	USCS Syr			structure, odor, moisture, optic	onal descriptions		% Coarse	% Fine	% Coarse	% Medium	% Fine	% Fines	Dilatancy	Toughnes	Plasticity	Strength						
Red-brown to tan poorly-graded SAND with gravel (SP), bedded, no odor, dry, trace SP Red-brown to tan poorly-graded SAND (SP), bedded, no odor, dry, trace SP Red-brown to tan poorly-graded SAND (SP), bedded, no odor, dry, trace SP Red-brown to tan poorly-graded SAND (SP), bedded, no odor, dry, trace SP Red-brown to tan poorly-graded SAND (SP), bedded, no odor, dry, trace O 0 10 40 50 BOTTOM OF EXPLORATION 10.0 FT Note: Exploration backfilled upon completion. Well Diagram Riser Fipe Screen Screen File Sand Screen File S	-	U S	G1		221.0 1.0	SM		0 , 0	, , , ,	O with silt and gravel (SP-	SM),		l				10										
SP Red-brown to tan poorly-graded SAND (SP), bedded, no odor, dry, trace 0 0 10 40 50 clayey sand SP Red-brown to tan poorly-graded SAND (SP), bedded, no odor, dry, trace 0 0 10 40 50 layey sand BOTTOM OF EXPLORATION 10.0 FT Note: Exploration backfilled upon completion. Sample ID Well Diagram Size Pipe Seven Consider Saven Conside	-					J.		Red-brown to tan poorly-graded SAND with gravel (SP), bedded, no odor,																			
Water Level Data Date Time Elapsed Depth (ft) to: Time (r) Gasing of Hole Gasing	=								- GLACIOFLUVIAL DE	POSITS -																	
The letter of Casing of Hole Clayey sand	- 5 - -	U S	G2																								
Note: Exploration backfilled upon completion. Note: Exploration backfilled upon completion.	-					SP	1 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7								40	50											
Water Level Data Date Time Elapsed Depth (ft) to: Time (hr. Bottom of Casing of Hole Time (hr. Bottom Bottom Of Hole Time (hr. Bottom Bottom Bottom Of Hole Time (hr. Bottom Bottom Bottom Of Hole Time (hr. Bottom Botto	- 10 -				212.0 10.0				BOTTOM OF EXPLORAT	TION 10.0 FT																	
Field Tests: Dilatancy: R - Rapid S - Slow N - None Toughness: L - Low M - Medium H - High Dry Strength: N - None L - Low M - Medium H - High Dry Strength: N - None L - Low M - Medium H - High V - Very High	D	ate		Elap	evel Dat	Depti	n (ft)	to:	Sample ID O - Open End Rod T - Thin Wall Tube U - Undisturbed Sample S - Splitspoon Sample	Well Diagram Riser Pipe Screen Filter Sand Cuttings Grout	Rock Samp	Cooles	den red	(ft)	1	0.0		7								
Toughness: L - Low M - Medium H - High Dry Strength: N - None L - Low M - Medium H - High V - Very High † Note: Maximum particle size is determined by direct observation within the limitations of sampler size.	Field	d Tests	 ::		Dilatan	cy: R-	Rapid	S - Slow		Bentonite Seal ity: N - Nonplastic L - Lov	v M - N	1ediu	ım	Н-													
	L		aximum		Toughn e size is	ess: L determ	- Low ined b	M - Mediu y direct ol	m H - High Dry Str bservation within the limitation	ns of sampler size.							Very	/ Hig	h								